

# MEP Constructors for Buildings and Spaces

## Contents

- Ceiling:

- [8 in lightweight concrete ceiling](#)
- [4 in reinforced-concrete ceiling](#)
- [Carpeted 4 in reinforced-concrete ceiling](#)
- [8 in reinforced-concrete ceiling](#)
- [5 in reinforced-concrete ceiling \(screeded\)](#)
- [5 in concrete ceiling](#)
- [5 in concrete ceiling \(screeded\)](#)
- [1/2 in plaster with TG boards on 16 in joist centers](#)
- [Plaster, wood boards, glass wool on joists](#)
- [12 in reinforced-concrete ceiling](#)
- [2 in screed, 6 in cast concrete](#)
- [Wood blocks, screed, 6 in concrete](#)
- [Wood blocks, concrete, batting, gypsum](#)
- [Wood blocks, concrete, batting, metal deck tray](#)
- [Concrete slab internal](#)
- [Timber-joist internal](#)
- [Timber-joist internal - industry](#)
- [2in heavyweight concrete with false ceiling](#)
- [4 in heavyweight concrete with false ceiling](#)
- [4 in lightweight concrete with false ceiling](#)
- [8 in heavyweight concrete with false ceiling](#)
- [8 in lightweight concrete with false ceiling](#)
- [2 in wood deck with false ceiling](#)
- [3in wood deck with false ceiling](#)
- [12 in heavyweight concrete with false ceiling](#)
- [4 in wood deck with false ceiling](#)
- [Steel deck with false ceiling](#)
- [Ceiling below joists, no insulation](#)
- [Ceiling below joists, R-2 board insulation](#)
- [Ceiling below joists, R-3 board insulation](#)
- [Ceiling below joists, R-4 board insulation](#)
- [Ceiling below joists, R-5 board insulation](#)
- [Ceiling below joists, R-6 board insulation](#)
- [Ceiling below joists, R-8 board insulation](#)
- [Ceiling below joists, R-10 board insulation](#)
- [Ceiling below joists, R-11 blanket or loose fill](#)
- [Ceiling below joists, R-13 blanket or loose fill](#)
- [Ceiling below joists, R-15 blanket or loose fill](#)
- [Ceiling below joists, R-19 blanket or loose fill](#)
- [Ceiling below joists, R-21 blanket or loose fill](#)
- [Ceiling below joists, R-30 blanket or loose fill](#)
- [Ceiling below joists, R-38 blanket or loose fill](#)
- [Exposed beams, 1 1/2 in wood, no insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-2 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-3 insulation](#)
- [Exposed beams, 2 in cement-fiber slab, no insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-4 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-5 insulation](#)

- Exposed beams, 3 in cement-fiber slab, no insulation
- [Exposed beams, 1 1/2 in wood plus R-6 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-7 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-10 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-12 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-15 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-17 to R-18 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-20 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-21 to R-23 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-24 to R-26 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-27 to R-29 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-30 to R-32 insulation](#)
- [Exposed beams, 1 1/2 in wood plus R-33 to R-35 insulation](#)
- [Wood block, concrete, plasterboard](#)

- **ExteriorWall:**

- [Standard wall construction - A](#)
- [Standard wall construction - B](#)
- [Standard wall construction - C](#)
- [Brick / block wall](#)
- [Timber-frame wall](#)
- [Lightweight curtain wall](#)
- [Metal-clad wall](#)
- [Brick / block wall](#)
- [Brick / block wall](#)
- [Timber-frame wall](#)
- [Brick / block wall](#)
- [Lightweight concrete-clad wall](#)
- [Brickwork single-leaf construction dense plaster](#)
- [Brickwork single-leaf construction light plaster](#)
- [Un-insulated brick/block wall](#)
- [Super-insulated external wall](#)
- [Sheet steel](#)
- [Sheet aluminum](#)
- [Brickwork single-leaf construction with insulation and plaster](#)
- [Brickwork single-leaf construction fiber insulation and render](#)
- [Brickwork single-leaf construction EPS insulation and render](#)
- [Lightweight concrete block air gap and plasterboard](#)
- [Lightweight concrete block GRP insulation and plasterboard](#)
- [Lightweight concrete block poly-insulation and plasterboard](#)
- [Brick cavity with dense plaster](#)
- [Brick cavity with mineral insulation and lightweight plaster](#)
- [Brick cavity full mineral insulation and lightweight plaster](#)
- [Brick cavity with UF foam insulation and lightweight plaster](#)
- [Brick, heavy concrete block, phenolic foam, light plaster](#)
- [Brick, heavy concrete block, mineral insulation, light plaster](#)
- [Brick, medium concrete block, foam insulation, light plaster](#)
- [Brick, light concrete block, foam insulation, light plaster](#)
- [Brick, light concrete block, light plaster](#)
- [Brick, foam insulation, light concrete block, light plaster](#)
- [Brick, mineral insulation, light concrete block, light plaster](#)
- [Face brick, insulation, light concrete block](#)
- [4in lightweight concrete](#)
- [4 in face brick, 8 in common brick](#)
- [4 in face brick, 8 in heavyweight concrete block](#)
- [4 in face brick, 8 in lightweight concrete block](#)
- [4 in face brick air space and 8 in clay tile](#)
- [4 in face brick air space and 2 in heavyweight concrete](#)

- [4 in face brick air space and 4 in common brick](#)
- [4 in face brick air space and 4 in heavyweight concrete block](#)
- [4 in face brick air space and 4 in lightweight concrete block](#)
- [12 in heavyweight concrete](#)
- [8 in heavyweight concrete with 2 in insulation](#)
- [8 in heavyweight concrete with 1 in insulation](#)
- [8 in heavyweight concrete with air space](#)
- [8 in heavyweight concrete](#)
- [4 in face brick 8 in common brick with 1 in insulation](#)
- [4 in face brick 8 in common brick with air space](#)
- [4 in face brick air space and 4 in lightweight block](#)
- [Wall with 3 in fiberglass insulation and stucco outside finish](#)
- [Two-sided brick wall with air space](#)
- [Brick wall 8 in concrete block and no air space](#)
- [Brick wall with 4 in concrete block](#)
- [Brick wall with 8 in concrete block](#)
- [Brick wall with 6 in concrete](#)
- [Frame wall with 2 in insulation and 4 in brick veneer](#)
- [Frame wall with 2 in insulation](#)
- [Metal curtain wall with 3 in insulation](#)
- [Metal curtain wall with 2 in insulation](#)
- [Metal curtain wall with 1 in insulation](#)
- [Wall 12 in concrete with 2 in insulation on the outside](#)
- [Wall 8 in concrete with 2 in insulation on the outside](#)
- [Wall 4 in concrete with 2 in insulation on the outside](#)
- [Wall 12 in concrete with 2 in insulation on the inside](#)
- [Wall 8 in concrete with 2 in insulation on the inside](#)
- [Wall 4 in concrete with 2 in insulation on the inside](#)
- [Frame wall with 3 in insulation](#)
- [Frame wall with 2 in insulation](#)
- [Frame wall with 1 in insulation](#)
- [Frame wall without insulation](#)
- [2 in insulation with 12 in heavyweight concrete](#)
- [2 in insulation with 8 in heavyweight concrete](#)
- [2 in insulation with 8 in common brick](#)
- [2 in insulation with 8 in heavyweight concrete block](#)
- [2 in insulation with 8 in lightweight concrete block](#)
- [2 in insulation with 8 in clay tile](#)
- [2 in insulation with 4 in heavyweight concrete](#)
- [2 in insulation with 4 in common brick](#)
- [2 in insulation with 4 in heavyweight concrete block](#)
- [2 in insulation with 4 in lightweight concrete block](#)
- [2 in insulation with 4 in clay tile](#)
- [4 in face brick, 2 in insulation, 12 in heavy concrete](#)
- [4 in face brick, 2 in insulation, 8 in heavy concrete](#)
- [4 in face brick 2 in insulation and 8 in common brick](#)
- [4 in face brick air space and 12 in heavyweight concrete](#)
- [4 in face brick air space and 8 in heavyweight concrete](#)
- [4 in face brick, 2 in insulation, 8 in heavy concrete block](#)
- [4 in face brick, 2 in insulation, 8 in light concrete block](#)
- [2 in face brick 2 in insulation and 8 in clay tile](#)
- [4 in face brick 2 in insulation and 4 in heavyweight concrete](#)
- [4 in face brick 2 in insulation and 4 in common brick](#)
- [4 in face brick, 2 in insulation, 4 in heavy concrete block](#)
- [4 in face brick with 8 in common brick](#)
- [8 in heavyweight concrete block with 1 in insulation](#)
- [8 in heavyweight concrete block](#)

- [8 in lightweight concrete block with insulation](#)
- [8 in lightweight concrete block](#)
- [4 in face brick 8 in clay tile and 1 in insulation](#)
- [4 in face brick 8 in clay tile and air space](#)
- [4 in face brick with 8 in clay tile](#)
- [8 in clay tile with 1 in Insulation](#)
- [8 in clay tile with air space](#)
- [8 in clay tile](#)
- [4 in heavyweight concrete with 2 in insulation](#)
- [4 in heavyweight concrete with 1 in insulation](#)
- [4 in heavyweight concrete with air space](#)
- [4 in heavyweight concrete](#)
- [4 in face brick 4 in common brick and 1 in insulation](#)
- [4 in face brick 4 in common brick and air space](#)
- [4 in face brick with 4 in common brick](#)
- [4 in common brick](#)
- [4 in heavyweight concrete block](#)
- [4 in face brick, 4 in light concrete block, 1 in insulation](#)
- [4 in face brick 4 in lightweight concrete block and air space](#)
- [4 in face brick with 4 in lightweight concrete block](#)
- [4 in lightweight concrete block and 1 in insulation](#)
- [4 in lightweight concrete block and air space](#)
- [4 in lightweight concrete block](#)
- [4 in face brick 4 in clay tile and 1 in insulation](#)
- [4 in face brick 4 in clay tile and air space](#)
- [4 in face brick and 4 in clay tile](#)
- [4 in clay tile and 1 in insulation](#)
- [4 in clay tile and air space](#)
- [4 in clay tile](#)
- [Sheet metal with 1 in insulation](#)
- [Sheet metal with 2 in insulation](#)
- [Sheet metal with 3 in insulation](#)
- [4 in insulation with 8 in lightweight concrete block](#)
- [6 in insulation with 8 in lightweight concrete block](#)
- [4 in insulation with 8 in clay tile](#)
- [6 in insulation with 8 in clay tile](#)
- [8 in heavyweight concrete with 4 in insulation](#)
- [8 in heavyweight concrete with 6 in insulation](#)
- [4 in insulation with 8 in common brick](#)
- [6 in insulation with 8 in common brick](#)
- [Frame wall with 6 in insulation](#)
- [Frame wall with 8 in insulation](#)
- [Sheet metal with 6 in insulation](#)
- [Sheet metal with 8 in insulation](#)
- [Frame wall with 6 in insulation and 4 in brick veneer](#)
- [Frame wall with 12 in insulation and 4 in brick veneer](#)
- [4 in face brick](#)
- [Metal curtain wall with 3 in insulation](#)
- [Metal curtain wall with 2 in insulation](#)
- [Metal curtain wall with 1 in insulation](#)
- [Wall 12 in concrete with 2 in insulation on the outside](#)
- [Wall 8 in concrete with 2 in insulation on the outside](#)
- [Wall 4 in concrete with 2 in insulation on the outside](#)

- [4 in face brick with 2 in insulation](#)
- [Spandrel glass, R-10 insulation board, gyp board](#)
- [Metal wall panel, R-10 insulation board, gyp board](#)
- [Metal wall panel, sheathing, R-11 batt insulation, gyp board](#)
- [1 in stone, R-10 insulation board, gyp board](#)
- [1 in stone, sheathing, R-11 batt insulation, gyp board](#)
- [1 in stucco, sheathing, R-11 batt insulation, gyp board](#)
- [1 in stucco, 8 in heavyweight CMU, R-11 batt insulation, gyp board](#)
- [Wood siding, sheathing, batt insulation, 1/2 in wood](#)
- [EIFS finish, R-5 insulation board, sheathing, gyp board](#)
- [Synthetic stucco, R-5 plus R-11 insulation, gypsum board](#)
- [Synthetic stucco, insulation, sheathing, light concrete, gypsum](#)
- [Synthetic stucco, insulation, concrete, gypsum](#)
- [Synthetic stucco, insulation board, light concrete, gypsum](#)
- [Brick, R-5 insulation board, sheathing, gypsum](#)
- [Brick, sheathing, R-11 batt insulation, gypsum](#)
- [Brick, R-5 plus R-11 insulation with sheathing, gypsum](#)
- [Brick, R-5 insulation board, 8 in light-weight concrete block](#)
- [Brick, 8 in lightweight CMU, R-11 batt insulation, gyp board](#)
- [Brick, R-5 insulation board, 8 in heavyweight CMU, gyp board](#)
- [Brick, R-5 insulation board, brick](#)
- [Brick, R-5 insulation board, 8 in lightweight concrete, gyp board](#)
- [Brick, R-5 insulation board, 12 in heavyweight concrete, gyp board](#)
- [Brick, 8 in heavyweight concrete, R-11 batt insulation, gyp board](#)
- [4 in lightweight concrete, R-5 board insulation, gyp board](#)
- [4 in lightweight concrete, R-11 batt insulation, gyp board](#)
- [4 in lightweight concrete, R-10 board insulation, 4 in lightweight concrete](#)
- [8 in lightweight CMU, R-11 batt insulation, gyp board](#)
- [8 in concrete block, filled, R-11 insulation, gypsum](#)
- [8 in lightweight CMU with fill insulation](#)
- [8 in lightweight CMU with fill insulation, gyp board](#)
- [8 in lightweight concrete, R-11 batt insulation, gyp board](#)
- [8 in heavyweight concrete, R-11 batt insulation, gyp board](#)
- [12 in lightweight CMU with fill insulation, gyp board](#)
- [12 in heavyweight concrete, R-19 batt insulation, gyp board](#)
- [12 in heavyweight concrete](#)
- [R-0 8 in CMU wall](#)
- [R-20 8 in CMU wall](#)
- [R-0 wood frame wall](#)
- [R-11.4 8 in CMU wall](#)
- [R-13 + R10 metal frame wall](#)
- [R-13 + R13 metal frame wall](#)
- [R-13 + R3.8 wood frame wall](#)
- [R-13 + R7.5 wood frame wall](#)
- [R-13.3 8 in concrete](#)
- [R-15.2 8 in concrete](#)
- [R-5.7 8 in concrete](#)
- [R7.6 8 in concrete](#)
- [R9.5 8 in concrete](#)
- [R-0 8 in CMU under ground wall](#)
- [R7.5 8 in CMU under ground wall](#)
- [R-19 wood frame wall](#)
- [R-21 wood frame wall](#)
- [R-13 wood frame wall](#)
- [R-30 wood frame wall](#)
- [R-15 wood frame wall](#)
- [R-2.7 8 in CMU under ground wall](#)

- [R-4 8 in CMU under ground wall](#)
- [R-5.4 8 in CMU under ground wall](#)
- [R8.1 8 in CMU under ground wall](#)
- [R-10.8 8 in CMU under ground wall](#)
- [R-12.5 8 in CMU under ground wall](#)
- [R-11 wood frame wall](#)
- [R-19 8 in concrete](#)
- [R-38 wood frame wall](#)
- [R-11.4 8 in concrete](#)
- [R-13.3 8 in concrete](#)
- [R-15.2 8 in concrete](#)
- [R-13+3.8 wood frame wall](#)
- [R-13+7.5 wood frame wall](#)
- [R-0 metal frame wall](#)
- [R9 curtain wall](#)
- [R-11 UG ex-wall](#)
- [R-13 UG ex-wall](#)
- [R-15 UG ex-wall](#)
- [R-19 UG ex-wall](#)
- [R-30 8 in concrete](#)
- [8 in concrete wall with perlite filled cores](#)
- [8 in concrete wall with poured cores](#)
- [8 in concrete wall hollow](#)
- [8 in CMU with concrete poured concrete](#)
- [8 in CMU with perlite poured concrete](#)
- [Straw bale wall](#)
- [Insulated concrete form \(ICF\) wall, 10" thick form](#)
- [Insulated concrete form \(ICF\) wall, 12" thick form](#)
- [Insulated concrete form \(ICF\) wall, 14" thick form](#)
- [Structurally ins. panel \(SIP\) wall 4 1/2 in \(114 mm\)](#)
- [Structurally ins. panel \(SIP\) wall 6 1/2 in](#)
- [Structurally ins. panel \(SIP\) wall 8 1/4 in \(210 mm\)](#)
- [Structurally ins. panel \(SIP\) wall 10 1/4 in \(260 mm\)](#)
- [Structurally ins. panel \(SIP\) wall 12 1/4 in \(311 mm\)](#)
- [R-2 CMU wall](#)
- [R-13 wood frame wall](#)
- [R-11 metal frame wall](#)
- [R-13 metal frame wall](#)
- [R-15 metal frame wall](#)
- [R-19 metal frame wall](#)
- [R-30 metal frame wall](#)
- [R-13+R13 metal frame wall](#)
- [R-15+R15 metal frame wall](#)
- [R-38 metal frame wall](#)
- [R-13+3.8 metal frame wall](#)
- [R-13+7.5 metal frame wall](#)
- [R-3 8 in CMU wall](#)
- [R-4 8 in CMU wall](#)
- [R-6 8 in concrete block](#)
- [2 ft stone, 2 in airspace, 1 in dense plaster](#)
- [Stone, insulation, plasterboard](#)
- [Render, no-fines concrete, plasterboard](#)
- [Render, no-fines concrete, insulation, plasterboard](#)
- [Render, mineral fiber insulation, no-fines concrete, plasterboard](#)
- [9 in solid brick, 1/2 in dense plaster](#)
- [9 in solid brick, 1/2 in plasterboard](#)
- [9 in solid brick, mineral fiber insulation, plasterboard](#)

- [Render, insulation, solid brick, dense plaster](#)
- [Render, dense concrete block, dense plaster](#)
- [Render, dense concrete block, plasterboard](#)
- [Render, dense concrete block, insulation, plasterboard](#)
- [Render, insulation, dense concrete block, dense plaster](#)
- [Dense concrete, 1 in insulation, dense concrete, dense plaster](#)
- [Dense concrete, 1 in insulation, dense concrete, plasterboard](#)
- [Dense concrete, 2 in insulation, dense concrete, plasterboard](#)
- [Render, dense concrete, insulation, dense concrete, dense plaster](#)
- [Brick, air, brick, dense plaster](#)
- [Brick, air, brick, light-weight plaster](#)
- [Brick, foam insulation, brick, dense plaster](#)
- [Brick, blown fiber insulation, brick, dense plaster](#)
- [Brick, polystyrene insulation, brick, plasterboard](#)
- [Brick, air, dense concrete block, dense plaster](#)
- [Brick, foam insulation, dense concrete block, dense plaster](#)
- [Brick, blown fiber insulation, dense concrete, dense plaster](#)
- [Brick, polystyrene insulation, dense concrete, dense plaster](#)
- [Brick, air, light-weight concrete block, dense plaster](#)
- [Brick, foam insulation, light-weight concrete, dense plaster](#)
- [Brick, fiber insulation, light-weight concrete, dense plaster](#)
- [Brick, fiber insulation, light-weight concrete, dense plaster](#)
- [Brick, polystyrene insulation, light-weight concrete, dense plaster](#)
- [Brick, air, plywood sheathing, studding, plasterboard](#)
- [1/2 in dense plaster, 8 in brick, 1/2 in dense plaster](#)
- [1/2 in dense plaster, dense concrete block, 1/2 in dense plaster](#)
- [Brick, polystyrene insulation, light-weight concrete, dense plaster](#)
- [Brick, 4 in autoclaved aerated concrete block, light-weight plaster](#)
- [Brick, 6 in autoclaved aerated concrete block, light-weight plaster](#)
- [Brick, insulation, autoclaved aerated concrete block, plaster](#)
- [Brick, plywood, studding, 4 in insulation, plasterboard](#)
- [Brick, plywood, studding, 6 in insulation, plasterboard](#)
- [Plasterboard, concrete block, air, concrete block, plasterboard](#)

- InteriorFloor:

- [Wilton carpet on concrete](#)
- [Timber flooring, gypsum](#)
- [Timber flooring, batt, gypsum](#)
- [Timber flooring, batt, metal deck tray](#)
- [Timber flooring, joists, plasterboard ceiling](#)
- [Loft floor - domestic A](#)
- [Loft floor - domestic B](#)
- [2in heavyweight concrete floor deck](#)
- [4 in heavyweight concrete floor deck](#)
- [2 in lightweight concrete floor deck](#)
- [8 in heavyweight concrete floor deck](#)
- [2 in wood deck](#)
- [3in wood deck](#)
- [8 in lightweight concrete floor deck](#)
- [Passive floor, no insulation, tile or vinyl](#)
- [Passive floor, no insulation, carpet or hardwood](#)
- [Passive floor, R-2 board insulation, any cover](#)
- [Passive floor, R-3 board insulation, any cover](#)
- [Passive floor, R-4 board insulation, any cover](#)
- [Passive floor, R-5 board insulation, any cover](#)
- [Passive floor, R-6 board insulation, any cover](#)
- [Passive floor, R-7 board insulation, any cover](#)
- [Passive floor, R-8 board insulation, any cover](#)

- [Passive floor, R-9 board insulation, any cover](#)
- [Passive floor, R-10 board insulation, any cover](#)
- [Passive floor, R-11 board insulation, any cover](#)
- [Passive floor, R-13 board insulation, any cover](#)
- [Passive floor, R-15 board insulation, any cover](#)
- [Passive floor, R-19 board insulation, any cover](#)
- [Passive floor, R-21 board insulation, any cover](#)
- [Passive floor, R-30 board insulation, any cover](#)
- [Passive floor, R-38 board insulation, any cover](#)
- [Radiant floor, R-38 blanket insulation, any cover](#)
- [Radiant floor, R-11 blanket insulation, any cover](#)
- [Radiant floor, R-13 blanket insulation, any cover](#)
- [Radiant floor, R-15 blanket insulation, any cover](#)
- [Radiant floor, R-19 blanket insulation, any cover](#)
- [Radiant floor, R-21 blanket insulation, any cover](#)
- [Radiant floor, R-30 blanket insulation, any cover](#)
- [Screed, concrete, dense plaster](#)
- [Vinyl floor covering, screed, concrete](#)
- [Carpet underlay, screed, concrete](#)
- [Carpet, underlay, timber on joists, ventilated](#)
- [Carpet, underlay, screed, concrete, insulation, building board](#)
- [Vinyl, screed, concrete - A](#)
- [Vinyl, screed, concrete - B](#)
- [Vinyl, screed, insulation, concrete](#)
- [Vinyl, timber, insulation, concrete](#)
- [Vinyl, timber on joists, ventilated](#)
- [Vinyl, timber on joists, building board - A](#)
- [Vinyl, timber on joists, building board - B](#)
- [Vinyl, screed, concrete, 2 in insulation, building board](#)
- [Vinyl, screed, concrete, 4 in insulation, building board](#)
- InteriorWall:
  - [Light plaster, brick, light plaster](#)
  - [Light plaster, double brick, light plaster](#)
  - [Light plaster, heavy concrete block, light plaster](#)
  - [Light plaster, medium concrete block, light plaster](#)
  - [Light plaster, light concrete block, light plaster](#)
  - [Standard double gypsum with 4 in air gap](#)
  - [Standard double fiberboard with 4 in air gap](#)
  - [4 in single-leaf brick \(plastered both sides\)](#)
  - [8 in single-leaf brick \(plastered both sides\)](#)
  - [1 1/4 ft single-leaf brick \(plastered both sides\)](#)
  - [Solid breeze blocks \(plastered both sides\)](#)
  - [4in single-leaf brick](#)
  - [5in single-leaf brickwork \(plastered on one side\)](#)
  - [Aerated concrete blocks](#)
  - [Hollow concrete blocks](#)
  - [Insulated concrete form](#)
  - [Glass blocks](#)
  - [4 in reinforced concrete](#)
  - [9 in medium-weight concrete block](#)
  - [1 1/2 ft dense concrete](#)
  - [Polystyrene faced with hardboard on plasterboard](#)
  - [Expanded-wood chipboard](#)
  - [Block cavity wall with air gap \(plastered\)](#)
  - [Cast concrete cavity wall with air gap \(plastered\)](#)
  - [Brick cavity wall with air gap](#)
  - [Brick cavity wall \(plaster both sides\)](#)

- [Standard double plasterboard with insulation](#)
- [3/8 in plasterboard on studs](#)
- [1/2 in plasterboard on studs](#)
- [1/2 in plasterboard on studs with mineral fiber slab](#)
- [1/4 in plywood on studs](#)
- [3/8 in plywood on studs](#)
- [Asbestos wallboard on timber frame](#)
- [Domestic solid party wall](#)
- [Domestic lightweight party wall](#)
- [Lightweight plasterboard partition](#)
- [Solid partition](#)
- [4in clay tile with plaster](#)
- [Light-weight concrete block with plaster](#)
- [Heavy-weight concrete block with plaster](#)
- [4 in common brick with plaster](#)
- [Heavyweight concrete with plaster](#)
- [5in clay tile with plaster](#)
- [Light-weight concrete block plastered](#)
- [heavyweight concrete block plastered](#)
- [8 in common brick with plaster](#)
- [8 in heavy concrete with plaster](#)
- [12 in heavy concrete with plaster](#)
- [4 in clay tile](#)
- [Light-weight concrete block](#)
- [4 in heavyweight concrete block](#)
- [4 in common brick](#)
- [4 in heavyweight concrete](#)
- [8 in clay tile](#)
- [8 in lightweight concrete block](#)
- [8 in heavyweight concrete block](#)
- [8 in common brick](#)
- [8 in heavyweight concrete](#)
- [12 in heavyweight concrete](#)
- [Frame partition with 3/4 in gypsum board](#)
- [1 in wood](#)
- [2in wood](#)
- [3 in wood](#)
- [4 in wood](#)
- [Frame partition with 1 in wood](#)
- [2 in furniture](#)
- [3in furniture](#)
- [2 in heavyweight concrete](#)
- [Frame construction, wood sheathing, wood studs](#)
- [Frame construction, wood sheathing, metal studs](#)
- [Frame construction, R-2 board insulation, wood studs](#)
- [Frame construction, R-2 board insulation, metal studs](#)
- [Frame construction, R-3 board insulation, wood studs](#)
- [Frame construction, R-3 board insulation, metal studs](#)
- [Frame construction, R-4 board insulation, wood studs](#)
- [Frame construction, R-4 board insulation, metal studs](#)
- [Frame construction, R-5 board insulation, wood studs](#)
- [Frame construction, R-5 board insulation, wood studs](#)
- [Frame construction, R-6 board insulation, wood studs](#)
- [Frame construction, R-6 board insulation, metal studs](#)
- [Frame construction, R-11 insulation, wood studs](#)
- [Frame construction, R-11 insulation, metal studs](#)
- [Frame construction, R-11 plus R-2 insulation, wood studs](#)

- [Frame construction, R-11 plus R-2 insulation, metal studs](#)
- [Frame construction, R-11 and R-3 insulation, wood studs](#)
- [Frame construction, R-11 plus R-3 insulation, metal studs](#)
- [Frame construction, R-11 plus R-4 insulation, wood studs](#)
- [Frame construction, R-11 plus R-4 insulation, metal studs](#)
- [Frame construction, R-11 plus R-5 insulation, wood studs](#)
- [Frame construction, R-11 plus R-5 insulation, metal studs](#)
- [Frame construction, R-11 plus R-6 insulation, wood studs](#)
- [Frame construction, R-11 plus R-6 insulation, metal studs](#)
- [Frame construction, R-15 insulation, wood sheathing, wood studs](#)
- [Frame construction, R-15 insulation, wood sheathing, metal studs](#)
- [Frame construction, R-15 plus R-2 insulation, wood studs](#)
- [Frame construction, R-15 plus R-2 insulation, metal studs](#)
- [Frame construction, R-15 plus R-3 insulation, wood studs](#)
- [Frame construction, R-15 plus R-3 insulation, metal studs](#)
- [Frame construction, R-15 plus R-4 insulation, wood studs](#)
- [Frame construction, R-15 plus R-4 insulation, metal studs](#)
- [Frame construction, R-15 plus R-5 insulation, wood studs](#)
- [Frame construction, R-15 plus R-5 insulation, metal studs](#)
- [Frame construction, R-15 plus R-6 insulation, wood studs](#)
- [Frame construction, R-15 plus R-6 insulation, metal studs](#)
- [Frame construction, R-21 insulation, wood sheathing, wood studs](#)
- [Frame construction, R-21 insulation, wood sheathing, metal studs](#)
- [Frame construction, R-21 plus R-2 insulation, wood studs](#)
- [Frame construction, R-21 plus R-2 insulation, metal studs](#)
- [Frame construction, R-21 plus R-3 insulation, wood studs](#)
- [Frame construction, R-21 plus R-3 insulation, metal studs](#)
- [Frame construction, R-21 plus R-4 insulation, wood studs](#)
- [Frame construction, R-21 plus R-4 insulation, metal studs](#)
- [Frame construction, R-21 plus R-5 insulation, wood studs](#)
- [Frame construction, R-21 plus R-5 insulation, metal studs](#)
- [Frame construction, R-21 plus R-6 insulation, wood studs](#)
- [Frame construction, R-21 plus R-6 insulation, metal studs](#)
- [Siding, R-2 insulation, interior finish](#)
- [Siding, R-2 insulation, filled core, interior finish](#)
- [Siding, R-3 insulation, interior finish](#)
- [Siding, R-3 insulation, filled core, interior finish](#)
- [Siding, R-4 insulation, interior finish](#)
- [Siding, R-4 insulation, filled core, interior finish](#)
- [Siding, R-5 insulation, interior finish](#)
- [Siding, R-5 insulation, filled core, interior finish](#)
- [Siding, R-6 insulation, interior finish](#)
- [Siding, R-6 insulation, filled core, plus interior finish](#)
- [Siding, R-10 insulation, interior finish](#)
- [Siding, R-10 insulation, filled core, interior finish](#)
- [Siding, R-15 insulation, interior finish](#)
- [Siding, R-15 insulation, filled core, interior finish](#)
- [Block, interior/exterior finish, R-11 plus R-2 insulation](#)
- [Block, interior/exterior finish, R-11 plus R-2 insulation, filled](#)
- [Block, interior/exterior finish, R-11 plus R-3 insulation](#)
- [Block, interior/exterior finish, R-11 plus R-3 insulation, filled](#)
- [Block, interior/exterior finish, R-11 plus R-4 insulation](#)
- [Block, interior/exterior finish, R-11 plus R-4 insulation, filled](#)
- [Block, interior/exterior finish, R-11 plus R-5 insulation](#)
- [Block, interior/exterior finish, R-11 plus R-5 insulation, filled](#)
- [Block, interior/exterior finish, R-15 plus R-2 insulation](#)
- [Block, interior/exterior finish, R-15 plus R-2 insulation, filled](#)

- [Block, interior/exterior finish, R-15 plus R-3 insulation](#)
- [Block, interior/exterior finish, R-15 plus R-3 insulation, filled](#)
- [Block, interior/exterior finish, R-15 plus R-4 insulation](#)
- [Block, interior/exterior finish, R-15 plus R-4 insulation, filled](#)
- [Block, interior/exterior finish, R-15 plus R-5 insulation](#)
- [Block, interior/exterior finish, R-15 plus R-5 insulation, filled](#)
- [Block, interior/exterior finish, R-21 plus R-2 insulation](#)
- [Block, interior/exterior finish, R-21 plus R-2 insulation, filled](#)
- [Block, interior/exterior finish, R-21 plus R-3 insulation](#)
- [Block, interior/exterior finish, R-21 plus R-3 insulation, filled](#)
- [Block, interior/exterior finish, R-21 plus R-4 insulation](#)
- [Block, interior/exterior finish, R-21 plus R-4 insulation, filled](#)
- [Block, interior/exterior finish, R-21 plus R-5 insulation](#)
- [Block, interior/exterior finish, R-21 plus R-5 insulation, filled](#)
- [Light-weight plaster, brick, light-weight plaster](#)
- [Light-weight plaster, concrete block, light-weight plaster](#)
- [Plasterboard, timber studding, plasterboard](#)
- NonSlidingDoor:
  - [Wooden](#)
  - [Metal](#)
  - [Timber flush-panel hollow-core](#)
  - [Solid hardwood](#)
  - [Hollow core wood](#)
  - [Door - wood - hollow core - wood storm](#)
  - [Hollow core wood, metal storm](#)
  - [Solid core wood](#)
  - [Solid core wood, wood storm](#)
  - [Solid core wood, metal storm](#)
  - [Wood panel](#)
  - [Wood panel with wood storm](#)
  - [Wood panel, metal storm](#)
  - [Metal, fiberglass core](#)
  - [Metal, fiberglass core, storm](#)
  - [Wood frame with single clear glass](#)
  - [Metal frame with single clear glass](#)
  - [Wood frame, single glass door, glass storm](#)
  - [Metal frame, single glass door, glass storm](#)
  - [Wood frame, double glass door](#)
  - [Metal frame, double glass door](#)
  - [Wood frame, double/triple glass, glass storm](#)
  - [Metal frame, double/triple glass, glass storm](#)
  - [French door, wood frame with single glass](#)
  - [French door, metal frame with single glass](#)
  - [French door, wood frame with double glass](#)
  - [French door, metal frame with double glass](#)
  - [French door, wood frame with triple glass](#)
  - [French door, metal frame with triple glass](#)
- Roof:
  - [Flat roof - A](#)
  - [Flat roof - B](#)
  - [Flat roof - C](#)
  - [Sloping roof including loft](#)
  - [Sloping roof including loft](#)
  - [Lightweight curtain roof](#)
  - [Lightweight curtain roof](#)
  - [Sloping roof - domestic](#)
  - [Un-insulated flat roof](#)

- [Super-insulated flat roof](#)
- [Roof terrace system](#)
- [Roof terrace system](#)
- [Steel sheet with 2 in insulation](#)
- [Steel sheet with 1 in insulation](#)
- [Steel sheet with 2 in insulation](#)
- [Steel sheet with 1 in insulation](#)
- [Steel sheet with 4 in insulation](#)
- [Steel sheet with 8 in insulation](#)
- [Steel sheet with 12 in insulation](#)
- [Stone chipping, asphalt, screed, heavy concrete block](#)
- [Stone chipping, asphalt, screed, light concrete block](#)
- [Asphalt, screed, dense cast concrete, dense plaster](#)
- [Asphalt, aerated concrete slab, dense plaster](#)
- [Asphalt, fiberboard, aced, air, aced](#)
- [Asphalt, fiberboard, gypsum](#)
- [Asphalt, fiberboard, 1 in batting, gypsum](#)
- [Asphalt, fiberboard, 2 in batting, gypsum](#)
- [3/4 in asphalt 1/2 in fiberboard 1 in air 3 in batt 3/8 in gyp.](#)
- [3/4 in asphalt 1/2 in fiberboard 2 in EPS slab 1 in air 3/8 in gyp.](#)
- [3/4 in asphalt 1/2 in fiberboard 2 in EPS slab 1 in air 3/8 in gyp.](#)
- [3/4 in asphalt 1/2 in screed 2 in wood wool slab 1 in air 3/8 in gyp.](#)
- [3/4 in felt / bitumen 1 in EPS slab 1/8 in metal deck](#)
- [4 in wood with 2 in insulation](#)
- [2 1/2 in wood with 2 in insulation](#)
- [4 in wood with 2 in insulation](#)
- [4 in wood with 1 in insulation](#)
- [2 1/2 in wood with 1 in insulation](#)
- [1 in wood with 1 in insulation](#)
- [8 in lightweight concrete](#)
- [6 in lightweight concrete](#)
- [4 in lightweight concrete](#)
- [6 in heavyweight concrete with 2 in insulation](#)
- [4 in heavyweight concrete with 2 in insulation](#)
- [2 in heavyweight concrete with 2 in insulation](#)
- [6 in heavyweight concrete with 1 in insulation](#)
- [4 in heavyweight concrete with 1 in insulation](#)
- [2 in heavyweight concrete with 1 in insulation](#)
- [4 in wood with 2 in insulation](#)
- [2 1/2 in wood with 2 in insulation](#)
- [1 in wood with 2 in insulation](#)
- [4 in wood with 1 in insulation](#)
- [2 1/2 in wood with 1 in insulation](#)
- [1 in wood with 1 in insulation](#)
- [8 in lightweight concrete](#)
- [6 in lightweight concrete](#)
- [4 in lightweight concrete](#)
- [6 in heavyweight concrete with 2 in insulation](#)
- [4 in heavyweight concrete with 2 in insulation](#)
- [2 in heavyweight concrete with 2 in insulation](#)
- [6 in heavyweight concrete with 1 in insulation](#)
- [4 in heavyweight concrete with 1 in insulation](#)
- [2 in heavyweight concrete with 1 in insulation](#)
- [2 in heavyweight concrete with 4 in insulation](#)
- [4 in heavyweight concrete with 4 in insulation](#)
- [6 in heavyweight concrete with 4 in insulation](#)
- [6 in heavyweight concrete with 6 in insulation](#)

- [6 in heavyweight concrete with 9 in insulation](#)
- [6 in heavyweight concrete with 12 in insulation](#)
- [4 in wood with 4 in insulation](#)
- [4 in wood with 8 in insulation](#)
- [4 in wood with 12 in insulation](#)
- [Concrete ballast, membrane, sheathing, insulation, metal deck](#)
- [Asphalt shingles, wood sheathing, R-19 batt insulation, gyp board](#)
- [Slate or tile, wood sheathing, R-19 batt insulation, gyp board](#)
- [Wood shingles, wood sheathing, R-19 batt insulation, gyp board](#)
- [Metal roof, R-19 batt insulation, gyp board](#)
- [Metal roof, R-19 batt insulation, suspended acoustical ceiling](#)
- [Metal roof, R-19 batt insulation](#)
- [Membrane, sheathing, R-10 insulation board, wood deck](#)
- [Membrane, sheathing, R-10 insulation, wood deck, suspended ceiling](#)
- [Membrane, sheathing, R-10 insulation board, metal deck](#)
- [Membrane, sheathing, R-10 insulation, metal deck, suspended ceiling](#)
- [Membrane, sheathing, R-15 insulation board, metal deck](#)
- [Membrane, sheathing, R-10 plus R-15 insulation boards, metal deck](#)
- [Membrane, sheathing, R-15 insulation, 4 in light concrete](#)
- [Membrane, sheathing, R-15 insulation, 6 in light concrete](#)
- [Membrane, sheathing, R-15 insulation, 8 in light concrete](#)
- [Membrane, sheathing, R-15 insulation, 6 in heavy concrete](#)
- [Membrane, sheathing, R-15 insulation, 8 in heavy concrete](#)
- [Membrane, concrete, R-19 insulation, suspended ceiling](#)
- [R-10 over roof deck](#)
- [R-15 over roof deck](#)
- [R-19 wood framed roof](#)
- [R-20 over roof deck](#)
- [R-25 over roof deck](#)
- [R-30 wood frame roof](#)
- [R-38 wood frame roof](#)
- [R-49 wood frame roof](#)
- [R-60 wood frame roof](#)
- [R-30 over roof deck](#)
- [R-15 over roof deck - cool roof](#)
- [R-20 over roof deck - cool roof](#)
- [R-18.7 over roof deck](#)
- [R-30 over roof deck - cool roof](#)
- [R-18.7 over roof deck - cool roof](#)
- [R-38 over roof deck](#)
- [R-38 over roof deck-cool roof](#)
- [R-50 over roof deck](#)
- [R-50 over roof deck-cool roof](#)
- [R-13 wood frame roof](#)
- [R-22 wood frame roof](#)
- [R-26 wood frame roof](#)
- [R-43 wood frame roof](#)
- [R-52 wood frame roof](#)
- [R-11 wood frame roof](#)
- [R-15 wood frame roof](#)
- [R-0 wood or steel frame roof](#)
- [R-0 over roof deck](#)
- [R-60 over roof deck](#)
- [R-19 insulation over concret deck](#)
- [R-38 attic ceiling](#)
- [R-30 attic ceiling](#)
- [R-45 attic ceiling](#)

- [R-11 wood frame roof](#)
- [R-22 insulated panels](#)
- [R-28 insulated panels](#)
- [R-36 insulated panels](#)
- [Ballast, 2 in polystyrene, screed, concrete, plaster](#)
- [Ballast, 4 in polystyrene, screed, concrete, plaster](#)
- [Waterproof covering, screed, cast concrete, dense plaster](#)
- [Waterproof covering, polyurethane, screed, concrete, plaster](#)
- [Waterproof covering, polyurethane, screed, concrete, plaster](#)
- [Waterproof covering, polyurethane, screed, concrete, plaster](#)
- [Waterproof covering, timber decking, plasterboard](#)
- [Waterproof covering, mineral fiber insulation, plasterboard](#)
- [Waterproof covering, 1 1/4 in polyurethane, decking, plasterboard](#)
- [Waterproof covering, 4 in polyurethane, decking, plasterboard](#)
- [Waterproof covering, 8 in polyurethane, decking, plasterboard](#)
- UndergroundSlab:
  - [Standard slab construction - A](#)
  - [Standard slab construction - B](#)
  - [Solid-ground floor](#)
  - [Suspended timber floor](#)
  - [Industrial solid](#)
  - [Un-insulated solid](#)
  - [Un-insulated suspended timber](#)
  - [Super-insulated](#)
  - [Slab edge uninsulated](#)
  - [Slab edge R-5 insulation](#)
  - [Slab edge R-10 insulation](#)
  - [Slab edge R-15 insulation](#)
  - [Slab edge R-20 insulation](#)

# MEP Constructions for Buildings and Spaces

## Ceilings

### 8 in lightweight concrete ceiling

U-Value: 1.3610 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

### 4 in reinforced-concrete ceiling

U-Value: 3.6842 W/(m<sup>2</sup> • °K)

4 in (100 mm) reinforced-concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.100 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

### Carpeted 4 in reinforced-concrete ceiling

U-Value: 2.2826 W/(m<sup>2</sup> • °K)

Carpeted 4 in (100 mm) reinforced-concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.100 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)

### 8 in reinforced-concrete ceiling

U-Value: 2.9167 W/(m<sup>2</sup> • °K)

8 in (200 mm) reinforced-concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

### 5 in reinforced-concrete ceiling (screeded)

U-Value: 2.4275 W/(m<sup>2</sup> • °K)

5 in (125 mm) reinforced-concrete ceiling (upper floor screeded)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.126 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)

### 5 in concrete ceiling

U-Value: 3.4146 W/(m<sup>2</sup> • °K)

5 in (125 mm) concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense	Concrete cast dense	-	0.130 m	1.90 W/(m • °K)	2300	840 J/(kg • °K)

reinforced	reinforced		kg/m <sup>3</sup>	°K)
------------	------------	--	-------------------	-----

<b>5 in concrete ceiling (screeded)</b>		<b>U-Value: 2.4108 W/(m<sup>2</sup> • °K)</b>
---	--	---

5 in (125 mm) concrete ceiling (2 in (50 mm) floating screed on upper floor)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.130 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>1/2 in plaster with TG boards on 16 in joist centers</b>		<b>U-Value: 1.6929 W/(m<sup>2</sup> • °K)</b>
---	--	---

1/2 in (12 mm) plaster ceiling with TG boards on 16 in (400 mm) joist centers

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster ceiling tiles	Plaster ceiling tiles	-	0.012 m	0.38 W/(m • °K)	1120 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Plaster, wood boards, glass wool on joists</b>		<b>U-Value: 0.8226 W/(m<sup>2</sup> • °K)</b>
---	--	---

1/2 in (12 mm) plaster ceiling TG boards with 1 in (25 mm) glass wool on joists

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster ceiling tiles	Plaster ceiling tiles	-	0.012 m	0.38 W/(m • °K)	1120 kg/m <sup>3</sup>	840 J/(kg • °K)
Glass fiber wool - fiber quilt	Glass fiber wool - fiber quilt	-	0.025 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>12 in reinforced-concrete ceiling</b>		<b>U-Value: 2.4138 W/(m<sup>2</sup> • °K)</b>
--	--	---

12 in (300 mm) reinforced-concrete ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.300 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>2 in screed, 6 in cast concrete</b>		<b>U-Value: 2.1993 W/(m<sup>2</sup> • °K)</b>
--	--	---

Ceiling 2 in (50 mm) screed, 6 in (150 mm) cast concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Wood blocks, screed, 6 in concrete</b>		<b>U-Value: 1.5791 W/(m<sup>2</sup> • °K)</b>
---	--	---

Ceiling 1 in (25 mm) wood blocks 2 in (50 mm) screed 6 in (150 mm) cast concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg

						• °K)
Screeed	Screeed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

## Wood blocks, concrete, batting, gypsum

U-Value: 0.7457 W/(m<sup>2</sup> • °K)

Ceiling, 1 in (25 mm) wood blocks, 2 1/2 in (65 mm) cast concrete, 1 in (25 mm) air, 1 in (25 mm) batting, 5/8 in (16 mm) gypsum

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.065 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> • - °K)/W	-	-	-	-
R-30, 9 1/2 in batt insulation	R-30, 9 1/2 in (240 mm) batt insulation	-	0.2438 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • 0.015879 m °K)/W	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## Wood blocks, concrete, batting, metal deck tray

U-Value: 0.8057 W/(m<sup>2</sup> • °K)

Ceiling 1 in (25 mm) wood blocks, 2 1/2 in (65 mm) cast concrete, 1 in (25 mm) air, 1 in (25 mm) batt, 1/16 in (2 mm) metal deck tray

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.065 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> • - °K)/W	-	-	-	-
R-30, 9 1/2 in batt insulation	R-30, 9 1/2 in (240 mm) batt insulation	-	0.2438 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
Metal surface	Metal surface	-	0.002 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Concrete slab internal

U-Value: 1.0687 W/(m<sup>2</sup> • °K)

Concrete slab internal ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Timber-joist internal

U-Value: 1.2585 W/(m<sup>2</sup> • °K)

Timber-joist internal ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

Timber-joist internal - industry			U-Value: 1.5926 W/(m <sup>2</sup> • °K)			
Timber-joist internal ceiling - industry						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

2 in heavyweight concrete with false ceiling			U-Value: 1.4128 W/(m <sup>2</sup> • °K)			
2 in (50 mm) heavyweight concrete deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in heavyweight concrete	2 in (50 mm) heavyweight concrete	-	0.0508 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

4 in heavyweight concrete with false ceiling			U-Value: 1.3301 W/(m <sup>2</sup> • °K)			
4 in (100 mm) heavyweight concrete deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

4 in lightweight concrete with false ceiling			U-Value: 1.0411 W/(m <sup>2</sup> • °K)			
4 in (100 mm) lightweight concrete deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

8 in heavyweight concrete with false ceiling			U-Value: 1.2337 W/(m <sup>2</sup> • °K)			
8 in (200 mm) heavyweight concrete deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

8 in lightweight concrete with false ceiling			U-Value: 0.8144 W/(m <sup>2</sup> • °K)			
8 in (200 mm) lightweight concrete deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

2 in wood deck with false ceiling			U-Value: 0.8985 W/(m <sup>2</sup> • °K)			
2 in (50 mm) wood deck with false ceiling						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
-----------	-------------------	---	----------	-----------------	-----------------------	------------------

3 in wood deck with false ceiling			U-Value: 0.7559 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3 in wood	3 in (75 mm) wood	-	0.076 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

12 in heavyweight concrete with false ceiling			U-Value: 1.1504 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

4 in wood deck with false ceiling			U-Value: 0.6524 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

Steel deck with false ceiling			U-Value: 1.4427 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Steel	Steel	-	0.005 m	45 W/(m • °K)	7800 kg/m <sup>3</sup>	480 J/(kg • °K)

Ceiling below joists, no insulation			U-Value: 1.3683 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-2 board insulation			U-Value: 1.1015 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-2 insulation	R-2 insulation	0.035222 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-3 board insulation			U-Value: 0.9255 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-3 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-4 board insulation			U-Value: 0.7949 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-4 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-5 board insulation			U-Value: 0.6983 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-5 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-6 board insulation			U-Value: 0.6189 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-6 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-8 board insulation			U-Value: 0.5110 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-8 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-8 insulation	R-8 insulation	1.40888 (m <sup>2</sup> • °K)	-	-	-	-

Ceiling below joists, R-10 board insulation			U-Value: 0.4315 W/(m <sup>2</sup> • °K)			
Ceiling below joists, R-10 board insulation [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-10 insulation	R-10 insulation	1.76110 (m <sup>2</sup> • °K)	-	-	-	-

## Ceiling below joists, R-11 blanket or loose fill

U-Value: 0.4769 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-11 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)	-	-	-	-

## Ceiling below joists, R-13 blanket or loose fill

U-Value: 0.4315 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-13 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-13 insulation	R-13 insulation	2.28943 (m <sup>2</sup> • °K)	-	-	-	-

## Ceiling below joists, R-15 blanket or loose fill

U-Value: 0.3917 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-15 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)	-	-	-	-

## Ceiling below joists, R-19 blanket or loose fill

U-Value: 0.2895 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-19 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-19 insulation	R-19 insulation	3.34609 (m <sup>2</sup> • °K)	-	-	-	-

## Ceiling below joists, R-21 blanket or loose fill

U-Value: 0.2668 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-21 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-21 insulation	R-21 insulation	3.6931 (m <sup>2</sup> • °K)/W	-	-	-	-

## Ceiling below joists, R-30 blanket or loose fill

U-Value: 0.1930 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-30 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-30 insulation	R-21 insulation	21 (m <sup>2</sup> • °K)/W	-	-	-	-

## Ceiling below joists, R-38 blanket or loose fill

U-Value: 0.1646 W/(m<sup>2</sup> • °K)

Ceiling below joists, R-38 blanket or loose fill [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
R-38 insulation	R-21 insulation	6.69219 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood, no insulation

U-Value: 1.6295 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood, no insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-2 insulation

U-Value: 1.0333 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-2 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-3 insulation

U-Value: 0.8744 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-3 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 2 in cement-fiber slab, no insulation

U-Value: 0.8119 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 2 in (50 mm) cement-fiber slab, no insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in Cement	2 in (50 mm) Cement	0.07083 (m <sup>2</sup> • 0.051 m °K)/W	-	0.72 W/(m • °K)	1860 kg/m <sup>3</sup>	840 J/(kg • °K)
No insulation	No insulation	0.00001 (m <sup>2</sup> • - °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-4 insulation

U-Value: 0.7608 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-4 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • - °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-5 insulation

U-Value: 0.6700 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-5 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • - °K)/W	-	-	-	-

## Exposed beams, 3 in cement-fiber slab, no insulation

U-Value: 0.6472 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 3 in (75 mm) cement-fiber slab, no insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3 in Cement	3 in (75 mm) Cement	0.10556 (m <sup>2</sup> • 0.076 m °K)/W	-	0.72 W/(m • °K)	1860 kg/m <sup>3</sup>	840 J/(kg • °K)
No insulation	No insulation	0.00001 (m <sup>2</sup> • - °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-6 insulation

U-Value: 0.5961 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-6 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3 in Cement	3 in (75 mm) Cement	0.10556 (m <sup>2</sup> • 0.076 m °K)/W	-	0.72 W/(m • °K)	1860 kg/m <sup>3</sup>	840 J/(kg • °K)
R-6 insulation	R-6 insulation	0.70444 (m <sup>2</sup> • - °K)/W	-	-	-	-

1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-7 insulation

U-Value: 0.5166 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-7 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-10 insulation

U-Value: 0.4201 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-10 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-10 insulation	R-10 insulation	1.76110 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-12 insulation

U-Value: 0.3577 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-12 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-12 insulation	R-12 insulation	2.11332 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-15 insulation

U-Value: 0.3066 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-15 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-17 to R-18 insulation

U-Value: 0.2725 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-17 to R-18 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific

Heat						
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-19 insulation	R-19 insulation	3.34609 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-20 insulation

U-Value: 0.2441 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-20 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-19 insulation	R-19 insulation	3.34609 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-21 to R-23 insulation

U-Value: 0.2214 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-21 to R-23 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-24 to R-26 insulation

U-Value: 0.1987 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-24 to R-26 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-25 insulation	R-25 insulation	4.40275 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-27 to R-29 insulation

U-Value: 0.1816 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-27 to R-29 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-28 insulation	R-28 insulation	4.93109 (m <sup>2</sup> • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-30 to R-32 insulation

U-Value: 0.1646 W/(m<sup>2</sup> • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-30 to R-32 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-30 insulation	R-30 insulation	5.28331 (m² • °K)/W	-	-	-	-

## Exposed beams, 1 1/2 in wood plus R-33 to R-35 insulation

U-Value: 0.1533 W/(m² • °K)

Ceiling on exposed beams, 1 1/2 in (40 mm) wood plus R-33 to R-35 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-34 insulation	R-34 insulation	5.98775 (m² • °K)/W	-	-	-	-

## Wood block, concrete, plasterboard

U-Value: 1.58 W/(m² • °K)

1 in (25 mm) wood block, 2 1/2 in (65 mm) cast concrete, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard ceiling [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
2 in heavyweight concrete	2 in (50 mm) heavyweight concrete	-	0.0508 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Exterior Walls

Standard wall construction - A			U-Value: 0.3495 W/(m <sup>2</sup> • °K)			
--------------------------------	--	--	---	--	--	--

Standard wall construction

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
8 in lightweight concrete block (filled)	8 in (200 mm) lightweight concrete block (filled)	-	0.2032 m	0.26 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> °K/W)	-	-	-	-

Standard wall construction - B			U-Value: 0.2993 W/(m <sup>2</sup> • °K)			
--------------------------------	--	--	---	--	--	--

Standard wall construction

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> °K/W)	-	-	-	-

Standard wall construction - C			U-Value: 0.3967 W/(m <sup>2</sup> • °K)			
--------------------------------	--	--	---	--	--	--

Standard wall construction

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> °K/W)	-	-	-	-

Brick / block wall			U-Value: 0.4396 W/(m <sup>2</sup> • °K)			
--------------------	--	--	---	--	--	--

Brick / block wall

Material	Description	R-	Thickness	Conductivity	Density	Specific
----------	-------------	----	-----------	--------------	---------	----------

Value						Heat
Outside surface resistance	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

## Timber-frame wall

U-Value: 0.4493 W/(m<sup>2</sup> • °K)

Timber-frame wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Lightweight curtain wall

U-Value: 0.4522 W/(m<sup>2</sup> • °K)

Lightweight curtain wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Metal-clad wall

U-Value: 0.4546 W/(m<sup>2</sup> • °K)

Metal-clad wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-

8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brick / block wall

U-Value: 0.3967 W/(m<sup>2</sup> • °K)

Brick / block wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface - resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface - resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brick / block wall

U-Value: 0.5416 W/(m<sup>2</sup> • °K)

Brick / block wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface - resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space - resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Wall air space - resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface - resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Timber-frame wall

U-Value: 0.5779 W/(m<sup>2</sup> • °K)

Timber-frame wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

Wall air space resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brick / block wall

U-Value: 0.5130 W/(m<sup>2</sup> • °K)

Brick / block wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space - resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Wall air space - resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface - resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Lightweight concrete-clad wall

U-Value: 0.5445 W/(m<sup>2</sup> • °K)

Lightweight concrete-clad wall

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

resistance	resistance	• °K)/W				
Brickwork single-leaf construction dense plaster		U-Value: 2.1839 W/(m <sup>2</sup> • °K)				
Brickwork single-leaf construction dense plaster						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> °K/W)	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> °K/W)	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> °K/W)	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R0 w/ 2x4 frame	Batt, R-0 including framing factor	0.17083 (m <sup>2</sup> °K/W)	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> °K/W)	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Brickwork single-leaf construction light plaster		U-Value: 1.9487 W/(m <sup>2</sup> • °K)				
Brickwork single-leaf construction light plaster						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> °K/W)	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> °K/W)	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> °K/W)	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R0 w/ 2x4 frame	Batt, R-0 including framing factor	0.17083 (m <sup>2</sup> °K/W)	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> °K/W)	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Un-insulated brick/block wall		U-Value: 1.4269 W/(m <sup>2</sup> • °K)				
Un-insulated brick/block wall						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> °K/W)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3/4 in (IN32)	Polystyrene 3/4 in (1.9 cm)	0.55031 (m <sup>2</sup> °K/W)	0.019049 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> °K/W)	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Super-insulated external wall		U-Value: 0.2204 W/(m <sup>2</sup> • °K)				
Super-insulated external wall						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-

1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Sheet steel

U-Value: 5.8817 W/(m<sup>2</sup> • °K)

Sheet steel

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Sheet aluminum

U-Value: 5.8821 W/(m<sup>2</sup> • °K)

Sheet aluminum

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brickwork single-leaf construction with insulation and plaster

U-Value: 0.6723 W/(m<sup>2</sup> • °K)

Brickwork single-leaf construction with insulation and plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

Polyurethane insulation	Polyurethane insulation	-	0.025 m	0.025 W/(m • °K)	30 kg/m³	1400 J/(kg • °K)
Plaster (dense)	Plaster (dense)	-	0.025 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

<b>Brickwork single-leaf construction fiber insulation and render</b>		<b>U-Value: 0.7362 W/(m² • °K)</b>
---	--	------------------------------------

Brickwork single-leaf construction fiber insulation and render

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Polyurethane insulation	Polyurethane insulation	-	0.025 m	0.025 W/(m • °K)	30 kg/m³	1400 J/(kg • °K)
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

<b>Brickwork single-leaf construction EPS insulation and render</b>		<b>U-Value: 0.5596 W/(m² • °K)</b>
---	--	------------------------------------

Brickwork single-leaf construction EPS insulation and render

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m³	1400 J/(kg • °K)
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

<b>Lightweight concrete block air gap and plasterboard</b>		<b>U-Value: 0.6825 W/(m² • °K)</b>
--	--	------------------------------------

Lightweight concrete block air gap and plasterboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m² °K/W)	-	-	-	-
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)

<b>Lightweight concrete block GRP insulation and plasterboard</b>		<b>U-Value: 0.5602 W/(m² • °K)</b>
---	--	------------------------------------

## Lightweight concrete block GRP insulation and plasterboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
Polyurethane insulation	Polyurethane insulation	-	0.025 m	0.025 W/(m • °K)	30 kg/m³	1400 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)

## Lightweight concrete block poly-insulation and plasterboard

U-Value: 0.4376 W/(m² • °K)

### Lightweight concrete block poly-insulation and plasterboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
Polyurethane insulation	Polyurethane insulation	-	0.025 m	0.025 W/(m • °K)	30 kg/m³	1400 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)

## Brick cavity with dense plaster

U-Value: 1.4917 W/(m² • °K)

### Brick cavity with dense plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m³	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m³	840 J/(kg • °K)

## Brick cavity with mineral insulation and lightweight plaster

U-Value: 0.6945 W/(m² • °K)

### Brick cavity with mineral insulation and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m³	840 J/(kg • °K)
4 in mineral fiber insulation	4 in (100 mm) mineral fiber insulation	-	0.095 m	0.035 W/(m • °K)	30 kg/m³	1000 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m³	1000 J/(kg • °K)
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m³	840 J/(kg • °K)

## Brick cavity full mineral insulation and lightweight plaster

U-Value: 0.5065 W/(m<sup>2</sup> • °K)

Brick cavity full mineral insulation and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in mineral fiber insulation	4 in (100 mm) mineral fiber insulation	-	0.095 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)

## Brick cavity with UF foam insulation and lightweight plaster

U-Value: 0.8543 W/(m<sup>2</sup> • °K)

Brick cavity with UF foam insulation and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Urea formaldehyde (UF) foam insulation	Urea formaldehyde (UF) foam insulation	-	0.050 m	0.040 W/(m • °K)	10 kg/m <sup>3</sup>	1400 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)

## Brick, heavy concrete block, phenolic foam, light plaster

U-Value: 0.8048 W/(m<sup>2</sup> • °K)

Brick-air heavyweight concrete block and Phenolic foam and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m <sup>2</sup> - or no value)	-	-	-	-
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Foam - phenol	Foam - phenol	-	- m	0.040 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, heavy concrete block, mineral insulation, light plaster

U-Value: 0.5359 W/(m<sup>2</sup> • °K)

Brick-air heavyweight concrete block and full mineral insulation and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 • °K)/W	-	-	-	-
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
4 in mineral fiber insulation	4 in (100 mm) mineral fiber insulation	-	0.095 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, medium concrete block, foam insulation, light plaster

U-Value: 0.5487 W/(m<sup>2</sup> • °K)

Brick-air medium concrete block, urea formaldehyde (UF) foam insulation and light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> - or no construction °K)/W	-	-	-	-
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Foam - phenol	Foam - phenol	-	- m	0.040 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, light concrete block, foam insulation, light plaster

U-Value: 0.4646 W/(m<sup>2</sup> • °K)

Brick-air thermolite block and UF insulation and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 • °K)/W	-	-	-	-
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Foam - phenol	Foam - phenol	-	- m	0.040 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, light concrete block, light plaster

U-Value: 0.9237 W/(m<sup>2</sup> • °K)

Brick-air lightweight concrete block and lightweight plaster

Material	Description	R-	Thickness	Conductivity	Density	Specific
----------	-------------	----	-----------	--------------	---------	----------

Value						Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, foam insulation, light concrete block, light plaster

U-Value: 0.5856 W/(m<sup>2</sup> • °K)

Brick-air UF insulation lightweight concrete block and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Brick, mineral insulation, light concrete block, light plaster

U-Value: 0.3855 W/(m<sup>2</sup> • °K)

Brick mineral insulation thermolite block and lightweight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
4 in mineral fiber insulation	4 in (100 mm) mineral fiber insulation	-	0.095 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Face brick, insulation, light concrete block

U-Value: 0.5511 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 4 in (100 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation	R-10, 2 in (50 mm)	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

board	insulation board					°K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in lightweight concrete

U-Value: 1.1407 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in face brick, 8 in common brick

U-Value: 1.2100 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick, air space and 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick, 8 in heavyweight concrete block

U-Value: 1.4244 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick air space and 8 in (200 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick, 8 in lightweight concrete block

U-Value: 1.1562 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick air space and 8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
------------	---------------------	---	----------	-----------------	------------------------	-----------------

## 4 in face brick air space and 8 in clay tile

4 in (100 mm) face brick air space and 8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Hol clay tile 8 in (m <sup>2</sup> (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick air space and 2 in heavyweight concrete

4 in (100 mm) face brick air space and 2 in (50 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
2 in lightweight concrete roof ballast	2 in (50 mm) lightweight concrete roof ballast	-	0.0508 m	0.19 W/(m • °K)	640 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick air space and 4 in common brick

4 in (100 mm) face brick air space and 4 in (100 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick air space and 4 in heavyweight concrete block

4 in (100 mm) face brick air space and 4 in (100 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
------------	---------------------	---	----------	-----------------	------------------------	-----------------

<b>4 in face brick air space and 4 in lightweight concrete block</b>		<b>U-Value: 1.2280 W/(m<sup>2</sup> • °K)</b>
--	--	---

4 in (100 mm) face brick air space and 4 in (100 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

<b>12 in heavyweight concrete</b>		<b>U-Value: 1.9968 W/(m<sup>2</sup> • °K)</b>
-----------------------------------	--	---

12 in (300 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

<b>8 in heavyweight concrete with 2 in insulation</b>		<b>U-Value: 0.6160 W/(m<sup>2</sup> • °K)</b>
---	--	---

8 in (200 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)

<b>8 in heavyweight concrete with 1 in insulation</b>		<b>U-Value: 0.9683 W/(m<sup>2</sup> • °K)</b>
---	--	---

8 in (200 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)

<b>8 in heavyweight concrete with air space</b>		<b>U-Value: 1.6076 W/(m<sup>2</sup> • °K)</b>
---	--	---

8 in (200 mm) heavyweight concrete with air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)

## 8 in heavyweight concrete

U-Value: 2.2621 W/(m<sup>2</sup> • °K)

8 in (200 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)

## 4 in face brick 8 in common brick with 1 in insulation

U-Value: 0.8091 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 8 in (200 mm) common brick with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Com brick 8 in (BK02) m	8 in (20.3 cm) common	0.28175 (m <sup>2</sup> • °K)/W	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in face brick 8 in common brick with air space

U-Value: 1.2118 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 8 in (200 mm) common brick with air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Com brick 8 in (BK02)	8 in (20.3 cm) common	0.28175 (m <sup>2</sup> • °K)/W	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in face brick air space and 4 in lightweight block

U-Value: 0.9866 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick air space and 4 in (100 mm) lightweight block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

<b>Wall with 3 in fiberglass insulation and stucco outside finish</b>		<b>U-Value: 0.4992 W/(m<sup>2</sup> • °K)</b>
---	--	---

Wall with 3 in (75 mm) fiberglass insulation and stucco outside finish

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Two-sided brick wall with air space</b>		<b>U-Value: 1.9894 W/(m<sup>2</sup> • °K)</b>
--	--	---

Two-sided brick wall with air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 (m <sup>2</sup> °K/W)	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
2 in lightweight concrete roof ballast	2 in (50 mm) lightweight concrete roof ballast	-	0.0508 m	0.19 W/(m • °K)	640 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Brick wall 8 in concrete block and no air space</b>		<b>U-Value: 1.2320 W/(m<sup>2</sup> • °K)</b>
--	--	---

Brick wall 8 in (200 mm) concrete block and no air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)

<b>Brick wall with 4 in concrete block</b>		<b>U-Value: 1.8709 W/(m<sup>2</sup> • °K)</b>
--	--	---

Brick wall with 4 in (100 mm) concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

<b>Brick wall with 8 in concrete block</b>		<b>U-Value: 1.6339 W/(m<sup>2</sup> • °K)</b>
--	--	---

Brick wall with 8 in (200 mm) concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)

<b>Brick wall with 6 in concrete</b>		<b>U-Value: 1.1655 W/(m<sup>2</sup> • °K)</b>
--------------------------------------	--	---

Brick wall with 6 in (150 mm) concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)
---------------------------------	--	---	----------	-----------------	-----------------------	-----------------

Frame wall with 2 in insulation and 4 in brick veneer			U-Value: 0.6857 W/(m <sup>2</sup> • °K)			
---	--	--	---	--	--	--

Frame wall with 2 in (50 mm) insulation and 4 in (100 mm) brick veneer

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-

Frame wall with 2 in insulation			U-Value: 0.7079 W/(m <sup>2</sup> • °K)			
---------------------------------	--	--	---	--	--	--

Frame wall with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-

Metal curtain wall with 3 in insulation			U-Value: 0.5149 W/(m <sup>2</sup> • °K)			
---	--	--	---	--	--	--

Metal curtain wall with 3 in (75 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

Metal curtain wall with 2 in insulation			U-Value: 0.7399 W/(m <sup>2</sup> • °K)			
---	--	--	---	--	--	--

Metal curtain wall with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

Metal curtain wall with 1 in insulation			U-Value: 0.6418 W/(m <sup>2</sup> • °K)			
Metal curtain wall with 1 in (25 mm) insulation						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

Wall 12 in concrete with 2 in insulation on the outside			U-Value: 0.6418 W/(m <sup>2</sup> • °K)			
Wall 12 in (300 mm) concrete with 2 in (50 mm) insulation on the outside						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
12 in concrete block	12 in (300 mm) concrete block	-	0.3048 m	1.4 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

Wall 8 in concrete with 2 in insulation on the outside			U-Value: 0.6669 W/(m <sup>2</sup> • °K)			
Wall 8 in (200 mm) concrete with 2 in (50 mm) insulation on the outside						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

Wall 4 in concrete with 2 in insulation on the outside			U-Value: 0.6941 W/(m <sup>2</sup> • °K)			
Wall 4 in (100 mm) concrete with 2 in (50 mm) insulation on the outside						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

Wall 12 in concrete with 2 in insulation on the inside			U-Value: 0.6418 W/(m <sup>2</sup> • °K)			
Wall 12 in (300 mm) concrete with 2 in (50 mm) insulation on the inside						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
12 in concrete block	12 in (300 mm) concrete block	-	0.3048 m	1.4 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

Wall 12 in (300 mm) concrete with 2 in (50 mm) insulation on the inside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
12 in concrete block	12 in (300 mm) concrete block	-	0.3048 m	1.4 W/(m • °K)	800 kg/m³	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
12 in concrete block	12 in (300 mm) concrete block	-	0.3048 m	1.4 W/(m • °K)	800 kg/m³	920 J/(kg • °K)

## Wall 8 in concrete with 2 in insulation on the inside

U-Value: 0.6669 W/(m² • °K)

Wall 8 in (200 mm) concrete with 2 in (50 mm) insulation on the inside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m³	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m³	920 J/(kg • °K)

## Wall 4 in concrete with 2 in insulation on the inside

U-Value: 0.6941 W/(m² • °K)

Wall 4 in (100 mm) concrete with 2 in (50 mm) insulation on the inside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)

## Frame wall with 3 in insulation

U-Value: 0.4392 W/(m² • °K)

Frame wall with 3 in (75 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in (m² w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Polystyrene 3 1/2 in (m² w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-

## Frame wall with 2 in insulation

U-Value: 0.5931 W/(m² • °K)

Frame wall with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-

## Frame wall with 1 in insulation

U-Value: 0.9130 W/(m<sup>2</sup> • °K)

Frame wall with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-

## Frame wall without insulation

U-Value: 1.9818 W/(m<sup>2</sup> • °K)

Frame wall without insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-
Polystyrene 3 1/2 in (m <sup>2</sup> w/ 48 in oc SIP wall frame)	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-

## 2 in insulation with 12 in heavyweight concrete

U-Value: 0.5945 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 12 in (300 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
12 in concrete block	12 in (300 mm) concrete block	-	0.3048 m	1.4 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

## 2 in insulation with 8 in heavyweight concrete

U-Value: 0.6160 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 8 in (200 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)

	block					°K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 2 in insulation with 8 in common brick

U-Value: 0.5601 W/(m² • °K)

2 in (50 mm) insulation with 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m³	920 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 2 in insulation with 8 in heavyweight concrete block

U-Value: 0.6020 W/(m² • °K)

2 in (50 mm) insulation with 8 in (200 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 2 in insulation with 8 in lightweight concrete block

U-Value: 0.4900 W/(m² • °K)

2 in (50 mm) insulation with 8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 2 in insulation with 8 in clay tile

U-Value: 0.5371 W/(m² • °K)

2 in (50 mm) insulation with 8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m² °K/W)	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m³	837.360000 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 2 in insulation with 4 in heavyweight concrete

U-Value: 0.6391 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 4 in (100 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

## 2 in insulation with 4 in common brick

U-Value: 0.6076 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 4 in (100 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 2 in insulation with 4 in heavyweight concrete block

U-Value: 0.6315 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 4 in (100 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 2 in insulation with 4 in lightweight concrete block

U-Value: 0.5639 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 4 in (100 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 2 in insulation with 4 in clay tile

U-Value: 0.5938 W/(m<sup>2</sup> • °K)

2 in (50 mm) insulation with 4 in (100 mm) clay tile

Material	Description	R-	Thickness	Conductivity	Density	Specific
----------	-------------	----	-----------	--------------	---------	----------

Value						Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m² • °K)/W	0.101585 m • °K)	0.519047 W/(m kg/m³	1121.400000 J/(kg • °K)	
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

## 4 in face brick, 2 in insulation, 12 in heavy concrete

U-Value: 0.5803 W/(m² • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 12 in (300 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

## 4 in face brick, 2 in insulation, 8 in heavy concrete

U-Value: 0.6008 W/(m² • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 8 in (200 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

## 4 in face brick 2 in insulation and 8 in common brick

U-Value: 0.5475 W/(m² • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Com brick 8 in (BK02) m	8 in (20.3 cm) common	0.28175 (m² • °K)/W	0.203200 m • °K)	0.721197 W/(m kg/m³	1922.400000 J/(kg • °K)	837.360000
R-10, 2 in insulation	R-10, 2 in (50 mm)	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

board	insulation board					°K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick air space and 12 in heavyweight concrete

4 in (100 mm) face brick air space and 12 in (300 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space	Wall air space resistance - resistance 0.15000 (m <sup>2</sup> )	0.15000 (m <sup>2</sup> )		-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick air space and 8 in heavyweight concrete

4 in (100 mm) face brick air space and 8 in (200 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance 0.15000 (m <sup>2</sup> )	0.15000 (m <sup>2</sup> )		-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Wall air space	Wall air space resistance - resistance 0.15000 (m <sup>2</sup> )	0.15000 (m <sup>2</sup> )		-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick, 2 in insulation, 8 in heavy concrete block

U-Value: 0.5875 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 8 in (200 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

<b>4 in face brick, 2 in insulation, 8 in light concrete block</b>		<b>U-Value: 0.5362 W/(m<sup>2</sup> • °K)</b>				
4 in (100 mm) face brick 2 in (50 mm) insulation and 8 in (200 mm) lightweight concrete block						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

  

<b>2 in face brick 2 in insulation and 8 in clay tile</b>		<b>U-Value: 0.5362 W/(m<sup>2</sup> • °K)</b>				
2 in (50 mm) face brick 2 in (50 mm) insulation and 8 in (200 mm) clay tile						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 8 in	2 cells, 8 in (20.3cm) 1121.400000 1121.400000	0.32613 (m <sup>2</sup> 837.360000 (CT04))	0.203200 m	0.623065 W/(m • °K)/W		
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

  

<b>4 in face brick 2 in insulation and 4 in heavyweight concrete</b>		<b>U-Value: 0.6227 W/(m<sup>2</sup> • °K)</b>				
4 in (100 mm) face brick 2 in (50 mm) insulation and 4 in (100 mm) heavyweight concrete						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

  

<b>4 in face brick 2 in insulation and 4 in common brick</b>		<b>U-Value: 0.5928 W/(m<sup>2</sup> • °K)</b>
4 in (100 mm) face brick 2 in (50 mm) insulation and 4 in (100 mm) common brick		

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick, 2 in insulation, 4 in heavy concrete block

U-Value: 0.6155 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 2 in (50 mm) insulation and 4 in (100 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick with 8 in common brick

U-Value: 1.5499 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick with 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Com brick 8 in (BK02)	8 in (20.3 cm) common brick	0.28175 (m <sup>2</sup> °K)/W	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 8 in heavyweight concrete block with 1 in insulation

U-Value: 0.9342 W/(m<sup>2</sup> • °K)

8 in (200 mm) heavyweight concrete block with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 8 in heavyweight concrete block

U-Value: 2.0846 W/(m<sup>2</sup> • °K)

8 in (200 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 8 in lightweight concrete block with insulation

U-Value: 1.5562 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete block with insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 8 in lightweight concrete block

U-Value: 0.8108 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in face brick 8 in clay tile and 1 in insulation

U-Value: 0.5255 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 8 in (200 mm) clay tile and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 8 in	2 cells, 8 in (20.3cm) 1121.400000 1121.400000	0.32613 (m <sup>2</sup> ) 837.360000 (CT04)	0.203200 m	0.623065 W/(m • °K)/W		
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 8 in	2 cells, 8 in (20.3cm) 1121.400000 1121.400000	0.32613 (m <sup>2</sup> ) 837.360000 (CT04)	0.203200 m	0.623065 W/(m • °K)/W		
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick 8 in clay tile and air space

U-Value: 1.1092 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 8 in (200 mm) clay tile and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick with 8 in clay tile

U-Value: 1.3859 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick with 8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 8 in clay tile with 1 in Insulation

U-Value: 0.7867 W/(m<sup>2</sup> • °K)

8 in (200 mm) clay tile with 1 in (25 mm) Insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in clay tile with air space

U-Value: 1.1622 W/(m<sup>2</sup> • °K)

8 in (200 mm) clay tile with air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm)	0.32613 (m <sup>2</sup> • °K)/W	0.203200 m	0.623065 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in clay tile

U-Value: 1.4696 W/(m<sup>2</sup> • °K)

8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm) 1121.400000 kg/m <sup>3</sup>	0.32613 (m <sup>2</sup> • °K)/W 837.360000 (CT04)	0.203200 m	0.623065 W/(m • °K)	0.623065 W/(m • °K)/W	837.360000 J/(kg • °K)
Hol clay tile 8 in (CT04)	2 cells, 8 in (20.3cm) 1121.400000 kg/m <sup>3</sup>	0.32613 (m <sup>2</sup> • °K)/W 837.360000 (CT04)	0.203200 m	0.623065 W/(m • °K)	0.623065 W/(m • °K)/W	837.360000 J/(kg • °K)

## 4 in heavyweight concrete with 2 in insulation

U-Value: 0.6391 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with 1 in insulation

U-Value: 1.0267 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with air space

U-Value: 1.7752 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> °K/W)	-	-	-	-
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete

U-Value: 2.6087 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in face brick 4 in common brick and 1 in insulation

U-Value: 0.9123 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) common brick and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14084 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick 4 in common brick and air space

U-Value: 1.4589 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) common brick and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common (m <sup>2</sup> )	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 • °K)/W	-	-	-	-
Com brick 4 in (BK01)	4 in (10.1 cm) common (m <sup>2</sup> )	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick with 4 in common brick

U-Value: 1.9784 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick with 4 in (100 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in common brick

U-Value: 2.1535 W/(m<sup>2</sup> • °K)

4 in (100 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Com brick 4 in (BK01)	4 in (10.1 cm) common brick	0.14086 • °K)/W	0.101585 m	0.721197 W/(m • °K)	1922.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in heavyweight concrete block

U-Value: 2.4866 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in face brick, 4 in light concrete block, 1 in insulation

U-Value: 0.8171 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) lightweight concrete block and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick 4 in lightweight concrete block and air space

U-Value: 1.2299 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) lightweight concrete block and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m <sup>2</sup> - or no value)	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick with 4 in lightweight concrete block

U-Value: 1.5796 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick with 4 in (100 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in lightweight concrete block and 1 in insulation

U-Value: 0.8455 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete block and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in lightweight concrete block and air space

U-Value: 1.2954 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete block and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> °K/W)	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in lightweight concrete block

U-Value: 1.6893 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in face brick 4 in clay tile and 1 in insulation

U-Value: 0.8816 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) clay tile and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 4 in	1 cell, 4 in (10.1cm) 1121.400000 mm <sup>2</sup> /cm <sup>3</sup>	0.19571 (m <sup>2</sup> °K/W) 837.360000 (CT02)	0.101585 m	0.519047 W/(m • °K)/W		
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 4 in	1 cell, 4 in (10.1cm) 1121.400000 mm <sup>2</sup> /cm <sup>3</sup>	0.19571 (m <sup>2</sup> °K/W) 837.360000 (CT02)	0.101585 m	0.519047 W/(m • °K)/W		
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick 4 in clay tile and air space

U-Value: 1.3819 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick 4 in (100 mm) clay tile and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> °K)/W	-	-	-	-
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick and 4 in clay tile

U-Value: 1.8394 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick and 4 in (100 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in clay tile and 1 in insulation

U-Value: 0.9147 W/(m<sup>2</sup> • °K)

4 in (100 mm) clay tile and 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in clay tile and air space

U-Value: 0.9 W/(m<sup>2</sup> • °K)

4 in (100 mm) clay tile and air space

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 4 in	1 cell, 4 in (10.1cm) 1121.400000	0.19671 (m <sup>2</sup> °K)/W 837.360000 (CT02)	0.101585 m	0.519047 W/(m • °K)/W	0.519047 W/(m • °K)	• °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> °K)/W	-	-	-	-
Hol clay tile 4 in	1 cell, 4 in (10.1cm) 1121.400000	0.19571 (m <sup>2</sup> °K)/W 837.360000 (CT02)	0.101585 m	0.519047 W/(m • °K)/W	0.519047 W/(m • °K)	• °K)

## 4 in clay tile

U-Value: 1.9899 W/(m<sup>2</sup> • °K)

4 in (100 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 • °K)/W	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
------------------------------	-----------------------	--------------------	------------	------------------------	----------------------------------	---------------------------

## Sheet metal with 1 in insulation

U-Value: 1.0630 W/(m<sup>2</sup> • °K)

Sheet metal with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Sheet metal with 2 in insulation

U-Value: 0.6530 W/(m<sup>2</sup> • °K)

Sheet metal with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Sheet metal with 3 in insulation

U-Value: 0.4712 W/(m<sup>2</sup> • °K)

Sheet metal with 3 in (75 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## 4 in insulation with 8 in lightweight concrete block

U-Value: 0.3104 W/(m<sup>2</sup> • °K)

4 in (100 mm) insulation with 8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 6 in insulation with 8 in lightweight

## concrete block

6 in (150 mm) insulation with 8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in insulation with 8 in clay tile

4 in (100 mm) insulation with 8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K/W)	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19571 (m <sup>2</sup> °K/W)	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 6 in insulation with 8 in clay tile

6 in (150 mm) insulation with 8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19671 (m <sup>2</sup> °K/W)	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19671 (m <sup>2</sup> °K/W)	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in heavyweight concrete with 4 in insulation

8 in (200 mm) heavyweight concrete with 4 in (100 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in heavyweight	8 in (200 mm) heavyweight	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

concrete	concrete	°K)
----------	----------	-----

8 in heavyweight concrete with 6 in insulation		U-Value: 0.2509 W/(m² • °K)	
--	--	-----------------------------	--

8 in (200 mm) heavyweight concrete with 6 in (150 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

4 in insulation with 8 in common brick		U-Value: 0.3371 W/(m² • °K)	
--	--	-----------------------------	--

4 in (100 mm) insulation with 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Com brick 8 in (BK02)	8 in (20.3 cm) common brick	0.28175 (m² • K/W)	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m³	837.360000 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Com brick 8 in (BK02)	8 in (20.3 cm) common brick	0.28175 (m² • K/W)	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m³	837.360000 J/(kg • °K)

6 in insulation with 8 in common brick		U-Value: 0.2411 W/(m² • °K)	
--	--	-----------------------------	--

6 in (150 mm) insulation with 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Com brick 8 in (BK02)	8 in (20.3 cm) common brick	0.28175 (m² • K/W)	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m³	837.360000 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Com brick 8 in (BK02)	8 in (20.3 cm) common brick	0.28175 (m² • K/W)	0.203200 m	0.721197 W/(m • °K)	1922.400000 kg/m³	837.360000 J/(kg • °K)

Frame wall with 6 in insulation		U-Value: 0.2470 W/(m² • °K)	
---------------------------------	--	-----------------------------	--

Frame wall with 6 in (150 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 9 1/4 in (m² w/ 48 in oc SIP wall frame)	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 • °K)/W	-	-	-	-
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Polystyrene 9 1/4 in w/ 48 in oc SIP wall frame	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 (m² • °K)/W	-	-	-	-

## Frame wall with 8 in insulation

U-Value: 0.1911 W/(m² • °K)

Frame wall with 8 in (200 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 9 1/4 in (m² w/ 48 in oc SIP wall frame	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 (m² • °K)/W	-	-	-	-
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Polystyrene 9 1/4 in (m² w/ 48 in oc SIP wall frame	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 (m² • °K)/W	-	-	-	-

## Sheet metal with 6 in insulation

U-Value: 0.2568 W/(m² • °K)

Sheet metal with 6 in (150 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 9 1/4 in (m² w/ 48 in oc SIP wall frame	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 (m² • °K)/W	-	-	-	-
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Polystyrene 9 1/4 in (m² w/ 48 in oc SIP wall frame	Polystyrene 9 1/4 in (230 mm) including SIP wall frame factor	5.14242 (m² • °K)/W	-	-	-	-

## Sheet metal with 8 in insulation

U-Value: 0.1970 W/(m² • °K)

Sheet metal with 8 in (200 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)

## Frame wall with 6 in insulation and 4 in brick veneer

U-Value: 0.2617 W/(m<sup>2</sup> • °K)

Frame wall with 6 in (150 mm) insulation and 4 in (100 mm) brick veneer

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Frame wall with 12 in insulation and 4 in brick veneer

U-Value: 0.1358 W/(m<sup>2</sup> • °K)

Frame wall with 12 in (300 mm) insulation and 4 in (100 mm) brick veneer

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick

U-Value: 0.3282 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick

U-Value: 0.2365 W/(m<sup>2</sup> • °K)

4 in (100 mm) face brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick

4 in (100 mm) face brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick

4 in (100 mm) face brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 4 in face brick

4 in (100 mm) face brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## Metal curtain wall with 3 in insulation

Metal curtain wall with 3 in (75 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Metal curtain wall with 2 in insulation

Metal curtain wall with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Metal curtain wall with 1 in insulation

Metal curtain wall with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)

## Wall 12 in concrete with 2 in insulation on the outside

U-Value: 0.6404 W/(m² • °K)

Wall 12 in (300 mm) concrete with 2 in (50 mm) insulation on the outside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
12 in lightweight concrete block	12 in (300 mm) lightweight concrete block	-	0.3048 m	0.71 W/(m • °K)	512 kg/m³	880 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## Wall 8 in concrete with 2 in insulation on the outside

U-Value: 0.6654 W/(m² • °K)

Wall 8 in (200 mm) concrete with 2 in (50 mm) insulation on the outside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m³	880 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## Wall 4 in concrete with 2 in insulation on the outside

U-Value: 0.6925 W/(m² • °K)

Wall 4 in (100 mm) concrete with 2 in (50 mm) insulation on the outside

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m³	880 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

## 4 in face brick with 2 in insulation

U-Value: 0.5255 W/(m² • °K)

4 in (100 mm) face brick with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)

<b>Spandrel glass, R-10 insulation board, gyp board</b>		<b>U-Value: 0.428 W/(m<sup>2</sup> • °K)</b>
---	--	--

Spandrel glass, R-10 insulation board, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

<b>Metal wall panel, R-10 insulation board, gyp board</b>		<b>U-Value: 0.429 W/(m<sup>2</sup> • °K)</b>
---	--	--

Metal wall panel, R-10 insulation board, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

<b>Metal wall panel, sheathing, R-11 batt insulation, gyp board</b>		<b>U-Value: 0.419 W/(m<sup>2</sup> • °K)</b>
---	--	--

Metal wall panel, sheathing, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance - °K/W	0.04000 (m <sup>2</sup>	-	-	-	-

Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 1 in stone, R-10 insulation board, gyp board

U-Value: 0.428 W/(m<sup>2</sup> • °K)

1 in (25 mm) stone, R-10 insulation board, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance)	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stone	1 in (25 mm) stone	-	0.0254 m	3.17 W/(m • °K)	2560 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance)	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 1 in stone, sheathing, R-11 batt insulation, gyp board

U-Value: 0.417 W/(m<sup>2</sup> • °K)

1 in (25 mm) stone, sheathing, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> resistance)	-	-	-	-
1 in stone	1 in (25 mm) stone	-	0.0254 m	3.17 W/(m • °K)	2560 kg/m <sup>3</sup>	790 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> resistance)	-	-	-	-

## 1 in stucco, sheathing, R-11 batt insulation, gyp board

U-Value: 0.413 W/(m<sup>2</sup> • °K)

1 in (25 mm) stucco, sheathing, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 1 in stucco, 8 in heavyweight CMU, R-11 batt insulation, gyp board

U-Value: 0.414 W/(m<sup>2</sup> • °K)

1 in (25 mm) stucco, 8 in (200 mm) heavyweight CMU, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in lightweight concrete block (filled)	8 in (200 mm) lightweight concrete block (filled)	-	0.2032 m	0.26 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> resistance • °K)/W	-	-	-	-

## Wood siding, sheathing, batt insulation, 1/2 in wood

U-Value: 0.406 W/(m<sup>2</sup> • °K)

Wood siding, sheathing, batt insulation, 1/2 in (12 mm) wood [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood siding	Wood siding	-	0.0127 m	0.09 W/(m • °K)	592 kg/m <sup>3</sup>	1170 J/(kg • °K)
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> resistance • °K)/W	-	-	-	-

## EIFS finish, R-5 insulation board, sheathing, gyp board

U-Value: 0.668 W/(m<sup>2</sup> • °K)

EIFS finish, R-5 insulation board, sheathing, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
EIFS finish	EIFS finish	-	0.0095 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Synthetic stucco, R-5 plus R-11 insulation, gypsum board

U-Value: 0.305 W/(m<sup>2</sup> • °K)

Synthetic stucco (EIFS) finish, R-5 insulation board, sheathing, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
EIFS finish	EIFS finish	-	0.0095 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Synthetic stucco, insulation, sheathing, light concrete, gypsum

U-Value: 0.524 W/(m<sup>2</sup> • °K)

EIFS finish, R-5 insulation board, sheathing, 8 in (200 mm) lightweight CMU, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
EIFS finish	EIFS finish	-	0.0095 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
Wall air space	Wall air space resistance	0.15000 (m <sup>2</sup>	-	-	-	-

resistance		• °K)/W				
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Synthetic stucco, insulation, concrete, gypsum

U-Value: 0.467 W/(m<sup>2</sup> • °K)

EIFS finish, R-10 insulation board, 8 in (200 mm) heavyweight concrete, gypsum [Source: ASHRAE]

## Synthetic stucco, insulation board, light concrete, gypsum

U-Value: 0.650 W/(m<sup>2</sup> • °K)

EIFS finish, R-5 insulation board, 8 in (200 mm) lightweight concrete, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
EIFS finish	EIFS finish	-	0.0095 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brick, R-5 insulation board, sheathing, gypsum

U-Value: 0.571 W/(m<sup>2</sup> • °K)

Brick, R-5 insulation board, sheathing, gypsum board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance)	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance)	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Brick, sheathing, R-11 batt insulation,

U-Value: 0.377 W/(m<sup>2</sup> • °K)

## gypsum

Brick, sheathing, R-11 batt insulation, gypsum board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance)	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance)	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

## Brick, R-5 plus R-11 insulation with sheathing, gypsum

U-Value: 0.283 W/(m<sup>2</sup> • °K)

Brick, R-5 insulation board, sheathing, R-11 batting insulation, gypsum board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> resistance • °K)/W	-	-	-	-

## Brick, R-5 insulation board, 8 in light- weight concrete block

U-Value: 0.581 W/(m<sup>2</sup> • °K)

Brick, R-5 insulation board, 8 in (200 mm) lightweight CMU [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-

R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m³	880 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m² • °K)/W	-	-	-	-

## Brick, 8 in lightweight CMU, R-11 batt insulation, gyp board

U-Value: 0.348 W/(m² • °K)

Brick, 8 in (200 mm) lightweight CMU, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m² • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
8 in lightweight concrete block	8 in (200 mm) lightweight concrete block	-	0.2032 m	0.50 W/(m • °K)	464 kg/m³	880 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m² • °K)/W	-	-	-	-

## Brick, R-5 insulation board, 8 in heavyweight CMU, gyp board

U-Value: 0.628 W/(m² • °K)

Brick, R-5 insulation board, 8 in (200 mm) heavyweight CMU, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m² • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m³	920 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m² • °K)/W	-	-	-	-

## Brick, R-5 insulation board, brick

U-Value: 0.702 W/(m² • °K)

Brick, R-5 insulation board, brick [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m² • °K)/W	-	-	-	-

resistance		$\cdot \text{ }^{\circ}\text{K}/\text{W}$				
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Wall air space resistance	Wall air space resistance	0.15000 (m² • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m² • °K)/W	-	-	-	-

## Brick, R-5 insulation board, 8 in lightweight concrete, gyp board

U-Value: 0.514 W/(m² • °K)

Brick, R-5 insulation board, 8 in (200 mm) lightweight concrete, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m² • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m³	840 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m² • °K)/W	-	-	-	-

## Brick, R-5 insulation board, 12 in heavyweight concrete, gyp board

U-Value: 0.581 W/(m² • °K)

Brick, R-5 insulation board, 12 in (300 mm) heavyweight concrete, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m² • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
Wall air space	Wall air space resistance - resistance	0.15000 (m² • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)

Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-
------------------------------------	------------------------------------	------------------------------------	---	---	---	---

<b>Brick, 8 in heavyweight concrete, R-11 batt insulation, gyp board</b>		<b>U-Value: 0.389 W/(m<sup>2</sup> • °K)</b>
--	--	--

Brick, 8 in (200 mm) heavyweight concrete, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)
Wall air space	Wall air space resistance	0.15000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

<b>4 in lightweight concrete, R-5 board insulation, gyp board</b>		<b>U-Value: 0.673 W/(m<sup>2</sup> • °K)</b>
---	--	--

4 in (100 mm) lightweight concrete, R-5 board insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Inside vertical surface	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

<b>4 in lightweight concrete, R-11 batt insulation, gyp board</b>		<b>U-Value: 0.418 W/(m<sup>2</sup> • °K)</b>
---	--	--

4 in (100 mm) lightweight concrete, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
EIFS finish	EIFS finish	-	0.0095 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 4 in lightweight concrete, R-10 board insulation, 4 in lightweight concrete

U-Value: 0.434 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete, R-10 board insulation, 4 in (100 mm) lightweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 8 in lightweight CMU, R-11 batt insulation, gyp board

U-Value: 0.383 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight CMU, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 8 in concrete block, filled, R-11 insulation, gypsum

U-Value: 0.335 W/(m<sup>2</sup> • °K)

8 in (200 mm) light-weight concrete block (CMU) with fill insulation, R-11 batt insulation and gypsum board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in lightweight concrete block (filled)	8 in (200 mm) lightweight concrete block (filled)	-	0.2032 m	0.26 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

U-Value: 1.056 W/(m<sup>2</sup> • °K)

## 8 in lightweight CMU with fill insulation

8 in (200 mm) lightweight CMU with fill insulation [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m <sup>2</sup> resistance)	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
12 in lightweight concrete block (filled)	12 in (300 mm) lightweight concrete block (filled)	-	0.3048 m	0.29 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)
Wall air space (m <sup>2</sup> resistance)	Wall air space resistance	0.15000 • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface (m <sup>2</sup> resistance)	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

## 8 in lightweight CMU with fill insulation, gyp board

U-Value: 0.834 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight CMU with fill insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance skirted	0.04000 (m <sup>2</sup> )	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Wall air space	Wall air space resistance - resistance skirted	0.15000 (m <sup>2</sup> )	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance skirted	0.12000 (m <sup>2</sup> ) resistance	-	-	-	-

## 8 in lightweight concrete, R-11 batt insulation, gyp board

U-Value: 0.387 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance skirted	0.04000 (m <sup>2</sup> )	-	-	-	-
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance skirted	0.12000 (m <sup>2</sup> ) resistance	-	-	-	-

## 8 in heavyweight concrete, R-11 batt insulation, gyp board

U-Value: 0.434 W/(m<sup>2</sup> • °K)

8 in (200 mm) heavyweight concrete, R-11 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Inside vertical surface resistance	Inside vertical surface resistance	0.12000 • °K)/W	-	-	-	-

## 12 in lightweight CMU with fill insulation, gyp board

U-Value: 0.689 W/(m<sup>2</sup> • °K)

12 in (300 mm) lightweight CMU with fill insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 12 in heavyweight concrete, R-19 batt insulation, gyp board

U-Value: 0.266 W/(m<sup>2</sup> • °K)

12 in (300 mm) heavyweight concrete, R-19 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in concrete block	8 in (200 mm) concrete block	-	0.2032 m	1.11 W/(m • °K)	800 kg/m <sup>3</sup>	920 J/(kg • °K)
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside vertical surface	Inside vertical surface - resistance	0.12000 (m <sup>2</sup> • °K)/W	-	-	-	-

## 12 in heavyweight concrete

U-Value: 3.122 W/(m<sup>2</sup> • °K)

12 in (300 mm) heavyweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
8 in lightweight concrete block (filled)	8 in (200 mm) lightweight concrete block (filled)	-	0.2032 m	0.26 W/(m • °K)	464 kg/m <sup>3</sup>	880 J/(kg • °K)

Inside vertical surface resistance	Inside vertical surface resistance	0.12000 (m <sup>2</sup> )	-	-	-	-
------------------------------------	------------------------------------	------------------------------	---	---	---	---

## R-0 8 in CMU wall

U-Value: 6.452772 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R0 concrete or block wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05))	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-20 8 in CMU wall

U-Value: 0.261523 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R20 concrete or block wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05))	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)

## R-0 wood frame wall

U-Value: 1.912221 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R0 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in 0.019049 m (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R0 w/ - 2x4 frame	Batt, R-0 including framing - 2x4 frame	0.17083 (m <sup>2</sup> factor)	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-11.4 8 in CMU wall

U-Value: 0.486022 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R11.4 concrete or block wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05))	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool Fill 3 1/2 in (m <sup>2</sup> R11 (IN11))	R11 Fill, 3 1/2 in (8.9 cm)	1.90255 • °K)/W	0.088906 m	0.046730 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13 + R10 metal frame wall

U-Value: 0.331646 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 + R10 sheathing 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

Face brick 4 in (BK05)	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### R-13 + R13 metal frame wall

U-Value: 0.281630 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 + R13 exterior 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 7/8 in R-3	R-3.0 MinBd 7/8 in (2.2 cm) 0.041538 W/(m (N21)	0.53491 (m <sup>2</sup> • °K)/W	0.022219 m	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)	
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

### R-13 + R3.8 wood frame wall

U-Value: 0.368868 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 + R3.8 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Polystyrene 1 in	Polystyrene 1 in (25 mm) 0.034615 W/(m (IN33)	0.73347 (m <sup>2</sup> • °K)/W	0.025389 m	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R13 w/ - 2x4 frame	Batt, R-13 including framing factor	1.62550 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

### R-13 + R7.5 wood frame wall

U-Value: 0.290248 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 + R7.5 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick	0.07747 • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
Polystyrene 2 in (IN35)	Polystyrene 2 in (3.1 cm)	1.4678033 • °K)/W	0.050808 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ 2x4 frame	Batt, R-13 including framing factor	1.62550 • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### R-13.3 8 in concrete

U-Value: 0.410167 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13.3 concrete [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Cellulose 3 1/2 in R- 13 (IN13)	Cellulose 3 1/2 in (8.9 cm)	2.28304 (m <sup>2</sup> • °K)/W	0.088906 m	0.038942 W/(m • °K)	48.060000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

### R-15.2 8 in concrete

U-Value: 0.384421 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R15.2 concrete [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)

### R-5.7 8 in concrete

U-Value: 0.882216 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R5.7 concrete [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Roof Insul 2 in (IN74)	Roof Insul 2 in (3.1 cm)	0.97854 (m <sup>2</sup> • °K)/W	0.050808 m	0.051922 W/(m • °K)	256.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### R7.6 8 in concrete

U-Value: 0.725613 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R7.6 concrete [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317(• °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
-----------------------	--------------------------	-----------------	------------	---------------------	------------------------------	------------------------

## R9.5 8 in concrete

U-Value: 0.932435 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R9.5 concrete [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 1 1/4 in (IN34)	Polystyrene 1 1/4 in (3.2 cm)	0.91749 (m <sup>2</sup> • °K)/W	0.031759 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)

## R-0 8 in CMU under ground wall

U-Value: 0.179987 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious	Fictitious insulation place - insulation	5.2833` (m <sup>2</sup> • holder °K)/W	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m	0.11799 (m <sup>2</sup> • °K)/W	0.204206 m	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Conc heavyweight	Conc heavyweight 140lb 8 in (CC05) 1.311205 W/(m 140lb 8 in)	0.15497 (m <sup>2</sup> • °K)/W (20.3cm)	0.203200 m	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R7.5 8 in CMU under ground wall

U-Value: 0.179987 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R7.5 concr. or block underground wall w/ soil layer and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious	Fictitious insulation place - insulation	5.28331 (m <sup>2</sup> • holder °K)/W	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m	0.11799 (m <sup>2</sup> • °K)/W	0.204206 m	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Conc heavyweight	Conc heavyweight 140lb 8 in (CC05) 1.311205 W/(m 140lb 8 in)	0.15497 (m <sup>2</sup> • °K)/W (20.3cm)	0.203200 m	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-19 wood frame wall

U-Value: 0.347873 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R19 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01))	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.44617 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-21 wood frame wall

U-Value: 0.291822 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R21 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls	0.15392 • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
Polyurethane 1/2 in (IN41)	Polyurethane 1/2 in (1.3 cm)	0.55215 • °K)/W	0.012710 m	0.023019 W/(m • °K)	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.44617 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13 wood frame wall

U-Value: 0.486858 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m • °K)	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ - 2x4 frame	Batt, R-13 including framing - 2x4 frame	1.62550 (m <sup>2</sup> factor • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-30 wood frame wall

U-Value: 0.212359 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R30 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m • °K)	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.44617 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-15 wood frame wall

U-Value: 0.321845 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R15 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls	0.15392 • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m³	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m³	1381.644000 J/(kg • °K)
Insul Bd 3 in (HF-B4)	Insul Bd 3 in (7.6 cm)	1.76102 °K)/W	0.076196 m	0.043268 W/(m • °K)	32.040000 kg/m³	837.360000 J/(kg • °K)
Polystyrene 1/2 in (IN31)	Polystyrene 1/2 in (1.3 cm)	0.36718 • °K)/W	0.012710 m	0.034615 W/(m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
Polystyrene 3/4 in (IN32)	Polystyrene 3/4 in (1.9 cm)	0.55031 • °K)/W	0.019049 m	0.034615 W/(m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

## R-2.7 8 in CMU under ground wall

U-Value: 1.214657 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m • °K)	0.11799 (m² • °K)/W	0.204206 m • °K)	0.204206 m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Polystyrene 3/4 in	Polystyrene 3/4 in (1.9 cm) 0.034615 W/(m (IN32)	0.55031 (m² • °K)/W	0.019049 m • °K)	0.019049 m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
Conc heavyweight	Conc heavyweight 140lb 8 in 1.311205 W/(m 140lb 8 in (CC05)	0.15497 (m² • °K)	0.203200 m • °K)	0.203200 m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)

## R-4 8 in CMU under ground wall

U-Value: 0.993618 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m • °K)	0.11799 (m² • °K)/W	0.204206 m • °K)	0.204206 m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Polystyrene 1 in	Polystyrene 1 in (25 mm) 0.034615 W/(m (IN33)	0.73347 (m² • °K)/W	0.025389 m • °K)	0.025389 m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
Conc heavyweight	Conc heavyweight 140lb 8 in 1.311205 W/(m 140lb 8 in (CC05)	0.15497 (m² • °K)	0.203200 m • °K)	0.203200 m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)

## R-5.4 8 in CMU under ground wall

U-Value: 0.840019 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m • °K)	0.11799 (m² • °K)/W	0.204206 m • °K)	0.204206 m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Polystyrene 1 1/4 in	Polystyrene 1 1/4 in (3.2 0.034615 W/(m (IN34)	0.91749 (m² cm) • °K)/W	0.031759 m • °K)	0.031759 m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
Conc heavyweight	Conc heavyweight 140lb 8 in 1.311205 W/(m 140lb 8 in (CC05)	0.15497 (m² • °K)	0.203200 m • °K)	0.203200 m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)

## R8.1 8 in CMU under ground wall

U-Value: 0.574460 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 • °K)/W	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Polystyrene 2 in (IN35)	Polystyrene 2 in (3.1 cm)	1.46780 • °K)/W	0.050808 m	0.034615 W/(m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)

### R-10.8 8 in CMU under ground wall

U-Value: 0.474529 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m • °K)	0.11799 (m² • °K)/W	0.204206 m	1842.300000 kg/m³	837.360000 J/(kg • °K)	
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m² • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m³	711.756000 J/(kg • °K)
Conc heavyweight	Conc heavyweight 140lb 8 in 1.311205 W/(m 140lb 8 in (CC05) • °K)	0.15497 (m² • °K)/W	0.203200 m (20.3cm)	2242.800000 kg/m³	837.360000 J/(kg • °K)	

### R-12.5 8 in CMU under ground wall

U-Value: 0.404166 W/(m² • °K)

ASHRAE 90.1 compliant underground wall with proxy soil and insulation layer [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm) 1.730735 W/(m • °K)	0.11799 (m² • °K)/W	0.204206 m	1842.300000 kg/m³	837.360000 J/(kg • °K)	
Polystyrene 3 in	Polystyrene 3 in (7.6 cm) 0.034615 W/(m (IN36)	2.20124 (m² • °K)/W	0.076196 m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)	
Conc heavyweight	Conc heavyweight 140lb 8 in 1.311205 W/(m 140lb 8 in (CC05) • °K)	0.15497 (m² • °K)/W	0.203200 m (20.3cm)	2242.800000 kg/m³	837.360000 J/(kg • °K)	

### R-11 wood frame wall

U-Value: 0.528057 W/(m² • °K)

ASHRAE 90.1 compliant R11 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m • °K)	0.15392 (m² • °K)/W	0.017769 m	-	512.640000 kg/m³	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m² • °K)/W	-	-	-	-
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m² • °K)/W	0.019049 m • °K)	512.640000 kg/m³	1381.644000 J/(kg • °K)	
Minwool batt R11 w/ - 2x4 frame	Batt, R-11 including framing - 2x4 frame	1.46524 (m² factor • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m • °K)	0.09908 (m² • °K)/W	0.015879 m	801.000000 kg/m³	837.360000 J/(kg • °K)	

### R-19 8 in concrete

U-Value: 0.243826 W/(m² • °K)

ASHRAE 90.1 compliant R19 concrete wall R = 23.29, U = 0.0429 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight	Conc heavyweight 140lb 8 in	0.15497 (m² • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)

140lb 8 in (CC05)	(20.3cm)	• °K)/W	• °K)	kg/m <sup>3</sup>	J/(kg • °K)
MinBd 1 in R-3 (IN22)	R-3.5 MinBd 1 in (2.5 cm)	0.61122 • °K)/W	0.025389 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup> J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup> J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup> J/(kg • °K)
Air Lay < 3/4 in Vert (AL11)	Air space in vertical walls	0.15850 • °K)/W	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup> J/(kg • °K)

## R-38 wood frame wall

U-Value: 0.154496 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R38 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.44617 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-11.4 8 in concrete

U-Value: 0.526280 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R11.4 concrete R=10.78 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 2 in (m <sup>2</sup> (IN35)	Polystyrene 2 in (3.1 cm)	1.46780 • °K)/W	0.050808 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
Air Lay < 3/4 in Vert (AL11)	Air space in vertical walls 0.15850 (m <sup>2</sup> (AL11)	-	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13.3 8 in concrete

U-Value: 0.441167 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13.3 concrete R=12.87 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)

Air Lay < 3/4 in Vert (AL11)	Air space in vertical walls	0.15850 (m <sup>2</sup> )	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> )	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-15.2 8 in concrete

U-Value: 0.379710 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R15.2 concrete R=14.95 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05))	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> )	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3 in (m <sup>2</sup> (IN36))	Polystyrene 3 in (7.6 cm)	2.20124 (m <sup>2</sup> )	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
Air Lay < 3/4 in Vert (AL11)	Air space in vertical walls 0.15850 (m <sup>2</sup> )	-	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> )	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13+3.8 wood frame wall

U-Value: 0.378982 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13+3.8 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m)	0.15392 (m <sup>2</sup> )	0.017769 m	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> )	-	-	-	-
Insul Bd 1 in (HF-B5)	Insul Bd 1 in (2 1/2 cm) 0.043268 W/(m)	0.58466 (m <sup>2</sup> )	0.025297 m	91.314000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m) (WD01)	0.16501 (m <sup>2</sup> )	0.019049 m	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R13 w/ - 2x4 frame	Batt, R-13 including framing - 2x4 frame	1.62550 (m <sup>2</sup> )	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m)	0.09908 (m <sup>2</sup> )	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-13+7.5 wood frame wall

U-Value: 0.291233 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13+7.5 sheathing 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 0.115440 W/(m)	0.15392 (m <sup>2</sup> )	0.017769 m	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> )	-	-	-	-
Polyurethane 1 1/4 in	Polyurethane 1 1/4 in (3.2 0.023019 W/(m) (IN44))	1.37969 (m <sup>2</sup> )	0.031759 m	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)	
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m) (WD01)	0.16501 (m <sup>2</sup> )	0.019049 m	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R13 w/ - 2x4 frame	Batt, R-13 including framing - 2x4 frame	1.62550 (m <sup>2</sup> )	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m)	0.09908 (m <sup>2</sup> )	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

R-0 metal frame wall				U-Value: 3.253685 W/(m² • °K)		
R0 16 in (400 mm) on center metal framed wall, typical for interior walls [Source: GBS]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)	0.015879	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall - or no air space	0.10919 (m² • °K)	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)	0.015879	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

  

R9 curtain wall				U-Value: 0.578705 W/(m² • °K)		
R9 curtain wall [Source: GBS]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick	0.07747 (m² • °K)	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m³	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m² • °K)	-	-	-	-
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m² • °K)	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

R-11 UG ex-wall				U-Value: 0.497089 W/(m² • °K)		
R11 UG ex-wall [Source: GBS]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m² • °K)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Wood shingle (WS01)	For walls	0.15392 (m² • °K)	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m³	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m² • °K)	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m² • °K)	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m³	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.46524 (m² • °K)	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

R-13 UG ex-wall				U-Value: 0.460414 W/(m² • °K)		
R13 UG ex-wall [Source: GBS]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m² • °K)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Wood shingle (WS01)	For walls	0.15392 (m² • °K)	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m³	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m² • °K)	-	-	-	-
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm)	0.16501 (m² • °K)	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m³	1381.644000 J/(kg • °K)

(WD01)		• °K)/W		• °K)	kg/m <sup>3</sup>	J/(kg • °K)
Minwool batt R13 w/ 2x4 frame	Batt, R-13 including framing factor	1.62550 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-15 UG ex-wall

U-Value: 0.378228 W/(m<sup>2</sup> • °K)

R15 UG ex-wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> • °K)/W	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Wood shingle (WS01)	For walls	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R15 w/ 2x4 frame	Batt, R-15 including framing factor	2.09747 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-19 UG ex-wall

U-Value: 0.334160 W/(m<sup>2</sup> • °K)

R19 UG ex-wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> • °K)/W	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Wood shingle (WS01)	For walls	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.44617 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-30 8 in concrete

U-Value: 0.168604 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall with R30 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)

MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Air Lay < 3/4 in Vert (AL11)	Air space in vertical walls	0.15850 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in concrete wall with perlite filled cores

U-Value: 0.971834 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall with perlite filled cores [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
CMU MW 8 in PerlFill (m <sup>2</sup> (CB33))	Perlite filled 8 in (20.3 cm)	1.02898 • °K)/W	0.203200 m	0.197477 W/(m • °K)	897.120000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in concrete wall with poured cores

U-Value: 4.222068 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall with poured cores [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
CMU MW 8 in ConcFill (m <sup>2</sup> (CB32))	Concrete filled 8 in (20.3 cm)	0.23685 • °K)/W	0.203200 m	0.857925 W/(m • °K)	1970.460000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in concrete wall hollow

U-Value: 3.301339 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall hollow [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
CMU MW 8 in hollow (CB31)	Hollow 8 in (20.3 cm)	0.30291 (m <sup>2</sup> • °K)/W	0.203200 m	0.670833 W/(m • °K)	849.060000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in CMU with concrete poured concrete

U-Value: 2.312985 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall with concrete poured cores R = 2.45, U = 0.408 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
CMU heavyweight 8 in	Concrete filled 8 in (20.3 cm) 1.311032 W/(m ConcFill (CB12))	0.15499 (m <sup>2</sup> • °K)/W	0.203200 m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Air Lay < 3/4 in Vert - (AL11)	Air space in vertical walls	0.15850 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm) 0.160266 W/(m	0.11886 • °K)/W	0.019049 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## 8 in CMU with perlite poured concrete

U-Value: 1.259280 W/(m<sup>2</sup> • °K)

8 in (200 mm) concrete wall with concrete poured cores R = 4.5, U = 0.222 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
CMU heavyweight 8 in	Perlite filled 8 in (20.3 cm) 0.393223 W/(m PerlFill (CB13))	0.51676 (m <sup>2</sup> • °K)/W	0.203200 m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Air Lay < 3/4 in Vert - (AL11)	Air space in vertical walls	0.15850 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm) 0.160266 W/(m	0.11886 • °K)/W	0.019049 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## Straw bale wall

U-Value: 0.186824 W/(m<sup>2</sup> • °K)

Straw bale, 3-string, 23 in (600 mm), R30 [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm)	0.03520 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Straw bale	Straw bale, 3-string, 23 inch (600 mm)	5.2822 (m <sup>2</sup> • °K)/W	0.584182 m	0.110594 W/(m • °K)	112.140000 kg/m <sup>3</sup>	1339.776000 J/(kg • °K)
Stucco 1 in (SC01)	Stucco 1 in (25 mm)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Insulated concrete form (ICF) wall, 10" thick form

U-Value: 0.207854 W/(m<sup>2</sup> • °K)

Insulated concrete form (ICF) wall, 10" thick form [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Polystyrene 3 in (m <sup>2</sup> (IN36))	Polystyrene 3 in (7.6 cm)	2.20124 (m <sup>2</sup> • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
ConcLW 80lb 4 in (SK24)	ConcLW 80lb 4 in (10.2 cm) 0.28178 (m <sup>2</sup> (CC24))	•	0.101585 m	0.360512 W/(m • °K)	1281.600000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3 in (m <sup>2</sup> (IN36))	Polystyrene 3 in (7.6 cm)	2.20124 (m <sup>2</sup> • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Insulated concrete form (ICF) wall, 12" thick form

U-Value: 0.205809 W/(m<sup>2</sup> • °K)

Insulated concrete form (ICF) wall, 12" thick form [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm)	0.03520 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Polystyrene 3 in (m <sup>2</sup> (IN36))	Polystyrene 3 in (7.6 cm)	2.20124 (m <sup>2</sup> • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
ConcLW 80lb 6 in (SK25)	ConcLW 80lb 6 in (15.2 cm) 0.422712.4 (m <sup>2</sup> (CC25))	•	0.152393 m	0.360512 W/(m • °K)	1281.600000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3 in (m <sup>2</sup> (IN36))	Polystyrene 3 in (7.6 cm)	2.20124 (m <sup>2</sup> • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Insulated concrete form (ICF) wall, 14" thick form

U-Value: 0.196824 W/(m<sup>2</sup> • °K)

Insulated concrete form (ICF) wall, 14" thick form [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm)	0.03520 • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
Polystyrene 3 in (IN36)	Polystyrene 3 in (7.6 cm)	2.20124 • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
ConcLW 80lb 8 in (CC26)	ConcLW 80lb 8 in (20.2 cm)	0.56364 • °K)/W	0.203200 m	0.360512 W/(m • °K)	1281.600000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3 in (IN36)	Polystyrene 3 in (7.6 cm)	2.20124.5 • °K)/W	0.076196 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 • °K)/W	0.012710 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### Structurally ins. panel (SIP) wall 4 1/2 in (114 mm)

U-Value: 0.384404 W/(m<sup>2</sup> • °K)

Structurally insulated panel (SIP) wall 4 1/2 in (114 mm) thick, 48 in o.c., R-14 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm) 0.721197 W/(m • °K)	0.03520 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m • °K)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

### Structurally ins. panel (SIP) wall 6 1/2 in

U-Value: 0.274693 W/(m<sup>2</sup> • °K)

Structurally ins. panel (SIP) 6 1/2 in (162 mm) wall, 48 in o.c., R-22 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm) 0.721197 W/(m • °K)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	0.721197 W/(m • °K)	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 5 1/2 in	Polystyrene 5 1/2 in (140 - w/48 in oc SIP wall • °K)/W	3.24043 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m • °K)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

### Structurally ins. panel (SIP) wall 8 1/4 in

U-Value: 0.219484 W/(m<sup>2</sup> • °K)

## (210 mm)

Structurally ins. panel (SIP) wall 8 1/4 in (210 mm) thick, 48 in o.c., R-28 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm) 0.721197 W/(m <sup>2</sup> • °K)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 7 1/4 in	Polystyrene 7 1/4 in (180 - w/ 48 in oc SIP wall • °K)/W	4.15620 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m <sup>2</sup> • °K)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## Structurally ins. panel (SIP) wall 10 1/4 in (260 mm)

U-Value: 0.180430 W/(m<sup>2</sup> • °K)

Structurally ins. panel (SIP) wall 10 1/4 in (260 mm) thick, 48 in o.c., R-36 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm) 0.721197 W/(m <sup>2</sup> • °K)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 9 1/4 in	Polystyrene 9 1/4 in (230 - w/ 48 in oc SIP wall • °K)/W	5.14242 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m <sup>2</sup> • °K)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## Structurally ins. panel (SIP) wall 12 1/4 in (311 mm)

U-Value: 0.152354 W/(m<sup>2</sup> • °K)

Structurally ins. panel (SIP) wall 12 1/4 in (311 mm) thick, 48 in o.c., R-44 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Stucco 1 in (SC01)	Stucco 1 in (25 mm) 0.721197 W/(m <sup>2</sup> • °K)	0.03502 (m <sup>2</sup> • °K)/W	0.025389 m	2659.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 11 1/4 in	Polystyrene 11 1/4 in (290 - w/ 48 in oc SIP wall • °K)/W	6.16386 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m <sup>2</sup> • °K)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	

GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 • °K)/W	0.012710 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
---------------------	-----------------------	--------------------	------------	------------------------	---------------------------------	---------------------------

R-2 CMU wall			U-Value: 1.414207 W/(m <sup>2</sup> • °K)			
--------------	--	--	---	--	--	--

2001 title 24 90.1 compliant R2 mass wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polyurethane 1/2 in (IN41)	Polyurethane 1/2 in (1.3 cm)	0.55215 (m <sup>2</sup> • °K)/W	0.012710 m	0.023019 W/(m • °K)	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)

R-13 wood frame wall			U-Value: 0.505679 W/(m <sup>2</sup> • °K)			
----------------------	--	--	---	--	--	--

2001 title 24 compliant R13 16 in (400 mm) on center wood framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in 0.019049 m (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ - 2x4 frame OKA01	Batt, R-13 including framing - 2x4 frame OKA01	1.62550 (m <sup>2</sup> factor)	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

R-11 metal frame wall			U-Value: 1.033300 W/(m <sup>2</sup> • °K)			
-----------------------	--	--	---	--	--	--

2001 title 24 compliant R11 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R11 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.78070 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

R-13 metal frame wall			U-Value: 0.984399 W/(m <sup>2</sup> • °K)			
-----------------------	--	--	---	--	--	--

2001 title 24 compliant R13 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-

GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
---------------------	-----------------------	--------------------	------------	------------------------	---------------------------------	---------------------------

## R-15 metal frame wall

U-Value: 0.949186 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R15 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R15 w/ factor	Batt, R-11 including mtl - Mtl frame factor	0.86646 (m <sup>2</sup> framing)	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-19 metal frame wall

U-Value: 0.784597 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R19 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R19 w/ Mtl frame	Batt, R-19 including mtl framing factor	1.08748 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-30 metal frame wall

U-Value: 0.329428 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R30 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05) m	4 in (10.1cm) face brick	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Insul Bd 3 in (HF-B4) m	Insul Bd 3 in (7.6 cm)	1.76102 (m <sup>2</sup> • °K)/W	0.076196 m	0.043268 W/(m • °K)	32.040000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 w/ Mtl frame	Batt, R-19 including mtl framing factor	1.08748 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02) m	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13+R13 metal frame wall

U-Value: 0.542130 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R13+R13 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m • °K)	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	0.160266 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)

Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-15+R15 metal frame wall

U-Value: 0.520848 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R15+R15 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)	
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R15 w/ - Mtl frame	Batt, R-11 including mtl framing factor	0.86646 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R15 w/ - Mtl frame	Batt, R-11 including mtl framing factor	0.86646 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-38 metal frame wall

U-Value: 0.234538 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R38 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick m	0.07747 (m <sup>2</sup> • °K)/W	0.101585 m	1.311205 W/(m • °K)	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool Fill 5 1/2 in R19 (IN12)	R19 Fill, 5 1/2 in (13.4 cm)	2.98915 (m <sup>2</sup> • °K)/W	0.139683 m	0.046730 W/(m • °K)	10.092600 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 w/ Mtl frame	Batt, R-19 including mtl framing factor	1.08748 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm) m	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13+3.8 metal frame wall

U-Value: 0.624802 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R13+3.8 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m	0.07747 (m <sup>2</sup> • °K)/W	-	0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Insul Bd 1 in (HF-B5)	Insul Bd 1 in (2 1/2 cm) 0.043268 W/(m	0.58466 (m <sup>2</sup> • °K)/W	-	0.025297 m	91.314000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R13 w/	Batt, R-11 including mtl	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-

Mtl frame	framing factor	(m <sup>2</sup> • °K)/W				
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-13+7.5 metal frame wall

U-Value: 0.417444 W/(m<sup>2</sup> • °K)

2001 title 24 compliant R13+7.5 16 in (400 mm) on center metal framed wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m • °K)	0.07747 (m <sup>2</sup> • °K)/W	-	0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Polyurethane 1 1/4 in	Polyurethane 1 1/4 in (3.2 cm) 0.023019 W/(m (IN44))	1.37969 (m <sup>2</sup> • °K)/W	-	0.031759 m	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)
Minwool batt R13 w/ Mtl frame	Batt, R-11 including mtl framing factor	0.82877 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm) 0.160266 W/(m • °K)	0.09908 (m <sup>2</sup> • °K)/W	-	0.015879 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-3 8 in CMU wall

U-Value: 1.417857 W/(m<sup>2</sup> • °K)

2004 Oregon compliant U 0.3 (R-3)mass wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 3/4 in (IN32)	Polystyrene 3/4 in (1.9 cm)	0.55031 (m <sup>2</sup> • °K)/W	0.019049 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)

## R-4 8 in CMU wall

U-Value: 1.125575 W/(m<sup>2</sup> • °K)

2004 Oregon compliant U 0.21 (R-4) mass wall [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight (m <sup>2</sup> 140lb 8 in (CC05))	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polystyrene 1 in (m <sup>2</sup> (IN33))	Polystyrene 1 in (25 mm)	0.73347 (m <sup>2</sup> • °K)/W	0.025389 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)

## R-6 8 in concrete block

U-Value: 0.794961 W/(m<sup>2</sup> • °K)

2004 Oregon compliant U 0.16 (R-6) mass wall. 8 in (200 mm) concrete block (CMU) [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Conc heavyweight	Conc heavyweight 140lb 8 in (1.311205 W/(m 140lb 8 in (CC05)))	0.15497 (m <sup>2</sup> • °K)/W	0.203200 m (20.3cm)	0.203200 m	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Polyurethane 1 in	Polyurethane 1 in (25 mm) 0.023019 W/(m (IN43))	1.10296 (m <sup>2</sup> • °K)/W	-	0.025389 m	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)

## 2 ft stone, 2 in airspace, 1 in dense plaster

U-Value: 1.23 W/(m<sup>2</sup> • °K)

2 ft (600 mm) stone, 2 in (50 mm) airspace, 1 in (25 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hard stone (unspecified)	Hard stone (unspecified)	-	0.600 m	3.49 W/(m • °K)	2880 kg/m³	840 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 • °K)/W	0.050 m	- W/(m • °K)	- kg/m³	- J/(kg • °K)
Plaster (dense)	Plaster (dense)	-	0.025 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)

## Stone, insulation, plasterboard

U-Value: 0.65 W/(m² • °K)

2 ft (600 mm) stone, 2 in (50 mm) airspace, 1 in (25 mm) EPS insulation, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hard stone (unspecified)	Hard stone (unspecified)	-	0.600 m	3.49 W/(m • °K)	2880 kg/m³	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m² • °K)	0.050 m	- W/(m • °K)	- kg/m³	- J/(kg • °K)
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m³	1400 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)

## Render, no-fines concrete, plasterboard

U-Value: 1.50 W/(m² • °K)

3/4 in (19 mm) render, 9 in (225 mm) no-fines concrete, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
No-fines concrete	No-fines concrete	-	0.220 m	0.96 W/(m • °K)	1800 kg/m³	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m² • °K)	0.050 m	- W/(m • °K)	- kg/m³	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)

## Render, no-fines concrete, insulation, plasterboard

U-Value: 0.52 W/(m² • °K)

3/4 in (19 mm) render, 9 in (225 mm) no-fines concrete, 2 in (50 mm) mineral fiber insulation between battens, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)
No-fines concrete	No-fines concrete	-	0.220 m	0.96 W/(m • °K)	1800 kg/m³	840 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.050 m	0.035 W/(m • °K)	30 kg/m³	1000 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)

## Render, mineral fiber insulation, no-fines concrete, plasterboard

U-Value: 0.48 W/(m² • °K)

3/4 in (19 mm) render, 2 in (50 mm) mineral fiber insulation between battens, 9 in (225 mm) no-fines concrete, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.050 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
No-fines concrete	No-fines concrete	-	0.220 m	0.96 W/(m • °K)	1800 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## 9 in solid brick, 1/2 in dense plaster

U-Value: 2.14 W/(m<sup>2</sup> • °K)

9 in (225 mm) solid brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## 9 in solid brick, 1/2 in plasterboard

U-Value: 1.43 W/(m<sup>2</sup> • °K)

9 in (225 mm) solid brick, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace W/(m • °K)	External wall airspace	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	-	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## 9 in solid brick, mineral fiber insulation, plasterboard

U-Value: 0.51 W/(m<sup>2</sup> • °K)

9 in (225 mm) solid brick, 2 in (50 mm) mineral fiber insulation between battens, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.050 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Render, insulation, solid brick, dense plaster

U-Value: 0.49 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) render, 2 in (50 mm) EPS insulation, 9 in (225 mm) solid brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-	Thickness	Conductivity	Density	Specific

Value						Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Brick	Brick	-	0.220 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Render, dense concrete block, dense plaster

U-Value: 2.73 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) render, 8 in (200 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Render, dense concrete block, plasterboard

U-Value: 1.68 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) render, 8 in (200 mm) dense concrete block, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> ) - 0.050 m	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Render, dense concrete block, insulation, plasterboard

U-Value: 0.71 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) render, 8 in (200 mm) dense concrete block, 1 in (25 mm) polyurethane insulation, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Polyurethane insulation	Polyurethane insulation	-	0.025 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Render, insulation, dense concrete block, dense plaster

**U-Value: 0.56 W/(m<sup>2</sup> • °K)**

3/4 in (19 mm) render, 2 in (50 mm) mineral fiber insulation between battens, 8 in (200 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.050 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Dense concrete, 1 in insulation, dense concrete, dense plaster

**U-Value: 0.95 W/(m<sup>2</sup> • °K)**

3 in (75 mm) dense concrete, 1 in (25 mm) EPS insulation, 4 in (100 mm) dense concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Dense concrete	Dense concrete	-	0.080 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Dense concrete, 1 in insulation, dense concrete, plasterboard

**U-Value: 0.78 W/(m<sup>2</sup> • °K)**

3 in (75 mm) dense concrete, 1 in (25 mm) EPS insulation, 4 in (100 mm) dense concrete, 2 in (50 mm) airspace, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Dense concrete	Dense concrete	-	0.080 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> )	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Dense concrete, 2 in insulation, dense concrete, plasterboard

**U-Value: 0.55 W/(m<sup>2</sup> • °K)**

3 in (75 mm) dense concrete, 2 in (50 mm) EPS insulation, 4 in (100 mm) dense concrete, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Dense concrete	Dense concrete	-	0.080 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Render, dense concrete, insulation, dense concrete, dense plaster

U-Value: 0.56 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) render, 3 in (75 mm) dense concrete, 2 in (50 mm) EPS insulation, 4 in (100 mm) dense concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
External render	External render	-	0.019 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
Dense concrete	Dense concrete	-	0.080 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, air, brick, dense plaster

U-Value: 1.47 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 4 in (100 mm) brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - kg/m <sup>3</sup>	0.18000 (m <sup>2</sup> ) - kg/m <sup>3</sup>	0.050 m	- W/(m • °K)	- J/(kg • °K)	-
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, air, brick, light-weight plaster

U-Value: 1.36 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 4 in (100 mm) brick, 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - kg/m <sup>3</sup>	0.18000 (m <sup>2</sup> ) - kg/m <sup>3</sup>	0.050 m	- W/(m • °K)	- J/(kg • °K)	-
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, foam insulation, brick, dense plaster

**U-Value: 0.57 W/(m<sup>2</sup> • °K)**

4 in (100 mm) brick, 2 in (50 mm) UF foam insulation, 4 in (100 mm) brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Urea formaldehyde (UF) foam insulation	Urea formaldehyde (UF) foam insulation	-	0.050 m	0.040 W/(m • °K)	10 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, blown fiber insulation, brick, dense plaster

**U-Value: 0.57 W/(m<sup>2</sup> • °K)**

4 in (100 mm) brick, 2 in (50 mm) blown fiber insulation, 4 in (100 mm) brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Blown fiber insulation	Blown fiber insulation	-	0.050 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, polystyrene insulation, brick, plasterboard

**U-Value: 0.79 W/(m<sup>2</sup> • °K)**

4 in (100 mm) brick, 1 in (25 mm) EPS insulation, 4 in (100 mm) brick, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Brick, air, dense concrete block, dense plaster

**U-Value: 1.75 W/(m<sup>2</sup> • °K)**

4 in (100 mm) brick, 2 in (50 mm) airspace, 4 in (100 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> °K/W)	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	

4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, foam insulation, dense concrete block, dense plaster

U-Value: 0.61 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) urea formaldehyde (UF) foam insulation, 4 in (100 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Urea formaldehyde (UF) foam insulation	Urea formaldehyde (UF) foam insulation	-	0.050 m	0.040 W/(m • °K)	10 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, blown fiber insulation, dense concrete, dense plaster

U-Value: 0.61 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) blown fiber insulation, 4 in (100 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Blown fiber insulation	Blown fiber insulation	-	0.050 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, polystyrene insulation, dense concrete, dense plaster

U-Value: 0.55 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) EPS insulation, 4 in (100 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
4 in dense concrete	4 in (100 mm) dense concrete	-	0.100 m	1.70 W/(m • °K)	2200 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, air, light-weight concrete block, dense plaster

U-Value: 0.96 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster [Source:

CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace	0.18000 • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, foam insulation, light-weight concrete, dense plaster

U-Value: 0.47 W/(m<sup>2</sup> • °K)4 in (100 mm) brick, 2 in (50 mm) UF foam insulation, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Urea formaldehyde (UF) foam insulation	Urea formaldehyde (UF) foam insulation	-	0.050 m	0.040 W/(m • °K)	10 kg/m <sup>3</sup>	1400 J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, fiber insulation, light-weight concrete, dense plaster

U-Value: 0.47 W/(m<sup>2</sup> • °K)4 in (100 mm) brick, 2 in (50 mm) blown fiber insulation, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Blown fiber insulation	Blown fiber insulation	-	0.050 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, fiber insulation, light-weight concrete, dense plaster

U-Value: 0.30 W/(m<sup>2</sup> • °K)4 in (100 mm) brick, 4 in (100 mm) blown fiber insulation, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in Blown fiber insulation	4 in (100 mm) Blown fiber insulation	-	0.100 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)

Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

<b>Brick, polystyrene insulation, lightweight concrete, dense plaster</b>		<b>U-Value: 0.44 W/(m<sup>2</sup> • °K)</b>
---	--	---

4 in (100 mm) brick, 2 in (50 mm) EPS insulation, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

<b>Brick, air, plywood sheathing, studding, plasterboard</b>		<b>U-Value: 1.13 W/(m<sup>2</sup> • °K)</b>
--	--	---

4 in (100 mm) brick, 2 in (50 mm) airspace, 3/4 in (19 mm) plywood sheathing, 4 in (100 mm) studding, 1/2 in (12 mm) plasterboard  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> °K/W)	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Plywood Sheathing	Plywood Sheathing	-	0.019 m	0.14 W/(m • °K)	530 kg/m <sup>3</sup>	1800 J/(kg • °K)
Timber studding	Timber studding	-	0.095 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
1/2 in plasterboard	1/2 in (12 mm) plasterboard	-	0.013 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>1/2 in dense plaster, 8 in brick, 1/2 in dense plaster</b>		<b>U-Value: 1.57 W/(m<sup>2</sup> • °K)</b>
---	--	---

1/2 in (12 mm) dense plaster, 8 in (200 mm) brick, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
8 in brick	8 in (200 mm) brick	-	0.215 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

<b>1/2 in dense plaster, dense concrete block, 1/2 in dense plaster</b>		<b>U-Value: 2.36 W/(m<sup>2</sup> • °K)</b>
---	--	---

1/2 in (12 mm) dense plaster, 8 in (200 mm) dense concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
8 in concrete block (dense)	8 in (200 mm) concrete block (dense)	-	0.215 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, polystyrene insulation, light-weight concrete, dense plaster

U-Value: 0.57 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 1 in (25 mm) airspace, 1 in (25 mm) EPS insulation, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1 in external wall	1 in (25 mm) external wall - J/(kg • °K) airspace	0.18000 (m <sup>2</sup> • °K)/W	0.025 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, 4 in autoclaved aerated concrete block, light-weight plaster

U-Value: 1.07 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 4 in (100 mm) autoclaved aerated concrete block (density 700 kg/m<sup>3</sup>), 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Autoclaved Aerated concrete block (density 700)	Autoclaved Aerated concrete block (density 700)	-	0.100 m	0.27 W/(m • °K)	700 kg/m <sup>3</sup>	1050 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, 6 in autoclaved aerated concrete block, light-weight plaster

U-Value: 0.71 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 6 in (150 mm) autoclaved aerated concrete (AAC) block (density 500 kg/m<sup>3</sup>), 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> • °K)/W	0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>	

Autoclaved Aerated concrete block (density 500)	Autoclaved Aerated concrete block (density 500)	-	0.150 m	0.18 W/(m • °K)	500 kg/m <sup>3</sup>	1050 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, insulation, autoclaved aerated concrete block, plaster

U-Value: 0.47 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 1 in (25 mm) airspace, 1 in (25 mm) EPS insulation, 6 in (150 mm) autoclaved aerated concrete block (density 500 kg/m<sup>3</sup>), 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
1 in external wall	1 in (25 mm) external wall - J/(kg • °K) airspace	0.18000 (m <sup>2</sup> • °K)/W		0.025 m	- W/(m • °K)	- kg/m <sup>3</sup>
Expanded polystyrene (EPS)	Expanded polystyrene (EPS)	-	0.025 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Autoclaved Aerated concrete block (density 500)	Autoclaved Aerated concrete block (density 500)	-	0.150 m	0.18 W/(m • °K)	500 kg/m <sup>3</sup>	1050 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Brick, plywood, studding, 4 in insulation, plasterboard

U-Value: 0.29 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 3/4 in (19 mm) plywood sheathing, 4 in (100 mm) studding, 4 in (100 mm) mineral fiber insulation between studs, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> • °K)/W		0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>
Plywood Sheathing	Plywood Sheathing	-	0.019 m	0.14 W/(m • °K)	530 kg/m <sup>3</sup>	1800 J/(kg • °K)
Timber studding	Timber studding	-	0.095 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
4 in mineral fiber insulation	4 in (100 mm) mineral fiber insulation	-	0.095 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plasterboard	1/2 in (12 mm) plasterboard	-	0.013 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Brick, plywood, studding, 6 in insulation, plasterboard

U-Value: 0.21 W/(m<sup>2</sup> • °K)

4 in (100 mm) brick, 2 in (50 mm) airspace, 3/4 in (19 mm) plywood sheathing, 6 in (150 mm) studding, 6 in (150 mm) mineral fiber insulation between studs, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
External wall airspace	External wall airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> • °K)/W		0.050 m	- W/(m • °K)	- kg/m <sup>3</sup>

Plywood Sheathing	Plywood Sheathing	-	0.019 m	0.14 W/(m • °K)	530 kg/m <sup>3</sup>	1800 J/(kg • °K)
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
6 in mineral fiber insulation	6 in (150 mm) mineral fiber insulation	-	0.140 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plasterboard	1/2 in (12 mm) plasterboard	-	0.013 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Plasterboard, concrete block, air, concrete block, plasterboard

**U-Value: 0.62 W/(m<sup>2</sup> • °K)**

1/2 in (12 mm) plasterboard on battens, 4 in (100 mm) lightweight aggregate concrete block, 3 in (75 mm) airspace, 4 in (100 mm) lightweight aggregate concrete block, 1/2 in (12 mm) plasterboard on battens [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
3 in external wall	3 in (75 mm) external wall - J/(kg • °K) airspace	0.18000 (m <sup>2</sup> • °K)/W	0.075 m	- W/(m • °K)	- kg/m <sup>3</sup>	
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Floors

Wilton carpet on concrete			U-Value: 1.2908 W/(m² • °K)			
1/2 in (12 mm) Wilton carpet, 1/2 in (12 mm) cellular rubber underlay, 2 in (50 mm) screed, 6 in (150 mm) cast concrete						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m³	1380 J/(kg • °K)
Cellulose 5 1/2 in R-20 (IN14)	Cellulose 5 1/2 in (13.4 cm)	3.58695 (m² • °K)/W	0.139683 m	0.038942 W/(m • °K)	48.060000 kg/m³	1381.644000 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m³	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m³	840 J/(kg • °K)

Timber flooring, gypsum			U-Value: 1.8135 W/(m² • °K)			
Ceiling, 3/8 in (10 mm) timber flooring, 8 in (200 mm) air, 5/8 in (16 mm) gypsum						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

Timber flooring, batting, gypsum			U-Value: 0.8500 W/(m² • °K)			
Ceiling, 3/8 in (10 mm) timber flooring, 8 in (200 mm) air, 1 in (25 mm) batt, 5/8 in (16 mm) gypsum						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
R-30, 9 1/2 in batt insulation	R-30, 9 1/2 in (240 mm) batt insulation	-	0.2438 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m² • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

Timber flooring, batt, metal deck tray			U-Value: 0.9290 W/(m² • °K)			
Ceiling, 3/8 in (10 mm) timber flooring, 1 in (25 mm) air, 1 in (25 mm) batting, 1/16 in (2 mm) metal deck tray						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
R-30, 9 1/2 in batt	R-30, 9 1/2 in (240 mm)	-	0.2438 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)

insulation	batt insulation					°K)
Metal surface	Metal surface	-	0.002 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Timber flooring, joists, plasterboard ceiling

U-Value: 1.88 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) timber flooring or chipboard on 4 in (100 mm) joists, 1/2 in (12 mm) plasterboard ceiling

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Loft floor - domestic A

U-Value: 0.3596 W/(m<sup>2</sup> • °K)

Loft floor - domestic

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Loft floor - domestic B

U-Value: 0.2481 W/(m<sup>2</sup> • °K)

Loft floor - domestic

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## 2 in heavyweight concrete floor deck

U-Value: 4.3599 W/(m<sup>2</sup> • °K)

2 in (50 mm) heavyweight concrete floor deck

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in heavyweight concrete	2 in (50 mm) heavyweight concrete	-	0.0508 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete floor deck

U-Value: 3.8651 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete floor deck

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 2 in lightweight concrete floor deck

U-Value: 3.7475 W/(m<sup>2</sup> • °K)

2 in (50 mm) lightweight concrete floor deck

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in lightweight concrete	2 in (50 mm) lightweight	-	0.051 m	0.53 W/(m • °K)	1280	840 J/(kg • °K)

concrete		kg/m <sup>3</sup>	°K)			
<b>8 in heavyweight concrete floor deck</b>			<b>U-Value: 3.1500 W/(m<sup>2</sup> • °K)</b>			
8 in (200 mm) heavyweight concrete floor deck						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
<b>2 in wood deck</b>			<b>U-Value: 1.6133 W/(m<sup>2</sup> • °K)</b>			
2 in (50 mm) wood deck						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
<b>3 in wood deck</b>			<b>U-Value: 1.2052 W/(m<sup>2</sup> • °K)</b>			
3 in (75 mm) wood deck						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3 in wood	3 in (75 mm) wood	-	0.076 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

8 in (200 mm) lightweight concrete floor deck	<b>U-Value: 1.3610 W/(m<sup>2</sup> • °K)</b>					
8 in (200 mm) lightweight concrete floor deck						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
<b>Passive floor, no insulation, tile or vinyl</b>			<b>U-Value: 2.9582 W/(m<sup>2</sup> • °K)</b>			
Passive floor, no insulation, tile or vinyl [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Slate or tile	Slate or tile	-	0.0127 m	1.59 W/(m • °K)	1920 kg/m <sup>3</sup>	1260 J/(kg • °K)
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)	-	-	-	-

Passive floor, no insulation, carpet or hardwood	<b>U-Value: 2.1860 W/(m<sup>2</sup> • °K)</b>					
Passive floor, no insulation, carpet or hardwood [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
No insulation (m <sup>2</sup> • °K)	No insulation	0.00001 (m <sup>2</sup> • °K)	-	-	-	-

## Passive floor, R-2 board insulation, any cover

U-Value: 1.3967 W/(m<sup>2</sup> • °K)

Passive floor, R-2 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-2 insulation (m <sup>2</sup> • °K)	R-2 insulation	0.35222	-	-	-	-

## Passive floor, R-3 board insulation, any cover

U-Value: 1.1072 W/(m<sup>2</sup> • °K)

Passive floor, R-3 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-3 insulation (m <sup>2</sup> • °K)	R-3 insulation	0.52833	-	-	-	-

## Passive floor, R-4 board insulation, any cover

U-Value: 0.9198 W/(m<sup>2</sup> • °K)

Passive floor, R-4 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-4 insulation (m <sup>2</sup> • °K)	R-4 insulation	0.70444	-	-	-	-

## Passive floor, R-5 board insulation, any cover

U-Value: 0.7892 W/(m<sup>2</sup> • °K)

Passive floor, R-5 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-5 insulation (m <sup>2</sup> • °K)	R-5 insulation	0.88055	-	-	-	-

## Passive floor, R-6 board insulation, any cover

U-Value: 0.6870 W/(m<sup>2</sup> • °K)

Passive floor, R-6 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-6 insulation (m <sup>2</sup> • °K)	R-6 insulation	1.05666	-	-	-	-

## Passive floor, R-7 board insulation, any cover

U-Value: 0.6132 W/(m<sup>2</sup> • °K)

Passive floor, R-7 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-7 insulation (m <sup>2</sup> • °K)	R-7 insulation	1.23277	-	-	-	-

## Passive floor, R-8 board insulation, any cover

U-Value: 0.5507 W/(m<sup>2</sup> • °K)

Passive floor, R-8 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-8 insulation (m <sup>2</sup> • °K)	R-8 insulation	1.40888	-	-	-	-

## Passive floor, R-9 board insulation, any cover

U-Value: 0.4996 W/(m<sup>2</sup> • °K)

Passive floor, R-9 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-9 insulation (m <sup>2</sup> • °K)	R-9 insulation	1.58499	-	-	-	-

## Passive floor, R-10 board insulation, any cover

U-Value: 0.4599 W/(m<sup>2</sup> • °K)

Passive floor, R-10 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-10 insulation (m <sup>2</sup> • °K)	R-10 insulation	1.76110	-	-	-	-

## Passive floor, R-11 board insulation, any cover

U-Value: 0.4485 W/(m<sup>2</sup> • °K)

Passive floor, R-11 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-11 insulation (m <sup>2</sup> • °K)	R-11 insulation	1.93721	-	-	-	-

<b>Passive floor, R-13 board insulation, any cover</b>		<b>U-Value: 0.3861 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-13 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-13 insulation (m <sup>2</sup> • °K)	R-13 insulation	2.28943	-	-	-	-

<b>Passive floor, R-15 board insulation, any cover</b>		<b>U-Value: 0.3463 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-15 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-15 insulation (m <sup>2</sup> • °K)	R-15 insulation	2.54165	-	-	-	-

<b>Passive floor, R-19 board insulation, any cover</b>		<b>U-Value: 0.2839 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-19 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-19 insulation (m <sup>2</sup> • °K)	R-19 insulation	3.34609	-	-	-	-

<b>Passive floor, R-21 board insulation, any cover</b>		<b>U-Value: 0.2668 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-21 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-21 insulation (m <sup>2</sup> • °K)	R-21 insulation	3.69831	-	-	-	-

<b>Passive floor, R-30 board insulation, any cover</b>		<b>U-Value: 0.1987 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-30 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-30 insulation (m <sup>2</sup> • °K)	R-30 insulation	5.28331	-	-	-	-

<b>Passive floor, R-38 board insulation, any cover</b>		<b>U-Value: 0.1703 W/(m<sup>2</sup> • °K)</b>
--	--	---

Passive floor, R-38 board insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-38 insulation (m <sup>2</sup> • °K)	R-38 insulation	6.69219	-	-	-	-

<b>Radiant floor, R-38 blanket insulation, any cover</b>		<b>U-Value: 0.1760 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-38 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-38 insulation (m <sup>2</sup> • °K)	R-38 insulation	6.69219	-	-	-	-

<b>Radiant floor, R-11 blanket insulation, any cover</b>		<b>U-Value: 0.4996 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-11 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-11 insulation (m <sup>2</sup> • °K)	R-11 insulation	1.93721	-	-	-	-

<b>Radiant floor, R-13 blanket insulation, any cover</b>		<b>U-Value: 0.4315 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-13 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-13 insulation (m <sup>2</sup> • °K)	R-13 insulation	2.28943	-	-	-	-

<b>Radiant floor, R-15 blanket insulation, any cover</b>		<b>U-Value: 0.3804 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-15 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-15 insulation (m <sup>2</sup> • °K)	R-15 insulation	2.64165	-	-	-	-

<b>Radiant floor, R-19 blanket insulation, any cover</b>		<b>U-Value: 0.3122 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-19 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-19 insulation (m <sup>2</sup> • °K)/W	R-19 insulation	3.34609	-	-	-	-

<b>Radiant floor, R-21 blanket insulation, any cover</b>		<b>U-Value: 0.2839 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-21 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-21 insulation (m <sup>2</sup> • °K)/W	R-21 insulation	3.69831	-	-	-	-

<b>Radiant floor, R-30 blanket insulation, any cover</b>		<b>U-Value: 0.2157 W/(m<sup>2</sup> • °K)</b>
--	--	---

Radiant floor, R-30 blanket insulation, any cover [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
R-30 insulation (m <sup>2</sup> • °K)/W	R-30 insulation	5.28331	-	-	-	-

<b>Screeed, concrete, dense plaster</b>		<b>U-Value: 2.38 W/(m<sup>2</sup> • °K)</b>
---	--	---

2 in (50 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

<b>Vinyl floor covering, screed, concrete</b>		<b>U-Value: 0 W/(m<sup>2</sup> • °K)</b>
---	--	--

Vinyl floor covering, 3 in (75 mm) screed, 6 in (150 mm) cast concrete [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)

6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)
---------------------------------	--	---	----------	-----------------	-----------------------	-----------------

Carpet underlay, screed, concrete			U-Value: 0 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
carpet/underlay - polyurethane board cellular	carpet/underlay - polyurethane board cellular	-	0.010 m	0.023 W/(m • °K)	24 kg/m <sup>3</sup>	1590 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

Carpet, underlay, timber on joists, ventilated			U-Value: 0 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
carpet/underlay - polyurethane board cellular	carpet/underlay - polyurethane board cellular	-	0.010 m	0.023 W/(m • °K)	24 kg/m <sup>3</sup>	1590 J/(kg • °K)
3/4 in chipboard	3/4 in (19 mm) chipboard	-	0.019 m	0.067 W/(m • °K)	430 kg/m <sup>3</sup>	1260 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-

Carpet, underlay, screed, concrete, insulation, building board			U-Value: 0.28 W/(m <sup>2</sup> • °K)			
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
carpet/underlay - polyurethane board cellular	carpet/underlay - polyurethane board cellular	-	0.010 m	0.023 W/(m • °K)	24 kg/m <sup>3</sup>	1590 J/(kg • °K)
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Asbestos cement building board	Asbestos cement building board	-	0.012 m	0.6 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)

Vinyl, screed, concrete - A			U-Value: 2.01 W/(m <sup>2</sup> • °K)			
Vinyl floor covering, 2 in (50 mm) screed, 6 in (150 mm) cast concrete [Source: CIBSE]						

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, screed, concrete - B

U-Value: 1.77 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 2 in (50 mm) screed, 6 in (150 mm) cast concrete [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, screed, insulation, concrete

U-Value: 0 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 3 in (75 mm) screed, 2 in (50 mm) extruded polystyrene insulation, 6 in (150 mm) cast concrete [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Polystyrene 2 in (IN35)	Polystyrene 2 in (3.1 cm)	1.46780 (m <sup>2</sup> • °K)/W	0.050808 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, timber, insulation, concrete

U-Value: 0 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 3/4 in (19 mm) timber or chipboard, 2 in (50 mm) extruded polystyrene insulation, 6 in (150 mm) cast concrete [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
3/4 in chipboard	3/4 in (19 mm) chipboard	-	0.019 m	0.067 W/(m • °K)	430 kg/m <sup>3</sup>	1260 J/(kg • °K)
Polystyrene 2 in (IN35)	Polystyrene 2 in (3.1 cm)	1.46780 (m <sup>2</sup> • °K)/W	0.050808 m	0.034615 W/(m • °K)	28.836000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, timber on joists, ventilated

U-Value: 0 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 3/4 in (19 mm) timber or chipboard on 4 in (100 mm) joists, ventilated underfloor cavity [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
3/4 in chipboard	3/4 in (19 mm) chipboard	-	0.019 m	0.067 W/(m • °K)	430 kg/m <sup>3</sup>	1260 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-

## Vinyl, timber on joists, building board - A

U-Value: 1.52 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 3/4 in (19 mm) timber or chipboard on 4 in (100 mm) joists, 1/2 in (12 mm) cementitious building board on underside  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
carpet/underlay - polyurethane board cellular	carpet/underlay - polyurethane board cellular	-	0.010 m	0.023 W/(m • °K)	24 kg/m <sup>3</sup>	1590 J/(kg • °K)
3/4 in chipboard	3/4 in (19 mm) chipboard	-	0.019 m	0.067 W/(m • °K)	430 kg/m <sup>3</sup>	1260 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, timber on joists, building board - B

U-Value: 1.38 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 3/4 in (19 mm) timber or chipboard on 4 in (100 mm) joists, 1/2 in (12 mm) cementitious building board on underside  
[Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
carpet/underlay - polyurethane board cellular	carpet/underlay - polyurethane board cellular	-	0.010 m	0.023 W/(m • °K)	24 kg/m <sup>3</sup>	1590 J/(kg • °K)
3/4 in chipboard	3/4 in (19 mm) chipboard	-	0.019 m	0.067 W/(m • °K)	430 kg/m <sup>3</sup>	1260 J/(kg • °K)
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-	0.1524 m	0.49 W/(m • °K)	512 kg/m <sup>3</sup>	880 J/(kg • °K)

## Vinyl, screed, concrete, 2 in insulation, building board

U-Value: 0.50 W/(m<sup>2</sup> • °K)

Vinyl floor covering, 2 in (50 mm) screed, 6 in (150 mm) cast concrete, 2 in (50 mm) mineral fiber insulation between battens, 1/2 in (12 mm) cementitious building board on underside [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Asbestos cement building board	Asbestos cement building board	-	0.012 m	0.6 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)

## Vinyl, screed, concrete, 4 in insulation, building board

**U-Value: 0.29 W/(m<sup>2</sup> • °K)**

Vinyl floor covering, 2 in (50 mm) screed, 6 in (150 mm) cast concrete, 4 in (100 mm) mineral fiber insulation between battens, 1/2 in (12 mm) cementitious building board on underside [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
AbsVinyl tile (AV01)	AbsVinyl tile	0.00881 (m <sup>2</sup> • °K)/W	-	-	-	-
Screed	Screed	-	0.05 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.150 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Asbestos cement building board	Asbestos cement building board	-	0.012 m	0.6 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Interior Walls

### Light plaster, brick, light plaster

1/2 in (12 mm) light-weight plaster, 4 in (100 mm) brick, 1/2 in (12 mm) light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Face brick 4 in (BK05)	4 in (10.1cm) face brick 1.311205 W/(m	0.07747 (m <sup>2</sup> )		0.101585 m	2082.600000 kg/m <sup>3</sup>	921.096000 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

### Light plaster, double brick, light plaster

1/2 in (12 mm) light-weight plaster, 4 in (100 mm) brick, 1 in (25 mm) air, 4 in (100 mm) brick, 1/2 in (12 mm) light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Face brick 4 in (BK05)	4 in (10.1cm) face brick 921.096000	0.07747 (m <sup>2</sup> )		0.101585 m	1.311205 W/(m 2082.600000	
Air space	Air space proxy for air wall - or no construction	0.10919 (m <sup>2</sup> )		-	-	-
Face brick 4 in (BK05)	4 in (10.1cm) face brick 921.096000	0.07747 (m <sup>2</sup> )		0.101585 m	1.311205 W/(m 2082.600000	
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

### Light plaster, heavy concrete block, light plaster

1/2 in (12 mm) light-weight plaster, 4 in (100 mm) heavy-weight concrete block, 1/2 in (12 mm) light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

### Light plaster, medium concrete block, light plaster

1/2 in (12 mm) light-weight plaster, 4 in (100 mm) medium-weight concrete block, 1/2 in (12 mm) light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in heavyweight	4 in (100 mm) heavyweight	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

concrete	concrete					°K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Light plaster, light concrete block, light plaster

U-Value: 1.0539 W/(m<sup>2</sup> • °K)

1/2 in (12 mm) light-weight plaster, 4 in (100 mm) light-weight concrete block, 1/2 in (12 mm) light-weight plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Standard double gypsum with 4 in air gap

U-Value: 1.3289 W/(m<sup>2</sup> • °K)

1 in (25 mm) gypsum, 4 in (100 mm) air, 1 in (25 mm) gypsum

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Gypsum lightweight (m <sup>2</sup> agg 1 in (GP05)	Gypsum lightweight agg 1 in (25 mm)	0.11030 • °K)/W	0.025389 m	0.230188 W/(m • °K)	720.900000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 • °K)/W	-	-	-	-
Gypsum lightweight (m <sup>2</sup> agg 1 in (GP05)	Gypsum lightweight agg 1 in (25 mm)	0.11030 • °K)/W	0.025389 m	0.230188 W/(m • °K)	720.900000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Standard double fiberboard with 4 in air gap

U-Value: 1.1905 W/(m<sup>2</sup> • °K)

1/2 in (12 mm) fiberboard, 4 in (100 mm) air, 1/2 in (12 mm) fiberboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 • °K)/W	-	-	-	-
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)

## 4 in single-leaf brick (plastered both sides)

U-Value: 1.9709 W/(m<sup>2</sup> • °K)

4 in (100 mm) single-leaf brick (plastered both sides)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## 8 in single-leaf brick (plastered both sides)

U-Value: 1.4433 W/(m<sup>2</sup> • °K)

8 in (200 mm) single-leaf brick (plastered both sides)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## 1 1/4 ft single-leaf brick (plastered both sides)

U-Value: 1.1080 W/(m<sup>2</sup> • °K)

1 1/4 ft (400 mm) single-leaf brick (plastered both sides)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Solid breeze blocks (plastered both sides)

U-Value: 1.1789 W/(m<sup>2</sup> • °K)

Solid breeze blocks (plastered both sides)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## 4 in single-leaf brick

U-Value: 2.2448 W/(m<sup>2</sup> • °K)

4 in (100 mm) single-leaf brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-	0.115 m	0.62 W/(m • °K)	1700 kg/m <sup>3</sup>	800 J/(kg • °K)

<b>5 in single-leaf brickwork (plastered on one side)</b>		<b>U-Value: 2.0302 W/(m<sup>2</sup> • °K)</b>
5 in (125 mm) single-leaf brickwork (plastered on one side)		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
Brick - brickwork inner leaf	Brick - brickwork inner leaf	-
Plaster (lightweight)	Plaster (lightweight)	-
<b>Aerated concrete blocks</b>		
Aerated concrete blocks		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
Autoclaved Aerated concrete block (density 700)	Autoclaved Aerated concrete block (density 700)	-
<b>Hollow concrete blocks</b>		
Hollow concrete blocks		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-
<b>Insulated concrete form</b>		
Insulated concrete form		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
6 in lightweight concrete block	6 in (150 mm) lightweight concrete block	-
<b>Glass blocks</b>		
Glass blocks		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
Concrete cast glass reinforced	Concrete cast glass reinforced	-
<b>4 in reinforced concrete</b>		
4 in (100 mm) reinforced concrete		
<b>Material</b>	<b>Description</b>	<b>R-Value</b>
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-
<b>9 in medium-weight concrete block</b>		
9 in (225 mm) medium-weight concrete block		

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block mediumweight 9 in	Concrete block mediumweight 9 in	-	0.220 m	0.77 W/(m • °K)	1900 kg/m³	840 J/(kg • °K)

## 1 1/2 ft dense concrete

1 1/2 ft dense concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## Polystyrene faced with hardboard on plasterboard

U-Value: 0.7987 W/(m² • °K)

1 in (25 mm) polystyrene faced with 1/8 in (3 mm) hardboard on 3/8 in (10 mm) plasterboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 1 in	Polystyrene 1 in (25 mm) 0.034615 W/(m (IN33))	0.73347 (m² • °K)/W	0.025389 m • °K)	28.836000 kg/m³	1214.172000 J/(kg • °K)	
Hardboard	Hardboard	-	0.003 m	0.08 W/(m • °K)	600 kg/m³	2000 J/(kg • °K)
3/8 in plasterboard	3/8 in (10 mm) plasterboard	-	0.009 m	0.16 W/(m • °K)	950 kg/m³	840 J/(kg • °K)

## Expanded-wood chipboard

U-Value: 2.8846 W/(m² • °K)

1/2 in (12 mm) expanded-wood chipboard

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Chipboard	Chipboard	-	0.013 m	0.067 W/(m • °K)	430 kg/m³	1260 J/(kg • °K)

## Block cavity wall with air gap (plastered)

U-Value: 1.3381 W/(m² • °K)

8 in (200 mm) block-cavity wall with 2 in (50 mm) air gap (plastered)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)
Air space	Air space proxy for air wall (m² or no construction)	0.10919 (m² • °K)/W	-	-	-	-
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m³	790 J/(kg • °K)

## Cast concrete cavity wall with air gap (plastered)

U-Value: 1.1684 W/(m² • °K)

8 in (200 mm) cast concrete cavity wall with 2 in (50 mm) air gap (plastered)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight	4 in (100 mm) heavyweight	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

concrete	concrete					°K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> °K)/W	-	-	-	-
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## Brick cavity wall with air gap

4 in (100 mm) brick cavity wall with 2 in (50 mm) air gap

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in lightweight concrete	2 in (50 mm) lightweight concrete	-	0.051 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
2 in lightweight concrete	2 in (50 mm) lightweight concrete	-	0.051 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## Brick cavity wall (plaster both sides)

4 in (100 mm) brick cavity wall with 1/2 in (12 mm) (plaster both sides)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
2 in lightweight concrete	2 in (50 mm) lightweight concrete	-	0.051 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall (m <sup>2</sup> or no construction)	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
2 in lightweight concrete	2 in (50 mm) lightweight concrete	-	0.051 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Standard double plasterboard with insulation

U-Value: 1.2331 W/(m<sup>2</sup> • °K)

Two 1/2 in (12 mm) plasterboard leaves with 1 in (25 mm) glass wool in cavity

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
Glass fiber wool - fiber quilt	Glass fiber wool - fiber quilt	-	0.025 m	0.040 W/(m • °K)	12 kg/m <sup>3</sup>	840 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## 3/8 in plasterboard on studs

U-Value: 1.8100 W/(m<sup>2</sup> • °K)

3/8 in (10 mm) plasterboard on 2 in (50 mm) by 4 in (100 mm) studs at 16 in (400 mm) centers

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3/8 in plasterboard	3/8 in (10 mm) plasterboard	-	0.009 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

**1/2 in plasterboard on studs****U-Value: 1.6598 W/(m<sup>2</sup> • °K)**

1/2 in (12 mm) plasterboard on 2 in (50 mm) by 4 in (100 mm) studs at 16 in (400 mm) centers

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

**1/2 in plasterboard on studs with mineral fiber slab****U-Value: 0.7594 W/(m<sup>2</sup> • °K)**

1/2 in (12 mm) plasterboard on studs at 16 in (400 mm) centers with 1 in (25 mm) mineral fiber slab

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.025 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)

**1/4 in plywood on studs****U-Value: 1.9231 W/(m<sup>2</sup> • °K)**

1/4 in (6 mm) plywood on 2 in (50 mm) by 2 in (50 mm) studs at 2 ft (600 mm) centers

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1/4 in plywood	1/4 in (6 mm) plywood	-	0.006 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.025 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)

**3/8 in plywood on studs****U-Value: 1.7857 W/(m<sup>2</sup> • °K)**

3/8 in (10 mm) plywood on 2 in (50 mm) by 2 in (50 mm) and 1 in (25 mm) by 2 in studs at 18 in centers 2 in (50 mm) apart

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
3/8 in plywood	3/8 in (10 mm) plywood	-	0.009 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
1/2 in wood	1/2 in (12 mm) wood	-	0.0127 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.025 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)

**Asbestos wallboard on timber frame****U-Value: 2.1127 W/(m<sup>2</sup> • °K)**

Asbestos wallboard on 1 1/4 in (32 mm) timber frame 8 in (200 mm) apart

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asbestos fiber	Asbestos fiber	-	0.010 m	0.06 W/(m • °K)	640 kg/m <sup>3</sup>	840 J/(kg • °K)

Timber flooring	Timber flooring	-	0.030 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
-----------------	-----------------	---	---------	-----------------	-----------------------	------------------

Domestic solid party wall			U-Value: 1.4572 W/(m <sup>2</sup> • °K)			
Domestic solid party wall						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

Domestic lightweight party wall			U-Value: 1.1905 W/(m <sup>2</sup> • °K)			
Domestic lightweight party wall						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

Lightweight plasterboard partition			U-Value: 1.5936 W/(m <sup>2</sup> • °K)			
Lightweight plasterboard partition						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

Solid partition			U-Value: 1.1658 W/(m <sup>2</sup> • °K)			
Solid partition						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

4 in clay tile with plaster			U-Value: 1.4778 W/(m <sup>2</sup> • °K)			
4 in (100 mm) clay tile with 3/4 in (19 mm) plaster						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Hol clay tile 4 in (CT02)	1 cell, 4 in (10.1cm)	0.19671 (m <sup>2</sup> °K)	0.101585 m	0.519047 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Light-weight concrete block with plaster			U-Value: 1.3053 W/(m <sup>2</sup> • °K)			
4 in (100 mm) lightweight concrete block with 3/4 in (19 mm) plaster						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Heavy-weight concrete block with plaster

U-Value: 1.7352 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete block with 3/4 in (19 mm) plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Cmt plaster 3/4 in	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> (CM03))	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in common brick with plaster

U-Value: 1.5662 W/(m<sup>2</sup> • °K)

4 in (100 mm) common brick with 3/4 in (19 mm) plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> )	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Heavyweight concrete with plaster

U-Value: 1.7938 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 3/4 in (19 mm) plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Cmt plaster 3/4 in	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> )	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 5 in clay tile with plaster

U-Value: 1.3866 W/(m<sup>2</sup> • °K)

5 in (125 mm) clay tile with 3/4 in (19 mm) plaster

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Clay tile 4 in (HF-C1)	4 in (10.1 cm) clay tile	0.17786.0 1 (m <sup>2</sup> )	0.101585 m	0.571143 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> )	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Light-weight concrete block plastered

U-Value: 0.9676 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete block plastered both sides

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Cmt plaster 3/4 in	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> (CM03))	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Cmt plaster 3/4 in	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> (CM03))	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## heavyweight concrete block plastered

U-Value: 1.5294 W/(m<sup>2</sup> • °K)

8 in (200 mm) heavyweight concrete block plastered both sides

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in common brick with plaster

8 in (200 mm) common brick plastered Both Sides

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 8 in heavy concrete with plaster

8 in (200 mm) heavy concrete plastered both sides

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 12 in heavy concrete with plaster

12 in (300 mm) heavy concrete plastered both sides

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Cmt plaster 3/4 in (CM03)	Plaster with sand aggregate, 3/4 in (19 mm)	0.02635 (m <sup>2</sup> °K)/W	0.019 m	0.721197 W/(m • °K)	1858.320000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## 4 in clay tile

4 in (100 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Clay tile 4 in (HF-C1)	4 in (10.1 cm) clay tile	0.17786 (m <sup>2</sup> °K)/W	0.101585 m	0.571143 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Light-weight concrete block

U-Value: 1.8962 W/(m<sup>2</sup> • °K)

4 in (100 mm) light-weight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

**4 in heavyweight concrete block**

4 in (100 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

**4 in common brick**

4 in (100 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

**4 in heavyweight concrete**

4 in (100 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in heavyweight concrete	4 in (100 mm) heavyweight concrete	-	0.1016 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

**8 in clay tile**

8 in (200 mm) clay tile

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Clay tile 8 in (HF-C6)	8 in (20.3 cm) clay tile	0.35578 (m <sup>2</sup> °K/W)	0.203200 m	0.571143 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

**8 in lightweight concrete block**

8 in (200 mm) lightweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

**8 in heavyweight concrete block**

8 in (200 mm) heavyweight concrete block

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

**8 in common brick**

U-Value: 1.8536 W/(m<sup>2</sup> • °K)

## 8 in (200 mm) common brick

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

**8 in heavyweight concrete**

8 in (200 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

**12 in heavyweight concrete**

12 in (300 mm) heavyweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
12 in heavyweight concrete	12 in (300 mm) heavyweight concrete	-	0.3048 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

**Frame partition with 3/4 in gypsum board**

Frame partition with 3/4 in (19 mm) gypsum board

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.46524 (m <sup>2</sup> °K/W)	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)

**1 in wood**

1 in (25 mm) wood

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

**2 in wood**

2 in (50 mm) wood

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

**3 in wood**

3 in (75 mm) wood

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood 3 in (HF-B1)	Wood 3 in (7.6 cm)	0.62893 (m <sup>2</sup> °K/W)	0.076196 m	0.121151 W/(m °K)	592.740000	837.360000

		• °K)/W	• °K)	kg/m <sup>3</sup>	J/(kg • °K)	
4 in wood		U-Value: 0.9094 W/(m <sup>2</sup> • °K)				
4 in (100 mm) wood						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

  

Frame partition with 1 in wood		U-Value: 1.1630 W/(m <sup>2</sup> • °K)				
Frame partition with 1 in (25 mm) wood						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

2 in furniture		U-Value: 0.7815 W/(m <sup>2</sup> • °K)				
2 in (50 mm) furniture						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

3 in furniture		U-Value: 0.5884 W/(m <sup>2</sup> • °K)				
3 in (75 mm) furniture						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood 3 in (HF-B1)	Wood 3 in (7.6 cm)	0.62893 (m <sup>2</sup> • °K)/W	0.076196 m	0.121151 W/(m • °K)	592.740000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

2 in heavyweight concrete		U-Value: 3.4559 W/(m <sup>2</sup> • °K)				
2 in (50 mm) heavyweight concrete						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in heavyweight concrete	2 in (50 mm) heavyweight concrete	-	0.051 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

Frame construction, wood sheathing, wood studs		U-Value: 1.4365 W/(m <sup>2</sup> • °K)				
Frame construction, no cavity insulation, no board insulation, wood sheathing, wood studs [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-

6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
----------------------	-------------------------------	---	---------	-----------------	-----------------------	------------------

## Frame construction, wood sheathing, metal studs

U-Value: 1.7885 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, no board insulation, wood sheathing, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-2 board insulation, wood studs

U-Value: 1.1015 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-2 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-2 board insulation, metal studs

U-Value: 1.3059 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-2 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-3 board insulation, wood studs

U-Value: 0.9198 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-3 board insulation, wood studs [Source: CIBSE]

Material	Description	R-	Thickness	Conductivity	Density	Specific
----------	-------------	----	-----------	--------------	---------	----------

Value						Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-3 board insulation, metal studs

U-Value: 1.0618 W/(m² • °K)

Frame construction, no cavity insulation, R-3 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m² mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m² • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-4 board insulation, wood studs

U-Value: 0.7892 W/(m² • °K)

Frame construction, no cavity insulation, R-4 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m² mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m² • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m² • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-4 board insulation, metal studs

U-Value: 0.8914 W/(m² • °K)

Frame construction, no cavity insulation, R-4 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m² mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m² • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m² • °K)/W	-	-	-	-

6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
---------------------	------------------------------	---	---------	-----------------	-----------------------	------------------

## Frame construction, R-5 board insulation, wood studs

U-Value: 0.6927 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-5 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-5 board insulation, wood studs

U-Value: 0.7722 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-5 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-6 board insulation, wood studs

U-Value: 0.6189 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-6 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-6 board insulation, metal studs

U-Value: 0.6813 W/(m<sup>2</sup> • °K)

Frame construction, no cavity insulation, R-6 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 insulation, wood studs

U-Value: 0.5507 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, no board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 insulation, metal studs

U-Value: 0.6927 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, no board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 plus R-2 insulation, wood studs

U-Value: 0.4883 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-2 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-

°K)/W					
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>

## Frame construction, R-11 plus R-2 insulation, metal studs

U-Value: 0.6018 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-2 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 and R-3 insulation, wood studs

U-Value: 0.4485 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-3 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 plus R-3 insulation, metal studs

U-Value: 0.5450 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-3 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 plus R-4 insulation, wood studs

U-Value: 0.4144 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-4 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-11 plus R-4 insulation, metal studs

U-Value: 0.4996 W/(m² • °K)

Frame construction, R-11 cavity insulation, R-4 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in - w/ 48 in oc SIP wall	Polystyrene 3 1/2 in (90 mm) including SIP wall	2.20138 (m² • °K)/W	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m² • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-11 plus R-5 insulation, wood studs

U-Value: 0.3861 W/(m² • °K)

Frame construction, R-11 cavity insulation, R-5 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in - w/ 48 in oc SIP wall	Polystyrene 3 1/2 in (90 mm) including SIP wall	2.20138 (m² • °K)/W	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m² • °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 (m² • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-11 plus R-5 insulation, metal studs

U-Value: 0.4599 W/(m² • °K)

Frame construction, R-11 cavity insulation, R-5 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in - w/ 48 in oc SIP wall	Polystyrene 3 1/2 in (90 mm) including SIP wall	2.20138 (m² • °K)/W	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m² • °K)/W	-	-	-	-

R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 plus R-6 insulation, wood studs

U-Value: 0.3633 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-6 board insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-11 plus R-6 insulation, metal studs

U-Value: 0.4258 W/(m<sup>2</sup> • °K)

Frame construction, R-11 cavity insulation, R-6 board insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 insulation, wood sheathing, wood studs

U-Value: 0.4883 W/(m<sup>2</sup> • °K)

Frame construction, R-15 cavity insulation, no board insulation, wood sheathing, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.0001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 insulation, wood sheathing, metal studs

U-Value: 0.6189 W/(m<sup>2</sup> • °K)

Frame construction, R-15 cavity insulation, no board insulation, wood sheathing, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 °K)/W	-	-	-	-
No insulation	No insulation	0.0001 °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-2 insulation, wood studs

U-Value: 0.4372 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-2 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-2 insulation, metal studs

U-Value: 0.5507 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-2 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-3 insulation, wood studs

U-Value: 0.4031 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-3 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-

R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 plus R-3 insulation, metal studs

Frame construction, R-15 cavity insulation, R-3 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 plus R-4 insulation, wood studs

Frame construction, R-15 cavity insulation, R-4 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 plus R-4 insulation, metal studs

Frame construction, R-15 cavity insulation, R-4 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-15 plus R-5 insulation, wood studs

U-Value: 0.3520 W/(m<sup>2</sup> • °K)

Frame construction, R-15 cavity insulation, R-5 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-5 insulation, metal studs

U-Value: 0.4258 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-5 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-6 insulation, wood studs

U-Value: 0.3293 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-6 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-
R-6 insulation	R-6 insulation	1.05666 (m² • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-15 plus R-6 insulation, metal studs

U-Value: 0.3974 W/(m² • °K)

Frame construction, R-15 cavity insulation, R-6 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W	-	-	-	-

R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 insulation, wood sheathing, wood studs

U-Value: 0.36907 W/(m<sup>2</sup> • °K)

Frame construction, R-21 cavity insulation, no board insulation, wood sheathing, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 insulation, wood sheathing, metal studs

U-Value: 0.5621 W/(m<sup>2</sup> • °K)

Frame construction, R-21 cavity insulation, no board insulation, wood sheathing, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W	2.20138 (m <sup>2</sup> mm) including SIP wall	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
No insulation	No insulation	0.00001 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-2 insulation, wood studs

U-Value: 0.3406 W/(m<sup>2</sup> • °K)

Frame construction, R-21 cavity insulation, R-2 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-2 insulation, metal studs

U-Value: 0.5053 W/(m<sup>2</sup> • °K)

Frame construction, R-21 cavity insulation, R-2 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-21 plus R-3 insulation, wood studs

U-Value: 0.3350 W/(m² • °K)

Frame construction, R-21 cavity insulation, R-3 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m² • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-21 plus R-3 insulation, metal studs

U-Value: 0.4655 W/(m² • °K)

Frame construction, R-21 cavity insulation, R-3 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m² • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-21 plus R-4 insulation, wood studs

U-Value: 0.3007 W/(m² • °K)

Frame construction, R-21 cavity insulation, R-4 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m² • °K)/W	-	-	-	-

R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-4 insulation, metal studs

Frame construction, R-21 cavity insulation, R-4 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-5 insulation, wood studs

Frame construction, R-21 cavity insulation, R-5 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-5 insulation, metal studs

Frame construction, R-21 cavity insulation, R-5 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m <sup>2</sup> mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

## Frame construction, R-21 plus R-6 insulation, wood studs

U-Value: 0.2725 W/(m<sup>2</sup> • °K)

Frame construction, R-21 cavity insulation, R-6 insulation, wood studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in w/ 48 in oc SIP wall frame	Polystyrene 3 1/2 in (90 mm) including SIP wall frame factor	2.20138 • °K)/W	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.99055 °K)/W	-	-	-	-
6 in timber studding	6 in (150 mm) timber studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Frame construction, R-21 plus R-6 insulation, metal studs

U-Value: 0.3747 W/(m² • °K)

Frame construction, R-21 cavity insulation, R-6 insulation, metal studs [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Polystyrene 3 1/2 in including SIP wall	Polystyrene 3 1/2 in (90 - w/ 48 in oc SIP wall • °K)/W frame	2.20138 (m² mm) frame factor	-	-	-	-
R-21 insulation	R-21 insulation	3.69831 (m² • °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 (m² • °K)/W	-	-	-	-
6 in metal studding	6 in (150 mm) metal studding	-	0.140 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

## Siding, R-2 insulation, interior finish

U-Value: 1.1412 W/(m² • °K)

Block, stucco or siding, R-2 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m³	840 J/(kg • °K)
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m²	0.012710 m	1249.560000 kg/m³	1088.568000 J/(kg • °K)	

## Siding, R-2 insulation, filled core, interior finish

U-Value: 0.8687 W/(m² • °K)

Block, stucco or siding, R-2 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m³	840 J/(kg • °K)
R-2 insulation	R-2 insulation	0.35222 (m² • °K)/W	-	-	-	-

Finish (HF-A6)	Finish (HF-A6)	0.03060 • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)
----------------	----------------	--------------------	------------	------------------------	----------------------------------	----------------------------

## Siding, R-3 insulation, interior finish

U-Value: 0.9482 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-3 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-3 insulation, filled core, interior finish

U-Value: 0.7464 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-3 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-4 insulation, interior finish

U-Value: 0.8119 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-4 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-4 insulation, filled core, interior finish

U-Value: 0.6643 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-4 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)

°K)						
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-5 insulation, interior finish

U-Value: 0.7097 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-5 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-5 insulation, filled core, interior finish

U-Value: 0.5961 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-5 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-6 insulation, interior finish

U-Value: 0.6302 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-6 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Siding, R-6 insulation, filled core, plus interior finish

U-Value: 0.5394 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-6 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-6 insulation	R-6 insulation	1.05666 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W		0.012710 m • °K)	0.415376 W/(m kg/m <sup>3</sup>	1249.560000 J/(kg • °K)

## Siding, R-10 insulation, interior finish

U-Value: 0.4372 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-10 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10 insulation	R-10 insulation	1.76110 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W		0.012710 m	0.415376 W/(m kg/m <sup>3</sup>	1249.560000 J/(kg • °K)

## Siding, R-10 insulation, filled core, interior finish

U-Value: 0.3917 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-10 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-10 insulation	R-10 insulation	1.76110 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W		0.012710 m	0.415376 W/(m kg/m <sup>3</sup>	1249.560000 J/(kg • °K)

## Siding, R-15 insulation, interior finish

U-Value: 0.3179 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-15 board insulation, open core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W		0.012710 m	0.415376 W/(m kg/m <sup>3</sup>	1249.560000 J/(kg • °K)

## Siding, R-15 insulation, filled core, interior finish

U-Value: 0.2895 W/(m<sup>2</sup> • °K)

Block, stucco or siding, R-15 board insulation, filled core, plus interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.641165 °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-2 insulation

U-Value: 0.5507 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-2 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-2 insulation, filled

U-Value: 0.4769 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-2 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-3 insulation

U-Value: 0.5053 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-3 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)

°K)						
R-11 insulation	R-11 insulation	1.93721 °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-3 insulation, filled

U-Value: 0.4428 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-3 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-4 insulation

U-Value: 0.4655 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-4 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-4 insulation, filled

U-Value: 0.4088 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-4 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-

°K)/W						
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> )	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-5 insulation

U-Value: 0.4258 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-5 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W		- -	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W		- -	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup> )	0.012710 m		1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-11 plus R-5 insulation, filled

U-Value: 0.3804 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-11 stud cavity, R-5 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-11 insulation	R-11 insulation	1.93721 (m <sup>2</sup> • °K)/W		- -	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W		- -	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup> )	0.012710 m		1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-15 plus R-2 insulation

U-Value: 0.5053 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-15 stud cavity, R-2 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W		- -	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W		- -	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup> )	0.012710 m		1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-15 plus R-2 insulation, filled

U-Value: 0.4428 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-15 stud cavity, R-2 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W		-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup>		0.012710 m	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-15 plus R-3 insulation

U-Value: 0.4655 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-15 stud cavity, R-3 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W		-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup>		0.012710 m	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-15 plus R-3 insulation, filled

U-Value: 0.4144 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-15 stud cavity, R-3 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m <sup>2</sup> • °K)/W		-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup>		0.012710 m	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-15 plus R-4 insulation

U-Value: 0.4315 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-15 stud cavity, R-4 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m³	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W		-	-	-
R-4 insulation	R-4 insulation	0.70444 (m² • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m² • °K)/W		0.012710 m	0.415376 W/(m² • °K)	1249.560000 kg/m³

## Block, interior/exterior finish, R-15 plus R-4 insulation, filled

U-Value: 0.3861 W/(m² • °K)

Block, any exterior finish, R-15 stud cavity, R-4 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m³	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W		-	-	-
R-4 insulation	R-4 insulation	0.70444 (m² • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m² • °K)/W		0.012710 m	0.415376 W/(m² • °K)	1249.560000 kg/m³

## Block, interior/exterior finish, R-15 plus R-5 insulation

U-Value: 0.3974 W/(m² • °K)

Block, any exterior finish, R-15 stud cavity, R-5 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m³	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 (m² • °K)/W		-	-	-
R-5 insulation	R-5 insulation	0.88055 (m² • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m² • °K)/W		0.012710 m	0.415376 W/(m² • °K)	1249.560000 kg/m³

## Block, interior/exterior finish, R-15 plus R-5 insulation, filled

U-Value: 0.3577 W/(m² • °K)

Block, any exterior finish, R-15 stud cavity, R-5 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m³	1000 J/(kg • °K)

1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-15 insulation	R-15 insulation	2.64165 °K)/W	-	-	-	-
R-5 insulation	R-5 insulation	0.88055 °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-2 insulation

U-Value: 0.4712 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-2 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-2 insulation, filled

U-Value: 0.4144 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-2 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-2 insulation	R-2 insulation	0.35222 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)/W	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-3 insulation

U-Value: 0.4315 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-3 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-

R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6)	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-3 insulation, filled

U-Value: 0.3861 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-3 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-3 insulation	R-3 insulation	0.52833 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-4 insulation

U-Value: 0.4031 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-4 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-4 insulation, filled

U-Value: 0.3633 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-4 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W	-	-	-	-
R-4 insulation	R-4 insulation	0.70444 (m <sup>2</sup> • °K)/W	-	-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m • °K)	0.03060 (m <sup>2</sup> • °K)/W	0.012710 m	0.415376 W/(m • °K)	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-5 insulation

U-Value: 0.3747 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-5 board, open core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W		-	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup>		0.012710 m	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Block, interior/exterior finish, R-21 plus R-5 insulation, filled

U-Value: 0.3406 W/(m<sup>2</sup> • °K)

Block, any exterior finish, R-21 stud cavity, R-5 board, filled core, interior finish [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Concrete block (dense)	Concrete block (dense)	-	0.200 m	1.63 W/(m • °K)	2300 kg/m <sup>3</sup>	1000 J/(kg • °K)
1 in stucco	1 in (25 mm) stucco	-	0.0254 m	0.72 W/(m • °K)	1856 kg/m <sup>3</sup>	840 J/(kg • °K)
R-21 insulation	R-21 insulation	3.69831 (m <sup>2</sup> • °K)/W		-	-	-
R-5 insulation	R-5 insulation	0.88055 (m <sup>2</sup> • °K)/W		-	-	-
Finish (HF-A6)	Finish (HF-A6) 0.415376 W/(m	0.03060 (m <sup>2</sup>		0.012710 m	1249.560000 kg/m <sup>3</sup>	1088.568000 J/(kg • °K)

## Light-weight plaster, brick, light-weight plaster

U-Value: 1.75 W/(m<sup>2</sup> • °K)

1/2 in (12 mm) lightweight plaster 4 in (100 mm) brick, 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in brick	4 in (100 mm) brick	-	0.105 m	0.72 W/(m • °K)	1920 kg/m <sup>3</sup>	840 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Light-weight plaster, concrete block, light-weight plaster

U-Value: 1.05 W/(m<sup>2</sup> • °K)

1/2 in (12 mm) lightweight plaster, 4 in (100 mm) lightweight concrete block, 1/2 in (12 mm) lightweight plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

°K)						
Lightweight aggregate concrete block	Lightweight aggregate concrete block	-	0.100 m	0.19 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)
Plaster (lightweight)	Plaster (lightweight)	-	0.013 m	0.16 W/(m • °K)	600 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Plasterboard, timber studding, plasterboard

U-Value: 1.75 W/(m<sup>2</sup> • °K)

1/2 in (12 mm) plasterboard, timber studding, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
Timber studding	Timber studding	-	0.095 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Doors

Wooden		U-Value: 2.1944 W/(m² • °K)				
Wooden door						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Metal		U-Value: 3.7021 W/(m² • °K)				
Metal door						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
Timber flush-panel hollow-core		U-Value: 2.3256 W/(m² • °K)				
Timber flush-Panel hollow-core door (normally hung)						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
Solid hardwood		U-Value: 2.5572 W/(m² • °K)				
Solid Hardwood door (normally hung)						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
Hollow core wood		U-Value: 3.1796 W/(m² • °K)				
Hollow core wood [Source: CIBSE]						

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m² • °K)/W	-	-	-	-
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)

## Door - wood - hollow core - wood storm

U-Value: 1.8737 W/(m² • °K)

Door - wood - hollow core - wood storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m² • °K)/W	-	-	-	-
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)

## Hollow core wood, metal storm

U-Value: 2.0441 W/(m² • °K)

Hollow core wood, metal storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m² • °K)/W	-	-	-	-
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m³	1210 J/(kg • °K)

## Solid core wood

U-Value: 2.6119 W/(m² • °K)

Solid core wood [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## Solid core wood, wood storm

U-Value: 1.6466 W/(m² • °K)

Solid core wood, wood storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## Solid core wood, metal storm

U-Value: 1.8170 W/(m<sup>2</sup> • °K)

Solid core wood, metal storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## Wood panel

U-Value: 3.8042 W/(m<sup>2</sup> • °K)

Wood panel [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## Wood panel with wood storm

U-Value: 2.0440 W/(m<sup>2</sup> • °K)

Wood panel with wood storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## Wood panel, metal storm

U-Value: 2.3279 W/(m<sup>2</sup> • °K)

Wood panel, metal storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 1/2 in wood	1 1/2 in (40 mm) wood	-	0.0376 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## Metal, fiberglass core

U-Value: 3.3500 W/(m<sup>2</sup> • °K)

Metal, fiberglass core [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Metal, fiberglass core, storm

U-Value: 2.0838 W/(m<sup>2</sup> • °K)

Metal with fiberglass core and storm door [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard	1/2 in (12 mm) fiberboard	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300

sheathing	sheathing					J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

## Wood frame with single clear glass

Wood frame with single clear glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## Metal frame with single clear glass

Metal frame with single clear glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## Wood frame, single glass door, glass storm

Wood frame, single glass door, glass storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## Metal frame, single glass door, glass storm

Metal frame, single glass door, glass storm [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## Wood frame, double glass door

Wood frame, double glass door [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528	880 J/(kg

glass		kg/m <sup>3</sup>	• °K)
-------	--	-------------------	-------

Metal frame, double glass door		U-Value: 4.1165 W/(m <sup>2</sup> • °K)				
Metal frame, double glass door [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

  

Wood frame, double/triple glass, glass storm		U-Value: 1.9361 W/(m <sup>2</sup> • °K)				
Wood frame, double/triple glass, glass storm [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

  

Metal frame, double/triple glass, glass storm		U-Value: 2.7822 W/(m <sup>2</sup> • °K)				
Metal frame, double/triple glass, glass storm [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

  

French door, wood frame with single glass		U-Value: 5.3089 W/(m <sup>2</sup> • °K)				
French door, wood frame with single clear glass [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

  

French door, metal frame with single glass		U-Value: 6.8703 W/(m <sup>2</sup> • °K)				
French door, metal frame with single clear glass [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## French door, wood frame with double glass

U-Value: 2.9639 W/(m<sup>2</sup> • °K)

French door, wood frame with double glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## French door, metal frame with double glass

U-Value: 4.2812 W/(m<sup>2</sup> • °K)

French door, metal frame with double glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## French door, wood frame with triple glass

U-Value: 2.1065 W/(m<sup>2</sup> • °K)

French door, wood frame with triple glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
5/8 in plywood	5/8 in (16 mm) plywood	-	0.0159 m	0.12 W/(m • °K)	544 kg/m <sup>3</sup>	1210 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

## French door, metal frame with triple glass

U-Value: 3.3216 W/(m<sup>2</sup> • °K)

French door, metal frame with triple glass [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Opaque spandrel glass	Opaque spandrel glass	-	0.0064 m	0.99 W/(m • °K)	2528 kg/m <sup>3</sup>	880 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Roofs

Flat roof - A			U-Value: 0.2497 W/(m <sup>2</sup> • °K)			
Flat roof						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K/W)	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> °K/W)	-	-	-	-

  

Flat roof - B			U-Value: 0.2277 W/(m <sup>2</sup> • °K)			
Flat roof						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K/W)	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K/W)	-	-	-	-
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m <sup>3</sup>	590 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> °K/W)	-	-	-	-

  

Flat roof - C			U-Value: 0.3183 W/(m <sup>2</sup> • °K)			
Flat roof						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K/W)	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)

U-Value: 0.1589 W/(m² • °K)						
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m² • °K)/W	-	-	-	-

## Sloping roof including loft

Sloping roof including loft

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m² • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m³	1460 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m³	590 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m² • °K)/W	-	-	-	-

## Sloping roof including loft

Sloping roof including loft

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m² • °K)/W	-	-	-	-
Wood shingles	Wood shingles	-	0.0064 m	0.04 W/(m • °K)	592 kg/m³	1300 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m² • °K)/W	-	-	-	-

## Lightweight curtain roof

Lightweight curtain roof

U-Value: 0.2487 W/(m² • °K)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K)/W	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> °K)/W	-	-	-	-

## Lightweight curtain roof

U-Value: 0.2392 W/(m<sup>2</sup> • °K)

Lightweight curtain roof

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> °K)/W	-	-	-	-
Slate or tile	Slate or tile	-	0.0127 m	1.59 W/(m • °K)	1920 kg/m <sup>3</sup>	1260 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> °K)/W	-	-	-	-

## Sloping roof - domestic

U-Value: 3.3775 W/(m<sup>2</sup> • °K)

Sloping roof - domestic

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls 1256.040000	0.15392 (m <sup>2</sup> °K)/W	0.017769 m	0.115440 W/(m 512.640000)	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ - 2x4 frame	Batt, R-13 including framing	1.62550 (m <sup>2</sup> °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Un-insulated flat roof		U-Value: 1.5583 W/(m <sup>2</sup> • °K)				
Un-insulated flat roof						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Wood shingle (WS01)	For walls	0.15392 (m <sup>2</sup> • °K)/W	0.017769 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1256.040000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R13 w/ 2x4 frame	Batt, R-13 including framing factor	1.62550 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

  

Super-insulated flat roof		U-Value: 0.1769 W/(m <sup>2</sup> • °K)				
Super-insulated flat roof						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)

Roof terrace system		U-Value: 0.4694 W/(m <sup>2</sup> • °K)				
Roof terrace system						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

Roof terrace system		U-Value: 1.3824 W/(m <sup>2</sup> • °K)				
Roof terrace system						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-

Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Steel sheet with 2 in insulation

U-Value: 0.5343 W/(m<sup>2</sup> • °K)

Steel sheet with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Steel sheet with 1 in insulation

U-Value: 0.5343 W/(m<sup>2</sup> • °K)

Steel sheet with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Steel sheet with 2 in insulation

U-Value: 0.7254 W/(m<sup>2</sup> • °K)

Steel sheet with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

Steel sheet with 1 in insulation			U-Value: 1.2694 W/(m <sup>2</sup> • °K)			
Steel sheet with 1 in (25 mm) insulation						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ 2x4 frame	Batt, R-11 including framing factor	1.54096 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

  

Steel sheet with 4 in insulation			U-Value: 0.3275 W/(m <sup>2</sup> • °K)			
Steel sheet with 4 in (100 mm) insulation						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> • °K)/W	-	-	-	-
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m <sup>3</sup>	590 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

Steel sheet with 8 in insulation			U-Value: 0.1846 W/(m <sup>2</sup> • °K)			
Steel sheet with 8 in (200 mm) insulation						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Steel sheet with 12 in insulation

U-Value: 0.1286 W/(m<sup>2</sup> • °K)

Steel sheet with 12 in (300 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## Stone chipping, asphalt, screed, heavy concrete block

U-Value: 2.5405 W/(m<sup>2</sup> • °K)

1 in (25 mm) stone chipping 3/4 in (19 mm) asphalt 1 1/2 in (40 mm) screed 6 in (150 mm) concrete block (heavy)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in stone	1 in (25 mm) stone	-	0.0254 m	3.17 W/(m • °K)	2560 kg/m <sup>3</sup>	790 J/(kg • °K)
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Stone chipping, asphalt, screed, light concrete block

U-Value: 0.9165 W/(m<sup>2</sup> • °K)

1 in (25 mm) stone chipping 3/4 in (19 mm) asphalt 1 1/2 in (40 mm) screed 6 in (150 mm) concrete block (light)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in stone	1 in (25 mm) stone	-	0.0254 m	3.17 W/(m • °K)	2560 kg/m <sup>3</sup>	790 J/(kg • °K)
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Asphalt, screed, dense cast concrete, dense plaster

U-Value: 2.0240 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 3 in (75 mm) screed 6 in (150 mm) cast concrete (dense) 1/2 in (12 mm) plaster (dense)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m³	920 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m³	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m³	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)

## Asphalt, aerated concrete slab, dense plaster

U-Value: 0.8760 W/(m² • °K)

3/4 in (19 mm) asphalt 6 in (150 mm) Aerated concrete slab 1/2 in (12 mm) plaster (dense)

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m³	920 J/(kg • °K)
Autoclaved Aerated concrete block (density 500)	Autoclaved Aerated concrete block (density 500)	-	0.150 m	0.18 W/(m • °K)	500 kg/m³	1050 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m³	1000 J/(kg • °K)

## Asphalt, fiberboard, aced, air, aced

U-Value: 1.5867 W/(m² • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 3/8 in (10 mm) aced 1 in (25 mm) air 3/8 in (10 mm) aced

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m³	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
Slate or tile	Slate or tile	-	0.0127 m	1.59 W/(m • °K)	1920 kg/m³	1260 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m² - or no construction)		-	-	-
Slate or tile	Slate or tile	-	0.0127 m	1.59 W/(m • °K)	1920 kg/m³	1260 J/(kg • °K)

## Asphalt, fiberboard, gypsum

U-Value: 1.3207 W/(m² • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 1 in (25 mm) air 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m³	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m² - or no construction)		-	-	-
GypBd 1/2 in (GP01) m	GypBd 1/2 in (1.3 cm)	0.07931 (m² - or no construction)	0.012710	0.160266 W/(m • °K)	801.000000 kg/m³	837.360000 J/(kg • °K)

## Asphalt, fiberboard, 1 in batting, gypsum

U-Value: 0.7923 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 1 in (25 mm) air 1 in (25 mm) batt 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m <sup>2</sup> - or no construction	-	• °K)/W	-	-
R-30, 9 1/2 in batt insulation	R-30, 9 1/2 in (240 mm) batt insulation	-	0.2438 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 837.360000	0.07931 (m <sup>2</sup>	-	0.012710 m	0.160266 W/(m 801.000000	-

## Asphalt, fiberboard, 2 in batting, gypsum

U-Value: 0.5299 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 1 in (25 mm) air 2 in (50 mm) batt 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m <sup>2</sup> - or no construction	-	• °K)/W	-	-
Minwool batt R7	Batt, R-7 5.74 cm 837.360000	1.32571 (m <sup>2</sup>	-	0.057361 m	0.043268 W/(m 9.612000	-
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 837.360000	0.07931 (m <sup>2</sup>	-	0.012710 m	0.160266 W/(m 801.000000	-

## 3/4 in asphalt 1/2 in fiberboard 1 in air 3 in batt 3/8 in gyp.

U-Value: 0.3981 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 1 in (25 mm) air 3 in (75 mm) batt 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
Air space	Air space proxy for air wall	0.10919 (m <sup>2</sup> - or no construction	-	• °K)/W	-	-
R-11, 3 1/2 in batt insulation	R-11, 3 1/2 in (87 mm) batt insulation	-	0.0894 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 837.360000	0.07931 (m <sup>2</sup>	-	0.012710 m	0.160266 W/(m 801.000000	-

## 3/4 in asphalt 1/2 in fiberboard 2 in EPS slab 1 in air 3/8 in gyp.

U-Value: 0.7399 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 2 in (50 mm) EPS slab 1 in (25 mm) air 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### 3/4 in asphalt 1/2 in fiberboard 2 in EPS slab 1 in air 3/8 in gyp.

U-Value: 0.4841 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) fiberboard 2 in (50 mm) EPS slab 1 in (25 mm) air 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
2 in Expanded polystyrene (EPS)	2 in (50 mm) Expanded polystyrene (EPS)	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### 3/4 in asphalt 1/2 in screed 2 in wood wool slab 1 in air 3/8 in gyp.

U-Value: 1.0502 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) asphalt 1/2 in (12 mm) screed 2 in (50 mm) wood wool slab 1 in (25 mm) air 3/8 in (10 mm) gyp.

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

### 3/4 in felt / bitumen 1 in EPS slab 1/8 in metal deck

U-Value: 1.1206 W/(m<sup>2</sup> • °K)

3/4 in (19 mm) felt / bitumen 1 in (25 mm) EPS slab 1/8 in (3 mm) metal deck

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Poured asphalt	Poured asphalt	-	0.019 m	1.20 W/(m • °K)	2100 kg/m <sup>3</sup>	920 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Air space	Air space proxy for air wall or no construction	0.10919 (m <sup>2</sup> • °K)/W	-	-	-	-

GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 • °K)/W	0.012710 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
---------------------	-----------------------	--------------------	------------	------------------------	---------------------------------	---------------------------

4 in wood with 2 in insulation		U-Value: 0.3688 W/(m <sup>2</sup> • °K)				
--------------------------------	--	---	--	--	--	--

4 in (100 mm) wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

2 1/2 in wood with 2 in insulation		U-Value: 0.6746 W/(m <sup>2</sup> • °K)				
------------------------------------	--	---	--	--	--	--

2 1/2 in wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

4 in wood with 2 in insulation		U-Value: 0.8566 W/(m <sup>2</sup> • °K)				
--------------------------------	--	---	--	--	--	--

4 in (100 mm) wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

4 in wood with 1 in insulation		U-Value: 0.4716 W/(m <sup>2</sup> • °K)				
--------------------------------	--	---	--	--	--	--

4 in (100 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

2 1/2 in wood with 1 in insulation		U-Value: 0.5538 W/(m <sup>2</sup> • °K)				
------------------------------------	--	---	--	--	--	--

2 1/2 in (65 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## 1 in wood with 1 in insulation

1 in (25 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## 8 in lightweight concrete

8 in (200 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 6 in lightweight concrete

6 in (150 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in lightweight concrete	6 in (150 mm) lightweight concrete	-	0.1524 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in lightweight concrete

4 in (100 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 6 in heavyweight concrete with 2 in insulation

6 in (150 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with 2 in insulation

U-Value: 0.5181 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 2 in heavyweight concrete with 2 in insulation

U-Value: 0.5261 W/(m<sup>2</sup> • °K)

2 in (50 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 6 in heavyweight concrete with 1 in insulation

U-Value: 0.7305 W/(m<sup>2</sup> • °K)

6 in (150 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with 1 in insulation

U-Value: 0.7465 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 2 in heavyweight concrete with 1 in

U-Value: 0.7632 W/(m<sup>2</sup> • °K)

## insulation

2 in (50 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 4 in wood with 2 in insulation

U-Value: 0.4508 W/(m² • °K)

4 in (100 mm) wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## 2 1/2 in wood with 2 in insulation

U-Value: 0.5254 W/(m² • °K)

2 1/2 in (65 mm) wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## 1 in wood with 2 in insulation

U-Value: 0.6296 W/(m² • °K)

1 in (25 mm) wood with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## 4 in wood with 1 in insulation

U-Value: 0.6145 W/(m² • °K)

4 in (100 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-5, 1 in insulation	R-5, 1 in (25 mm) insulation	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

board	board					°K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## 2 1/2 in wood with 1 in insulation

U-Value: 0.7619 W/(m<sup>2</sup> • °K)

2 1/2 in (65 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## 1 in wood with 1 in insulation

U-Value: 1.0023 W/(m<sup>2</sup> • °K)

1 in (25 mm) wood with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

## 8 in lightweight concrete

U-Value: 0.7291 W/(m<sup>2</sup> • °K)

8 in (200 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 6 in lightweight concrete

U-Value: 0.9277 W/(m<sup>2</sup> • °K)

6 in (150 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in lightweight concrete	6 in (150 mm) lightweight concrete	-	0.1524 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)

## 4 in lightweight concrete

U-Value: 1.2750 W/(m<sup>2</sup> • °K)

4 in (100 mm) lightweight concrete

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in brick	4 in (100 mm) brick	-	0.1016 m	0.89 W/(m • °K)	1920 kg/m <sup>3</sup>	790 J/(kg • °K)

## 6 in heavyweight concrete with 2 in insulation

U-Value: 0.6819 W/(m<sup>2</sup> • °K)

6 in (150 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with 2 in insulation

U-Value: 0.6958 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 2 in heavyweight concrete with 2 in insulation

U-Value: 0.7103 W/(m<sup>2</sup> • °K)

2 in (50 mm) heavyweight concrete with 2 in (50 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 6 in heavyweight concrete with 1 in insulation

U-Value: 1.1418 W/(m<sup>2</sup> • °K)

6 in (150 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

## 4 in heavyweight concrete with 1 in insulation

U-Value: 1.1814 W/(m<sup>2</sup> • °K)

4 in (100 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)

6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 2 in heavyweight concrete with 1 in insulation

U-Value: 1.2238 W/(m² • °K)

2 in (50 mm) heavyweight concrete with 1 in (25 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-5, 1 in insulation board	R-5, 1 in (25 mm) insulation board	-	0.0254 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 2 in heavyweight concrete with 4 in insulation

U-Value: 0.3244 W/(m² • °K)

2 in (50 mm) heavyweight concrete with 4 in (100 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 4 in heavyweight concrete with 4 in insulation

U-Value: 0.3214 W/(m² • °K)

4 in (100 mm) heavyweight concrete with 4 in (100 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 6 in heavyweight concrete with 4 in insulation

U-Value: 0.3184 W/(m² • °K)

6 in (150 mm) heavyweight concrete with 4 in (100 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 6 in heavyweight concrete with 6 in insulation

U-Value: 0.2314 W/(m² • °K)

6 in (150 mm) heavyweight concrete with 6 in (150 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 6 in heavyweight concrete with 9 in insulation

U-Value: 0.1641 W/(m² • °K)

6 in (150 mm) heavyweight concrete with 9 in (225 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 6 in heavyweight concrete with 12 in insulation

U-Value: 0.1271 W/(m² • °K)

6 in (150 mm) heavyweight concrete with 12 in (300 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m³	900 J/(kg • °K)

## 4 in wood with 4 in insulation

U-Value: 0.2569 W/(m² • °K)

4 in (100 mm) wood with 4 in (100 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## 4 in wood with 8 in insulation

U-Value: 0.1599 W/(m² • °K)

4 in (100 mm) wood with 8 in (200 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## 4 in wood with 12 in insulation

U-Value: 0.1160 W/(m² • °K)

4 in (100 mm) wood with 12 in (300 mm) insulation

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)
4 in wood	4 in (100 mm) wood	-	0.1016 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)

## Concrete ballast, membrane, sheathing, insulation, metal deck

U-Value: 0.297 W/(m<sup>2</sup> • °K)

2 in (50 mm) concrete roof ballast, membrane, sheathing, R-15 insulation board, metal deck [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
2 in lightweight concrete roof ballast	2 in (50 mm) lightweight concrete roof ballast	-	0.0508 m	0.19 W/(m • °K)	640 kg/m <sup>3</sup>	840 J/(kg • °K)
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Asphalt shingles, wood sheathing, R-19 batt insulation, gyp board

U-Value: 0.235 W/(m<sup>2</sup> • °K)

Asphalt shingles, wood sheathing, R-19 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Asphalt shingles	Asphalt shingles	-	0.0032 m	0.04 W/(m • °K)	1120 kg/m <sup>3</sup>	1260 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m <sup>2</sup> • °K)/W	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m <sup>3</sup>	1090 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Slate or tile, wood sheathing, R-19 batt insulation, gyp board

U-Value: 0.239 W/(m<sup>2</sup> • °K)

Slate or tile, wood sheathing, R-19 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Slate or tile	Slate or tile	-	0.0127 m	1.59 W/(m • °K)	1920 kg/m <sup>3</sup>	1260 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)

							°K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 • °K)/W	-	-	-	-	
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)	
Ceiling air space resistance	Ceiling air space resistance	0.18000 • °K)/W	-	-	-	-	
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)	
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 • °K)/W	-	-	-	-	

## Wood shingles, wood sheathing, R-19 batt insulation, gyp board

U-Value: 0.231 W/(m² • °K)

Wood shingles, wood sheathing, R-19 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m²	-	-	-	-
Wood shingles	Wood shingles	-	0.0064 m	0.04 W/(m • °K)	592 kg/m³	1300 J/(kg • °K)
1 in wood	1 in (25 mm) wood	-	0.0254 m	0.15 W/(m • °K)	608 kg/m³	1630 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m²	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m²	-	-	-	-
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m²	-	-	-	-

## Metal roof, R-19 batt insulation, gyp board

U-Value: 0.249 W/(m² • °K)

Metal roof, R-19 batt insulation, gyp board [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface (m² resistance)	Outside surface resistance	0.04000 • °K)/W	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
Ceiling air space (m² resistance)	Ceiling air space resistance	0.18000 • °K)/W	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
5/8 in gyp board	5/8 in (16 mm) gyp board	-	0.0159 m	0.16 W/(m • °K)	800 kg/m³	1090 J/(kg • °K)
Inside horizontal (m² surface resistance)	Inside horizontal surface resistance	0.16000 • °K)/W	-	-	-	-

Metal roof, R-19 batt insulation, suspended acoustical ceiling			U-Value: 0.227 W/(m² • °K)			
Metal roof, R-19 batt insulation, suspended acoustical ceiling [Source: ASHRAE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m² °K)	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m² °K)	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m² °K)	-	-	-	-
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m³	590 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m² °K)	-	-	-	-

  

Metal roof, R-19 batt insulation			U-Value: 0.255 W/(m² • °K)			
Metal roof, R-19 batt insulation [Source: ASHRAE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface resistance	Outside surface resistance	0.04000 (m² °K)	-	-	-	-
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m³	500 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m² °K)	-	-	-	-
R-19, 6 1/4 in batt insulation	R-19, 6 1/4 in (155 mm) batt insulation	-	0.1544 m	0.05 W/(m • °K)	19 kg/m³	960 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m² °K)	-	-	-	-

  

Membrane, sheathing, R-10 insulation board, wood deck			U-Value: 0.393 W/(m² • °K)			
Membrane, sheathing, R-10 insulation board, wood deck [Source: ASHRAE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m² °K)	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m³	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m³	1300 J/(kg • °K)
R-10, 2 in insulation	R-10, 2 in (50 mm)	-	0.0508 m	0.03 W/(m • °K)	43 kg/m³	1210 J/(kg • °K)

board	insulation board					°K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Membrane, sheathing, R-10 insulation, wood deck, suspended ceiling

U-Value: 0.329 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-10 insulation board, wood deck, suspended acoustical ceiling [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
2 in wood	2 in (50 mm) wood	-	0.0508 m	0.15 W/(m • °K)	608 kg/m <sup>3</sup>	1630 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m <sup>2</sup> • °K)/W	-	-	-	-
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m <sup>3</sup>	590 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Membrane, sheathing, R-10 insulation board, metal deck

U-Value: 0.452 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-10 insulation board, metal deck [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m • °K)	7824 kg/m <sup>3</sup>	500 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Membrane, sheathing, R-10 insulation, metal deck, suspended ceiling

U-Value: 0.370 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-10 insulation board, metal deck, suspended acoustical ceiling [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-

resistance		$\cdot \text{ }^{\circ}\text{K}/\text{W}$				
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	1120 kg/m <sup>3</sup>	1460 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	400 kg/m <sup>3</sup>	1300 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	43 kg/m <sup>3</sup>	1210 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	7824 kg/m <sup>3</sup>	500 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Ceiling air space resistance	Ceiling air space resistance	0.18000 (m <sup>2</sup> $\cdot \text{ }^{\circ}\text{K})/\text{W}$		-	-	-
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	368 kg/m <sup>3</sup>	590 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> $\cdot \text{ }^{\circ}\text{K})/\text{W}$		-	-	-

## Membrane, sheathing, R-15 insulation board, metal deck

U-Value: 0.323 W/(m<sup>2</sup>  $\cdot \text{ }^{\circ}\text{K}$ )

Membrane, sheathing, R-15 insulation board, metal deck [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> $\cdot \text{ }^{\circ}\text{K})/\text{W}$		-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	1120 kg/m <sup>3</sup>	1460 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	400 kg/m <sup>3</sup>	1300 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	43 kg/m <sup>3</sup>	1210 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	7824 kg/m <sup>3</sup>	500 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Inside horizontal surface - surface resistance	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> $\cdot \text{ }^{\circ}\text{K})/\text{W}$		-	-	-

## Membrane, sheathing, R-10 plus R-15 insulation boards, metal deck

U-Value: 0.206 W/(m<sup>2</sup>  $\cdot \text{ }^{\circ}\text{K}$ )

Membrane, sheathing, R-10 plus R-15 insulation boards, metal deck [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> $\cdot \text{ }^{\circ}\text{K})/\text{W}$		-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	1120 kg/m <sup>3</sup>	1460 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	400 kg/m <sup>3</sup>	1300 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
R-10, 2 in insulation board	R-10, 2 in (50 mm) insulation board	-	0.0508 m	0.03 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	43 kg/m <sup>3</sup>	1210 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	43 kg/m <sup>3</sup>	1210 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )
Metal surface	Metal surface	-	0.0008 m	45.28 W/(m $\cdot \text{ }^{\circ}\text{K}$ )	7824 kg/m <sup>3</sup>	500 J/(kg $\cdot \text{ }^{\circ}\text{K}$ )

## Membrane, sheathing, R-15 insulation, 4 in light concrete

U-Value: 0.304 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-15 insulation board, 4 in (100 mm) lightweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
4 in lightweight concrete	4 in (100 mm) lightweight concrete	-	0.1016 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.1600 (m <sup>2</sup> • °K)/W	-	-	-	-

## Membrane, sheathing, R-15 insulation, 6 in light concrete

U-Value: 0.296 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-15 insulation board, 6 in (150 mm) lightweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in lightweight concrete	6 in (150 mm) lightweight concrete	-	0.1524 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

## Membrane, sheathing, R-15 insulation, 8 in light concrete

U-Value: 0.288 W/(m<sup>2</sup> • °K)

Membrane, sheathing, R-15 insulation board, 8 in (200 mm) lightweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in lightweight concrete	8 in (200 mm) lightweight concrete	-	0.2032 m	0.53 W/(m • °K)	1280 kg/m <sup>3</sup>	840 J/(kg • °K)
Inside horizontal	Inside horizontal surface	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

surface resistance	resistance	• °K)/W
--------------------	------------	---------

<b>Membrane, sheathing, R-15 insulation, 6 in heavy concrete</b>		<b>U-Value: 0.315 W/(m<sup>2</sup> • °K)</b>
--	--	--

Membrane, sheathing, R-15 insulation board, 6 in (150 mm) heavyweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

<b>Membrane, sheathing, R-15 insulation, 8 in heavy concrete</b>		<b>U-Value: 0.313 W/(m<sup>2</sup> • °K)</b>
--	--	--

Membrane, sheathing, R-15 insulation board, 8 in (200 mm) heavyweight concrete [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
1/2 in fiberboard sheathing	1/2 in (12 mm) fiberboard sheathing	-	0.0127 m	0.07 W/(m • °K)	400 kg/m <sup>3</sup>	1300 J/(kg • °K)
R-15, 3 in insulation board	R-15, 3 in (75 mm) insulation board	-	0.0762 m	0.03 W/(m • °K)	43 kg/m <sup>3</sup>	1210 J/(kg • °K)
8 in heavyweight concrete	8 in (200 mm) heavyweight concrete	-	0.2032 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Inside horizontal	Inside horizontal surface - surface resistance	0.16000 (m <sup>2</sup> • °K)/W	-	-	-	-

<b>Membrane, concrete, R-19 insulation, suspended ceiling</b>		<b>U-Value: 0.239 W/(m<sup>2</sup> • °K)</b>
---	--	--

Membrane, 6 in (150 mm) heavyweight concrete, R-19 batt insulation, suspended acoustical ceiling [Source: ASHRAE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Outside surface	Outside surface resistance - resistance	0.04000 (m <sup>2</sup> • °K)/W	-	-	-	-
Built-up roofing	Built-up roofing	-	0.0095 m	0.16 W/(m • °K)	1120 kg/m <sup>3</sup>	1460 J/(kg • °K)
6 in heavyweight concrete	6 in (150 mm) heavyweight concrete	-	0.1524 m	1.95 W/(m • °K)	2240 kg/m <sup>3</sup>	900 J/(kg • °K)
Ceiling air space	Ceiling air space resistance - resistance	0.18000 (m <sup>2</sup> • °K)/W	-	-	-	-
R-19, 6 1/4 in batt	R-19, 6 1/4 in (155 mm)	-	0.1544 m	0.05 W/(m • °K)	19 kg/m <sup>3</sup>	960 J/(kg • °K)

insulation	batt insulation					°K)
Acoustic tile	Acoustic tile	-	0.0191 m	0.06 W/(m • °K)	368 kg/m <sup>3</sup>	590 J/(kg • °K)
Inside horizontal surface resistance	Inside horizontal surface resistance	0.16000 (m <sup>2</sup> °K)/W	-	-	-	-

## R-10 over roof deck

U-Value: 0.483402 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R10 insulation over roof deck [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-15 over roof deck

U-Value: 0.373047 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R15 insulation over roof deck [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 2 in R-7 (IN23) m	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23) m	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-19 wood framed roof

U-Value: 0.346474 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R19 wood framed roof with attic [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 w/ 2x6 frame	Batt, R-19 including framing factor	2.58530 (m <sup>2</sup> • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-20 over roof deck

U-Value: 0.256208 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R20 insulation over roof deck [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-25 over roof deck

U-Value: 0.221481 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R25 insulation over roof deck [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (0.009540 m BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23) mm	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23) mm	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-30 wood frame roof

U-Value: 0.167165 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R30 wood framed roof with attic [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-38 wood frame roof

U-Value: 0.133381 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R38 wood framed roof with attic [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
----------	-------------	---------	-----------	--------------	---------	---------------

Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)	
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-49 wood frame roof

U-Value: 0.113531 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R49 wood framed roof with attic [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R24 (IN04)	Batt, R-24 21.24 cm	4.90906 (m <sup>2</sup> • °K)/W	0.212405 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-60 wood frame roof

U-Value: 0.085740 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R60 wood framed roof with attic [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-30 over roof deck

U-Value: 0.174291 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R30 insulation over roof deck [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.834372 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-15 over roof deck - cool roof

U-Value: 0.373047 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R15 insulation over roof deck with reflective coating [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.162516 W/(m (BR01))	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m • °K)	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm) 0.041538 W/(m)	1.22317 (m <sup>2</sup> )	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm) 0.041538 W/(m)	1.22317 (m <sup>2</sup> )	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01))	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m • °K)	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-20 over roof deck - cool roof

U-Value: 0.256208 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R20 insulation over roof deck-Cool roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.162516 W/(m (BR01))	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m • °K)	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.115440 W/(m (WD01))	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m • °K)	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-18.7 over roof deck

U-Value: 0.303780 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R18.7 insulation over roof deck [Source: CIBSE]

Material	Description	R-	Thickness	Conductivity	Density	Specific
----------	-------------	----	-----------	--------------	---------	----------

Value						Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-30 over roof deck - cool roof

U-Value: 0.174291 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R30 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-18.7 over roof deck - cool roof

U-Value: 0.303780 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R18.7 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-38 over roof deck

U-Value: 0.148155 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R38 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup>	0.009540	0.162516 W/(m	1121.400000	1465.380000

(BR01)			• °K)/W	• °K)	kg/m <sup>3</sup>	J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 7/8 in R-3 (N21)	R-3.0 MinBd 7/8 in (2.2 cm)	0.53491 • °K)/W	0.022219 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 7/8 in R-3 (N21)	R-3.0 MinBd 7/8 in (2.2 cm)	0.53491 • °K)/W	0.022219 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-38 over roof deck-cool roof

U-Value: 0.148155 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R38 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 3 in R-10.4 (IN24)	R-10.4 MinBd 3 in (7.6 cm)	1.83437 (m <sup>2</sup> • °K)/W	0.076196 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 7/8 in R-3 (N21)	R-3.0 MinBd 7/8 in (2.2 cm) 0.022219 m (N21)	0.53491 (m <sup>2</sup> • °K)/W	-	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 7/8 in R-3 (N21)	R-3.0 MinBd 7/8 in (2.2 cm) 0.022219 m (N21)	0.53491 (m <sup>2</sup> • °K)/W	-	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-50 over roof deck

U-Value: 0.114398 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R50 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R24	Batt, R-24 21.24 cm	4.90906	0.212405 m	0.043268 W/(m • °K)	9.612000	837.360000

(IN04)		(m <sup>2</sup> • °K)/W		• °K)	kg/m <sup>3</sup>	J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-50 over roof deck-cool roof

U-Value: 0.114398 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant continuous R50 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in	Blt-Up roof 3/8 in (1 cm) 0.009540 m (BR01)	0.05870 (m <sup>2</sup> • °K)/W	-	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R24 (IN04)	Batt, R-24 21.24 cm	4.90906 (m <sup>2</sup> • °K)/W	0.212405 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Wood Sft 3/4 in	Wood Sft 3/4 in (1.9 cm) 0.019049 m (WD01)	0.16501 (m <sup>2</sup> • °K)/W	-	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-13 wood frame roof

U-Value: 0.386977 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 wood framed roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Cellulose 3 1/2 in R-13 (IN13)	Cellulose 3 1/2 in (8.9 cm)	2.28304 (m <sup>2</sup> • °K)/W	0.088906 m	0.038942 W/(m • °K)	48.060000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-22 wood frame roof

U-Value: 0.233288 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R22 wood framed roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 (IN02)	Batt, R-11 9.01 cm	2.08295 (m <sup>2</sup> • °K)/W	0.090125 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool Fill 3 1/2 in (m <sup>2</sup> R11 (IN11))	R11 Fill, 3 1/2 in (8.9 cm)	1.90255 (m <sup>2</sup> • °K)/W	0.088906 m	0.046730 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

• °K)/W	• °K)	kg/m <sup>3</sup>	J/(kg • °K)
---------	-------	-------------------	-------------

R-26 wood frame roof		U-Value: 0.197023 W/(m <sup>2</sup> • °K)				
ASHRAE 90.1 compliant R26 wood framed roof [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Insul Bd 2 in (HF-B3)	Insul Bd 2 in (3.1 cm)	1.17637 (m <sup>2</sup> • °K)/W	0.050899 m	0.043268 W/(m • °K)	32.040000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

  

R-43 wood frame roof		U-Value: 0.123992 W/(m <sup>2</sup> • °K)				
ASHRAE 90.1 compliant R43 wood framed roof [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R11 (IN02)	Batt, R-11 9.01 cm	2.08295 (m <sup>2</sup> • °K)/W	0.090125 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

  

R-52 wood frame roof		U-Value: 0.104382 W/(m <sup>2</sup> • °K)				
ASHRAE 90.1 compliant R52 wood framed roof [Source: CIBSE]						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.68108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
---------------------	-----------------------	---------------------------------	---------------------	------------------------------	------------------------

## R-11 wood frame roof

U-Value: 0.453798 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R13 wood framed roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool Fill 3 1/2 in (m <sup>2</sup> R11 (IN11))	R11 Fill, 3 1/2 in (8.9 cm)	1.90255 (m <sup>2</sup> • °K)/W	0.088906 m	0.046730 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-15 wood frame roof

U-Value: 0.363977 W/(m<sup>2</sup> • °K)

ASHRAE 90.1 compliant R15 wood framed roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
MinBd 2 in R-7 (IN23)	R-7.0 MinBd 2 in (50 mm)	1.22317 (m <sup>2</sup> • °K)/W	0.050808 m	0.041538 W/(m • °K)	240.300000 kg/m <sup>3</sup>	711.756000 J/(kg • °K)
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-0 wood or steel frame roof

U-Value: 4.835096 W/(m<sup>2</sup> • °K)

R0 wood or steel framed roof [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	0.115440 W/(m • °K)	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)

## R-0 over roof deck

U-Value: 4.268411 W/(m<sup>2</sup> • °K)

R0 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat

Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-60 over roof deck

U-Value: 0.092384 W/(m<sup>2</sup> • °K)

R60 insulation over roof deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Minwool batt R24 (IN04)	Batt, R-24 21.24 cm	4.90906 (m <sup>2</sup> • °K)/W	0.212405 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R30 (IN05)	Batt, R-30 24.58 cm	5.6108 (m <sup>2</sup> • °K)/W	0.245809 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Wood Sft 3/4 in (WD01)	Wood Sft 3/4 in (1.9 cm)	0.16501 (m <sup>2</sup> • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)

## R-19 insulation over concret deck

U-Value: 0.286936 W/(m<sup>2</sup> • °K)

R19 insulation over concrete deck [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Blt-Up roof 3/8 in (BR01)	Blt-Up roof 3/8 in (1 cm)	0.05870 (m <sup>2</sup> • °K)/W	0.009540 m	0.162516 W/(m • °K)	1121.400000 kg/m <sup>3</sup>	1465.380000 J/(kg • °K)
Polyurethane 3 in (IN46)	Polyurethane 3 in (7.6 cm)	3.31014 (m <sup>2</sup> • °K)/W	0.076196 m	0.023019 W/(m • °K)	24.030000 kg/m <sup>3</sup>	1590.984000 J/(kg • °K)
Conc heavyweight 140lb 6 in (CC04)	Conc heavyweight 140lb 6 in (15.2 cm)	0.11622 (m <sup>2</sup> • °K)/W	0.152393 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-38 attic ceiling

U-Value: 0.136704 W/(m<sup>2</sup> • °K)

R38 over gypsum board [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-30 attic ceiling

U-Value: 0.172417 W/(m<sup>2</sup> • °K)

R30 over gypsum board [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Minwool batt R11	Batt, R-11 9.01 cm	2.08295	0.090125 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

(IN02)		(m <sup>2</sup> • °K)/W		• °K)	kg/m <sup>3</sup>	J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-45 attic ceiling

R45 over gypsum board [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Minwool batt R7 (IN01)	Batt, R-7 5.74 cm	1.3571 (m <sup>2</sup> • °K)/W	0.057361 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Minwool batt R19 (IN03)	Batt, R-19 15.57 cm	3.59813 (m <sup>2</sup> • °K)/W	0.155684 m	0.043268 W/(m • °K)	9.612000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
GypBd 3/4 in (GP03)	GypBd 3/4 in (1.9 cm)	0.11886 (m <sup>2</sup> • °K)/W	0.019049 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-11 wood frame roof

2001 title 24 compliant R11 wood framed roof with attic [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph roll roof (AR01)	Rolled roofing	0.02642 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Wood Sft 3/4 in (m <sup>2</sup> (WD01))	Wood Sft 3/4 in (1.9 cm)	0.16501 • °K)/W	0.019049 m	0.115440 W/(m • °K)	512.640000 kg/m <sup>3</sup>	1381.644000 J/(kg • °K)
Minwool batt R11 w/ (m <sup>2</sup> 2x4 frame)	Batt, R-11 including framing factor	1.54096 • °K)/W	-	-	-	-
GypBd 5/8 in (GP02)	GypBd 5/8 in (1.6 cm)	0.09908 (m <sup>2</sup> • °K)/W	0.015879 m	0.160266 W/(m • °K)	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)

## R-22 insulated panels

Structurally ins. panel (SIP) 6 1/2 in (162 mm) roof, 48 in o.c., R-22 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph siding (AR02)	Shingle and siding	0.07749 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 5 1/2 in	Polystyrene 5 1/2 in (140 - w/48 in oc SIP roof • °K)/W	3.76876 (m <sup>2</sup> mm) including SIP roof	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

	• °K)/W	• °K)	kg/m <sup>3</sup>	J/(kg • °K)
--	---------	-------	-------------------	-------------

## R-28 insulated panels

U-Value: 0.189207 W/(m<sup>2</sup> • °K)

Structurally ins. panel (SIP) roof 8 1/4 in (210 mm) thick, 48 in o.c., R-28 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph siding (AR02)	Shingle and siding	0.07749 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 7 1/4 in frame factor	Polystyrene 7 1/4 in (180 - w/48 in oc SIP roof • °K)/W	4.84303 (m <sup>2</sup> mm) including SIP roof	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## R-36 insulated panels

U-Value: 0.150576 W/(m<sup>2</sup> • °K)

Structurally ins. panel (SIP) roof 10 1/4 in (260 mm) thick, 48 in o.c., R-36 insulation [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Asph siding (AR02)	Shingle and siding	0.07749 (m <sup>2</sup> • °K)/W	-	-	-	-
Bldg paper felt (BP01)	Permeable felt	0.01057 (m <sup>2</sup> • °K)/W	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
Polystyrene 9 1/4 in frame factor	Polystyrene 9 1/4 in (230 - w/48 in oc SIP roof • °K)/W	6.19908 (m <sup>2</sup> mm) including SIP roof	-	-	-	-
Plywd 5/8 in (PW04)	Plywd 5/8 in (1.6 cm) 0.115440 W/(m)	0.13755 (m <sup>2</sup> • °K)/W	0.015879 m	544.680000 kg/m <sup>3</sup>	1214.172000 J/(kg • °K)	
GypBd 1/2 in (GP01)	GypBd 1/2 in (1.3 cm) 0.160266 W/(m)	0.07931 (m <sup>2</sup> • °K)/W	0.012710 m	801.000000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)	

## Ballast, 2 in polystyrene, screed, concrete, plaster

U-Value: 0.51 W/(m<sup>2</sup> • °K)

Ballast (chips or paving slab), 2 in (50 mm) extruded polystyrene insulation, waterproof roof covering, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Ballast (chips or paving slab)	Ballast (chips or paving slab)	-	- m	0.96 W/(m • °K)	1800 kg/m <sup>3</sup>	1000 J/(kg • °K)
Extruded polystyrene insulation	Extruded polystyrene insulation	-	0.050 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)

1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
------------------------	--------------------------------	---	---------	----------------	------------------------	------------------

## Ballast, 4 in polystyrene, screed, concrete, plaster

U-Value: 0.30 W/(m<sup>2</sup> • °K)

Ballast (chips or paving slab), 4 in (100 mm) extruded polystyrene insulation, waterproof roof covering, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Ballast (chips or paving slab)	Ballast (chips or paving slab)	-	- m	0.96 W/(m • °K)	1800 kg/m <sup>3</sup>	1000 J/(kg • °K)
4 in Extruded polystyrene insulation	4 in (100 mm) Extruded polystyrene insulation	-	0.100 m	0.035 W/(m • °K)	25 kg/m <sup>3</sup>	1400 J/(kg • °K)
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Waterproof covering, screed, cast concrete, dense plaster

U-Value: 2.05 W/(m<sup>2</sup> • °K)

Waterproof covering, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Waterproof covering, polyurethane, screed, concrete, plaster

U-Value: 0.53 W/(m<sup>2</sup> • °K)

Waterproof roof covering, 1 1/4 in (32 mm) polyurethane insulation, vapor control layer, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
1 1/4 in polyurethane insulation	1 1/4 in (32 mm) polyurethane insulation	-	0.035 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)

1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)
------------------------	--------------------------------	---	---------	----------------	------------------------	------------------

## Waterproof covering, polyurethane, screed, concrete, plaster

U-Value: 0.22 W/(m<sup>2</sup> • °K)

Waterproof roof covering, 4 in (100 mm) polyurethane insulation, vapour control layer, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in polyurethane insulation	4 in (100 mm) polyurethane insulation	-	0.100 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Waterproof covering, polyurethane, screed, concrete, plaster

U-Value: 0.12 W/(m<sup>2</sup> • °K)

Waterproof roof covering, 8 in (200 mm) polyurethane insulation, vapour control layer, 3 in (75 mm) screed, 6 in (150 mm) cast concrete, 1/2 in (12 mm) dense plaster [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in polyurethane insulation	8 in (200 mm) polyurethane insulation	-	0.200 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Screed	Screed	-	0.075 m	0.41 W/(m • °K)	1200 kg/m <sup>3</sup>	840 J/(kg • °K)
Cast concrete	Cast concrete	-	0.150 m	1.13 W/(m • °K)	2000 kg/m <sup>3</sup>	1000 J/(kg • °K)
1/2 in plaster (dense)	1/2 in (12 mm) plaster (dense)	-	0.013 m	0.5 W/(m • °K)	1300 kg/m <sup>3</sup>	1000 J/(kg • °K)

## Waterproof covering, timber decking, plasterboard

U-Value: 1.87 W/(m<sup>2</sup> • °K)

Waterproof roof covering, 3/4 in (19 mm) timber decking, ventilated airspace, vapour control layer, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
Timber decking	Timber decking	-	0.019 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Flat roof airspace	Flat roof airspace - J/(kg • °K)	0.16000 (m <sup>2</sup> )	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)

Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)
--------------	--------------	---	---------	-----------------	-----------------------	-----------------

<b>Waterproof covering, mineral fiber insulation, plasterboard</b>	<b>U-Value: 0.51 W/(m<sup>2</sup> • °K)</b>
--	---

Waterproof roof covering, 3/4 in (19 mm) timber decking, ventilated airspace, 2 in (50 mm) mineral fiber insulation, vapour control layer, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
Timber decking	Timber decking	-	0.019 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Flat roof airspace	Flat roof airspace - J/(kg • °K)	0.16000 (m <sup>2</sup> )	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Mineral fiber insulation	Mineral fiber insulation	-	0.050 m	0.035 W/(m • °K)	30 kg/m <sup>3</sup>	1000 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Waterproof covering, 1 1/4 in polyurethane, decking, plasterboard</b>	<b>U-Value: 0.52 W/(m<sup>2</sup> • °K)</b>
--	---

Waterproof roof covering, 1 1/4 in (32 mm) polyurethane insulation, vapour control layer, 3/4 in (19 mm) timber decking, unventilated airspace, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
1 1/4 in polyurethane insulation	1 1/4 in (32 mm) polyurethane insulation	-	0.035 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Timber decking	Timber decking	-	0.019 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Pitched roof airspace	Pitched roof airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> )	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

<b>Waterproof covering, 4 in polyurethane, decking, plasterboard</b>	<b>U-Value: 0.22 W/(m<sup>2</sup> • °K)</b>
--	---

Waterproof roof covering, 4 in (100 mm) polyurethane insulation, vapour control layer, 3/4 in (19 mm) timber decking, unventilated airspace, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
4 in polyurethane insulation	4 in (100 mm) polyurethane insulation	-	0.100 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Timber decking	Timber decking	-	0.019 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

Pitched roof airspace	Pitched roof airspace	0.18000 (m <sup>2</sup> )	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

## Waterproof covering, 8 in polyurethane, decking, plasterboard

U-Value: 0.12 W/(m<sup>2</sup> • °K)

Waterproof roof covering, 8 in (200 mm) polyurethane decking, insulation, vapour control layer, 3/4 in (19 mm) timber unventilated airspace, 1/2 in (12 mm) plasterboard [Source: CIBSE]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Waterproof roof covering	Waterproof roof covering	-	- m	0.19 W/(m • °K)	960 kg/m <sup>3</sup>	840 J/(kg • °K)
8 in polyurethane insulation	8 in (200 mm) polyurethane insulation	-	0.200 m	0.025 W/(m • °K)	30 kg/m <sup>3</sup>	1400 J/(kg • °K)
Vapour control layer	Vapour control layer	-	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Timber decking	Timber decking	-	0.019 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)
Pitched roof airspace	Pitched roof airspace - J/(kg • °K)	0.18000 (m <sup>2</sup> )	- m	- W/(m • °K)	- kg/m <sup>3</sup>	- J/(kg • °K)
Plasterboard	Plasterboard	-	0.012 m	0.16 W/(m • °K)	950 kg/m <sup>3</sup>	840 J/(kg • °K)

# MEP Constructions for Buildings and Spaces

## Slabs

Standard slab construction - A			U-Value: 0.2499 W/(m <sup>2</sup> • °K)			
Standard slab construction						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

Standard slab construction - B		U-Value: 0.4063 W/(m² • °K)				
Standard slab construction						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m³	1380 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m³	840 J/(kg • °K)

Solid-ground floor		U-Value: 0.4063 W/(m <sup>2</sup> • °K)				
Solid-ground floor						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m <sup>3</sup>	1380 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m <sup>3</sup>	840 J/(kg • °K)

Suspended timber floor		U-Value: 0.3857 W/(m <sup>2</sup> • °K)				
Suspended timber floor						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m <sup>3</sup>	1200 J/(kg • °K)

Industrial solid		U-Value: 0.4082 W/(m² • °K)				
Solid-ground floor - industry						
Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m³	1380 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m³	840 J/(kg • °K)

**Un-insulated solid**      U-Value: 0.7059 W/(m<sup>2</sup> • °K)

### Un-insulated Solid-ground floor

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m³	1380 J/(kg • °K)
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m³	840 J/(kg • °K)

### Un-insulated suspended timber

U-Value: 0.6278 W/(m² • °K)

#### Un-insulated Suspended timber floor

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Timber flooring	Timber flooring	-	0.1 m	0.14 W/(m • °K)	650 kg/m³	1200 J/(kg • °K)

### Super-insulated

U-Value: 0.2756 W/(m² • °K)

#### Super-insulated floor

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
Carpet	Carpet	-	0.0127 m	0.06 W/(m • °K)	288 kg/m³	1380 J/(kg • °K)
R-34 insulation	R-34 insulation	34 (m² • °K)/W	-	-	-	-
Concrete cast dense reinforced	Concrete cast dense reinforced	-	0.200 m	1.90 W/(m • °K)	2300 kg/m³	840 J/(kg • °K)

### Slab edge uninsulated

U-Value: 0.27 W/(m² • °K)

#### Slab edge uninsulated [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious insulation	Fictitious insulation place holder	5.28331 (m² • °K)/W	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 •	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 •	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)
Carpet fiber pad (CP01)	With fibrous pad	0.36631 •	-	-	-	-

### Slab edge R-5 insulation

U-Value: 0.15 W/(m² • °K)

#### Slab edge R-5 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious insulation	Fictitious insulation place holder	5.28331 (m² • °K)/W	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 •	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m³	837.360000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 •	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m³	837.360000 J/(kg • °K)
Carpet fiber pad (CP01)	With fibrous pad	0.36631 •	-	-	-	-

## Slab edge R-10 insulation

U-Value: 0.116 W/(m<sup>2</sup> • °K)

Slab edge R-10 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious insulation	Fictitious insulation place holder	5.28331 (m <sup>2</sup> • °K)	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> • °K)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Carpet fiber pad (CP01)	With fibrous pad	0.36631 (m <sup>2</sup> • °K)	-	-	-	-

## Slab edge R-15 insulation

U-Value: 0.11 W/(m<sup>2</sup> • °K)

Slab edge R-15 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious insulation	Fictitious insulation place holder	5.28331 (m <sup>2</sup> • °K)	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> • °K)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Carpet fiber pad (CP01)	With fibrous pad	0.36631 (m <sup>2</sup> • °K)	-	-	-	-

## Slab edge R-20 insulation

U-Value: 0.1 W/(m<sup>2</sup> • °K)

Slab edge R-20 insulation [Source: GBS]

Material	Description	R-Value	Thickness	Conductivity	Density	Specific Heat
UG surface fictitious insulation	Fictitious insulation place holder	5.28331 (m <sup>2</sup> • °K)	-	-	-	-
Soil 8 in	Soil 8 in (20.3 cm)	0.11799 (m <sup>2</sup> • °K)	0.204206 m	1.730735 W/(m • °K)	1842.300000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Conc heavyweight 140lb 8 in (CC05)	Conc heavyweight 140lb 8 in (20.3cm)	0.15497 (m <sup>2</sup> • °K)	0.203200 m	1.311205 W/(m • °K)	2242.800000 kg/m <sup>3</sup>	837.360000 J/(kg • °K)
Carpet fiber pad (CP01)	With fibrous pad	0.36631 (m <sup>2</sup> • °K)	-	-	-	-